



Customer information packet

EM31159

1.5HP, 1170RPM, 3PH, 60HZ, 56H, 3540M, ODP, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	ODP
Frame	56H
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	1.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CURUSEEV
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	5.200 A @ 208.0 V 5.000 A @ 230.0 V 2.500 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	84.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	2.5 a
Insulation Class	F

Part detail

Revision	G
Type	AC
Mech. spec.	35J382
Base	
Status	PRD/A
Elec. spec.	35WGG334
Layout	35LYJ382
Eff. date	10-01-2024
CD Diagram	CD0005
Poles	06
Leads	9#18
Proprietary	False
Created date	09-09-2022

Inverter Code	Not Inverter
KVA Code	L
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3540M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	14.00 IN
Power Factor	66
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1170 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3155LUA											
CAT.NO.	EM31159										
SPEC.	35J382G334G1										
HP	1.5										
VOLTS	230/460										
AMPS	5/2.5										
RPM	1170										
FRAME	56H		HZ	60			PH	3			
SF	1.15	CODE	L	DES	B	CLASS	F				
F.L. AVG. EFF.	84	PF	66								
RATING	40C AMB-CONT										
CC											
DE	6205		ODE	6203							
ENCL	ODP	SN									
USABLE AT	N/A										

AC Induction Motor Performance Data

Record # 87765

Preliminary Data Sheet

Winding: 35WGG334-R002				Type: 3540M		Enclosure: OPEN	
Nameplate Data				460 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		1.5		Full Load Torque		6.78 LB-FT	
Volts		230/460		Start Configuration		direct on line	
Full Load Amps		5/2.5		Breakdown Torque		24.05 LB-FT	
R.P.M.		1170		Pull-up Torque		13.05 LB-FT	
Hz	60	Phase	3	Locked-rotor Torque		15.2 LB-FT	
NEMA Design Code		B	KVA Code	L	Starting Current		15.6 A
Service Factor (S.F.)		1.15		No-load Current		1.66 A	
NEMA Nom. Eff.		84	Power Factor	66	Line-line Res. @ 25°C		10.6 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		69°C	
S.F. Amps		5.6/2.8		Temp. Rise @ S.F. Load		82°C	
				Locked-rotor Power Factor		43.7	
				Rotor inertia		0.29 lb-ft²	

Load Characteristics 460 V, 60 Hz, 1.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	29	45	57	66	72	75	70
Efficiency	72.7	81.1	83.6	83.7	82.9	81.1	83.2
Speed	1193	1186	1179	1171	1162	1152	1166
Line amperes	1.72	1.9	2.19	2.55	2.96	3.45	2.8

ABB Motors and Mechanical Inc.

WINDING # 35WGG334

Typical performance - not guaranteed values.

1.5 HP 3 PH 60 HZ 1170 RPM 460 V 3540M

TORQUES (LB-FT): PO=24.05 PU=13.05 LR=15.2 LRA=15.6





