



Customer information packet

EM3702T

2HP, 865RPM, 3PH, 60HZ, 213T, 3732M, TEFC, F1, N

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	213T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	2.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	900 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	3.500 A @ 460.0 V 7.000 A @ 230.0 V 7.200 A @ 208.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	84.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater

Part detail

Revision	J
Type	AC
Mech. spec.	37G813
Base	
Status	PRD/A
Elec. spec.	37WGS277
Layout	37LYG813
Eff. date	12-18-2025
CD Diagram	CD0005
Poles	08
Leads	9#14
Proprietary	False
Created date	04-07-2015

High Voltage Full Load Amps	3.5 a
Insulation Class	F
Inverter Code	Not Inverter
IP Rating	NONE
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 14 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3732M
Mounting Arrangement	F1
Number of Poles	8
Overall Length	17.89 IN
Power Factor	62
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.375 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	865 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None

Winding Thermal 2

None

Nameplate

NP2116L											
CAT.NO.	EM3702T										
SPEC.	37G813S277G1										
HP	2										
VOLTS	230/460										
AMP	7/3.5										
RPM	865										
FRAME	213T			HZ		60		PH		3	
SER.F.	1.15	CODE	H	DES		B	CL		F		
NEMA-NOM-EFF	84	PF	62								
RATING	40C AMB-CONT										
CC	010A										
DE	6307	ODE		6206							
ENCL	TEFC	SN									

AC Induction Motor Performance Data

Record # 49983

Typical performance - not guaranteed values

Winding: 37WGS277-R008			Type: 3732M		Enclosure: TEFC	
Nameplate Data				460 V, 60 Hz: High Voltage Connection		
Rated Output (HP)		2		Full Load Torque		11.9 LB-FT
Volts		230/460		Start Configuration		direct on line
Full Load Amps		7/3.5		Breakdown Torque		29 LB-FT
R.P.M.		865		Pull-up Torque		16.9 LB-FT
Hz	60	Phase	3	Locked-rotor Torque		18.2 LB-FT
NEMA Design Code		B	KVA Code	H	Starting Current	
Service Factor (S.F.)		1.15		No-load Current		2.17 A
NEMA Nom. Eff.		84	Power Factor	62	Line-line Res. @ 25°C	
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		36°C
S.F. Amps				Temp. Rise @ S.F. Load		43°C
				Locked-rotor Power Factor		34.8
				Rotor inertia		0.796 LB-FT2

Load Characteristics 460 V, 60 Hz, 2 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	26	43	54	62	66	69	64
Efficiency	75.5	83.7	85.9	85	84.1	81.8	84.5
Speed	892	884	876	866	854	838	859
Line amperes	2.28	2.57	2.98	3.51	4.18	4.94	3.91

ABB Motors and Mechanical Inc.

WINDING # 37WGS277

Typical performance - not guaranteed values.

2 HP 3 PH 60 HZ 865 RPM 460 V 3732M

TORQUES (LB-FT): PO=29 PU=16.9 LR=18.2 LRA=16





