



Customer information packet

ERHM3162TA

5HP, 3450RPM, 3PH, 60HZ, 145TY, 3540M, OPEN, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	OPEN
Frame	145TY
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	5.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	UR CSA CSA EEV
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Resilient
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	6.100 A @ 460.0 V 13.000 A @ 208.0 V 12.200 A @ 230.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	86.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Terminal Panel
Front Shaft Indicator	None

Part detail

Revision	Q
Type	AC
Mech. spec.	35J829
Base	
Status	PRD/A
Elec. spec.	35WGM541
Layout	35LYJ829
Eff. date	07-25-2024
CD Diagram	CD0007
Poles	02
Leads	12#18
Proprietary	False
Created date	08-05-2010

Heater Indicator	No Heater
High Voltage Full Load Amps	6.1 a
Insulation Class	F
Inverter Code	Not Inverter
KVA Code	L
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Exit	Terminal Panel
Motor Lead Quantity/Wire Size	12 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3540M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	15.02 IN
Power Factor	89
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Resilient Mount
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	0.875 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3450 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Do Not Use Eve-Not Valid
Vibration Sensor Indicator	No Vibration Sensor

Winding Thermal 1	Automatic Thermal Overload
Winding Thermal 1 Location	SB
Winding Thermal 2	None

Nameplate

NP2601L											
CAT.NO.	ERHM3162TA										
SPEC.	35J829M541G1										
HP	5										
VOLTS	230/460										
AMP	12.2/6.1										
RPM	3450										
FRAME	143TY		HZ	60			PH	3			
SER.F.	1.15	CODE	L	DES	A	CL	F				
NEMA-NOM-EFF	86.5	PF	89								
RATING	40C AMB-CONT										
CC	010A										
DE	6205		ODE	6203							
ENCL	OPEN	SN									

AC Induction Motor Performance Data

Record # 53123

Typical performance - not guaranteed values

Winding: 35WGM541-R003			Type: 3540M		Enclosure: OPEN		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		5	Full Load Torque		7.65 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		12.2/6.1	Breakdown Torque		34.5 LB-FT		
R.P.M.		3450	Pull-up Torque		20.8 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		32.1 LB-FT	
NEMA Design Code		A	KVA Code	L	Starting Current		60.4 A
Service Factor (S.F.)		1.15	No-load Current		2.21 A		
NEMA Nom. Eff.		86.5	Power Factor	89	Line-line Res. @ 25°C		2.93 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		56°C
S.F. Amps					Temp. Rise @ S.F. Load		68°C
					Locked-rotor Power Factor		48.2
					Rotor inertia		0.111 LB-FT2

Load Characteristics 460 V, 60 Hz, 5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	54	76	85	89	91	92	90
Efficiency	83.8	88.1	87.9	86.9	84.9	82.6	85.7
Speed	3564	3530	3493	3452	3406	3353	3424
Line amperes	2.62	3.53	4.75	6.1	7.57	9.29	6.98

ABB Motors and Mechanical Inc.

WINDING # 35WGM541

Typical performance - not guaranteed values.

5 HP 3 PH 60 HZ 3450 RPM 460 V 3540M

TORQUES (LB-FT): PO=34.5 PU=20.8 LR=32.1 LRA=60.4

