



Customer information packet

FDEM4314T-5

60HP, 1780RPM, 3PH, 60HZ, 364T, A3658M, TEFC, F

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	364T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	60.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	575.0 V @ 60 HZ
Agency Approvals	UR NEMA PREMIUM
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Current @ Voltage	55.000 A @ 575.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	95.0 %
Feedback Device	NO FEEDBACK
Heater Indicator	No Heater
High Voltage Full Load Amps	55.0 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	G
Lifting Lugs	Standard Lifting Lugs
Motor Lead Quantity/Wire Size	3 @ 4 AWG
Motor Standards	NEMA
Motor Type	A3658M

Part detail

Revision	-
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	A36WG4086
Layout	617431-412
Eff. date	07-24-2025
CD Diagram	416820-036
Poles	04
Leads	3#4
Proprietary	False
Created date	07-23-2025


Mounting Arrangement	F1
Number of Poles	4
Overall Length	33.48 IN
Power Factor	84
Product Family	FARM DUTY
Pulley End Bearing Type	Ball
Service Factor	1.15
Shaft Diameter	2.375 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1780 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Winding	None


Nameplate

NP2496L	
MOBIL POLYREX EM	

NP3159L


SPEC NO.	A36-0052-4086			CAT.NO.	FDEM4314T-5					FRAME	364T	
HP	60	VOLTS	575		PHASE	3	DESIGN	B	TYPE	P		
RPM	1780	AMPS	55		HZ	60	AMB	40	SF	1.15		
DRIVE END BEARING	65BC03JGG30A			DUTY	CONT	INSUL.CLASS		F				
OPP D.E. BEARING	65BC03JGG30A			ENCL	TEFC	CODE	G					
SER.NO.				POWER FACTOR		84	NEMA-NOM-EFFICIENCY			95		
						MAX CORR KVAR		13.6	GUARANTEED EFFICIENCY		94.1	
						NEMA NOM/CSA QUOTED EFF						
									MOTOR WEIGHT		9999	





416820-036

A-C MOTOR
CONNECTION DIAGRAM
STANDARD 3 LEAD CONNECTED



(N.P. 1575-BA)

416820-036

REV. DESC: LOADED TO BUS, C/R 335225		
REV. LTR: -	VERSION: 00	TDR: 000000538207
FILE: \MGA\00000\682		REVISED: 11: 54: 06 04/30/2010
MTL: -		BY: RAGRA

BALDOR

CONN DIAG - STANDARD 3 LEAD
SH 1 of 1