



Customer information packet

FDL3611TM

2HP, 1725RPM, 1PH, 60HZ, 182T, 3634L, TEFC, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	182T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Cap Start, Induction Run
Output @ Frequency	2.000 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	115.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	14.000 A @ 230.0 V 28.000 A @ 115.0 V
Design Code	L
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	75.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	14.0 a

Part detail

Revision	M
Type	AC
Mech. spec.	36Q168
Base	
Status	PRD/A
Elec. spec.	36WG3444
Layout	36LYQ168
Eff. date	07-25-2024
CD Diagram	CD0008
Poles	04
Leads	4#14 A&J,2#16 B PH,1#10 #4TH
Proprietary	False
Created date	12-12-2013

Insulation Class	F
Inverter Code	Not Inverter
KVA Code	J
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	4 @ 14 AWG, A&J
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3634L
Mounting Arrangement	F1
Number of Poles	4
Overall Length	16.55 IN
Power Factor	67
Product Family	General Purpose
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	1.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1725 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	Manual Thermal Overload
Winding Thermal 1 Location	KO
Winding Thermal 2	None

Nameplate

NP1280L									
CAT.NO.	FDL3611TM								
SPEC.	36Q168-3444G1								
HP	2								
VOLTS	115/230								
AMP	28/14								
RPM	1725								
FRAME	182T	HZ		60	PH		1		
SER.F.	1.00	CODE		J	DES		L	CL	F
NEMA-NOM-EFF	75	PF		67					
RATING	40C AMB-CONT								
CC									
DE	6206	ODE		6205					
ENCL	TEFC	SN							

Accessories

Part number	Description	Multiplier
36-3301FD	C FACE KIT FARM DUTY 182-4TC ENCL, 6206	P1
36EP1304A62SP	FLANGE MTD ENDPLATE 182-4TD -ENCL (LESS	A8

AC Induction Motor Performance Data

Record # 61428

Typical performance - not guaranteed values

Winding: 36WG3444-R003			Type: 3634L		Enclosure: TEFC	
Nameplate Data			230 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		2	Full Load Torque		6 LB-FT	
Volts		115/230	Start Configuration		direct on line	
Full Load Amps		28/14	Breakdown Torque		23 LB-FT	
R.P.M.		1725	Pull-up Torque		22 LB-FT	
Hz	60	Phase	1	Locked-rotor Torque	27 LB-FT	
NEMA Design Code	L	KVA Code	J	Starting Current	105 A	
Service Factor (S.F.)			1	No-load Current	8.5 A	
NEMA Nom. Eff.	75	Power Factor	67	Line-line Res. @ 25°C	0.732 Ω A Ph 0.396 Ω B Ph	
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load	86°C	

Load Characteristics 230 V, 60 Hz, 2 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	43	57	68	76	81	84
Efficiency	47	62	68	71	71.5	71
Speed	1786	1776	1765	1754	1740	1725
Line amperes	8.8	9.7	10.8	12.3	14.2	16.4

ABB Motors and Mechanical Inc.

WINDING # 36WG3444

Typical performance - not guaranteed values.

2 HP 1 PH 60 HZ 1725 RPM 230 V 3634L

TORQUES (LB-FT) : PO=23 PU=22 LR=27 LRA=105





