



Customer information packet

FPM2563TS-4

200/150HP, 60//50HZ, 4PL, 3PH, 445TS, OPEN

Class - None

Division - Not Applicable

Specifications

Enclosure	DP
Frame	445TS
Frame Material	Iron
Frequency	50.00 Hz 60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	200.000 HP @ 60 HZ 150.000 HP @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	380.0 V @ 50 HZ 460.0 V @ 60 HZ
Agency Approvals	CSA EEV CCSA US UL
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Current @ Voltage	205.000 A @ 380.0 V 224.000 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	95.0 %
Feedback Device	NO FEEDBACK
Heater Indicator	No Heater
High Voltage Full Load Amps	205.0 a
Insulation Class	B
Inverter Code	Not Inverter

Part detail


Revision	G
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	A44WG5465
Layout	617428-044
Eff. date	09-25-2025
CD Diagram	421948-079
Poles	04
Leads	12#6
Proprietary	False
Created date	09-17-2015

KVA Code	F
Lifting Lugs	No Lifting Lugs
Motor Lead Quantity/Wire Size	12 @ 6 AWG
Motor Standards	NEMA
Motor Type	A44060M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	35.88 IN
Power Factor	88
Product Family	Other
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Service Factor	1.15
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1480 rpm
	1780 rpm
Speed Code	Single Speed
Starting Method	Wye Start - Delta Run
Thermal Device - Bearing	None
Thermal Device - Winding	None

Nameplate

NP3488L																
CAT.NO.	FPM2563TS-4				CUST P/N							I.P.				
SPEC.	P44G1852				SER.NO.							FRAME		445TS		
HZ	60	HP	200		RPM	1780		HZ	50		HP	150		RPM	1480	
VOLTS	460				CODE	F		VOLTS	380				CODE	G		
AMPS	224				DES	B		AMPS	205				DES	B		
EFF	95		SER.F.	1.15		PF	88		EFF	94.8		SER.F.	1.15		PF	87
RATING	40C AMB-CONT					DE BRG	65BC03J30X					GREASE	POLYREX EM			
BLANK						ODE BRG	65BC03J30X					MTR. WT.				
						CLASS	F			PH	3					
						ENCL	DP			CC	010A					
HTR-VOLTS		HTR-AMPS			HTR-WATTS			MAX. SPACE HEATER TEMP.								

REL. S. O.	FRAME	HP	TYPE	PHASE/ HERTZ	RPM	VOLTS
	445T	200	P	3/60	1780	460
AMPS	DUTY	AMB °C/ INSUL.	S. F.	NEMA DESIGN	CODE LETTER	ENCL.
224	CONT	40/B	1.15	B	F	PREM
E/S	ROTOR		TEST S. O.	TEST DATE	STATOR RES. @25 °C OHMS (BETWEEN LINES)	
498023	418143036LE		---	---	.0356	
PERFORMANCE						
LOAD	HP	AMPERES	RPM	% POWER FACTOR	% EFFICIENCY	
NO LOAD	0	58.4	1800	4.94	0	
1/4	50.1	78.8	1796	63.7	93.5	
2/4	100	119	1791	82.2	95.6	
3/4	150	169	1786	86.8	95.7	
4/4	200	224	1781	87.8	95.1	
5/4	250	282	1775	88.3	94.1	
SPEED TORQUE						
		RPM	TORQUE % FULL LOAD	TORQUE LB.-FT.	AMPERES	
LOCKED ROTOR	0	158	930	1370		
PULL UP	540	145	855	1315		
BREAKDOWN	1704	247	1455	822		
FULL LOAD	1781	100	590	224		
AMPERES SHOWN FOR 460. VOLT CONNECTION. IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE						
REMARKS: E MASTER MOTOR TYPICAL DATA NEMA NOM. EFF. 95.0% - GUAR. MIN. EFF. 94.5%						
				A-C MOTOR PERFORMANCE DATA		
DR. BY _____ CD _____ CK. BY T. KELAATI APP. BY T. KELAATI DATE 12/17/15				A44WG5465-R001 ISSUE DATE 12/17/15		
A MEMBER OF THE ABB GROUP						



Printed on 12/17/15 14:41 @ bengap01.baldor.com

