



Customer information packet

GNEM2524T

15HP//11KW, 1180//980RPM, 3PH, 60//50HZ, 284

Specifications

Enclosure	OPSB
Frame	284T
Frame Material	Steel
Frequency	50.00 Hz 60.00 Hz
Motor Letter Type	Three Phase
Output @ Frequency	15.000 HP @ 60 HZ 11.000 KW @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	190.0 V @ 50 HZ 208.0 V @ 60 HZ 230.0 V @ 60 HZ 380.0 V @ 50 HZ 460.0 V @ 60 HZ
Agency Approvals	C UR US CE IE3 WEEE
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	46.000 A @ 190.0 V 42.000 A @ 208.0 V 40.000 A @ 230.0 V 23.000 A @ 380.0 V 20.000 A @ 460.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT

Part detail

Revision	C
Type	AC
Mech. spec.	40G48
Base	
Status	PRD/A
Elec. spec.	40WGX502
Layout	40LYG048
Eff. date	09-02-2025
CD Diagram	CD0180
Poles	06
Leads	9#10
Proprietary	False
Created date	08-16-2023

Efficiency @ 100% Load	91.7 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	20.0 a
Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	J
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 10 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	4056M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	25.06 IN
Power Factor	75
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.875 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1180 rpm 980 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None

Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4304L									
CAT.NO.	GNEM2524T								
SPEC.	40G048X502G1								
HP	15HP//11KW					PH	3		
VOLTS	208-230/460//190/380								
AMPS	44-42/21//48/24								
R.P.M. (1/MIN)	1185//980					WT.	113		KG
FRAME	284T		HZ	60//50			I.P.	22	
SER.F.	1.15	CODE	J	DES.	A	CLASS	F		
NOM.EFF.	91.7//90.3		% (100%)						
P.F.	73	IC01, 10:1 VT							
RATING	40C AMB-CONT				CC	010A			
DE	6311		ODE	6309					
ENCL	OPSB	SN							
	IE3-50HZ 92.8(75%),92.5(50%)								
	IE3-60HZ 93.4(75%),92.4(50%)								
	SFA 49-46/23//52/26								

AC Induction Motor Performance Data

Record # 105136

Typical performance - not guaranteed values

Winding: 40WGX502-R001		Type: 4056M	Enclosure: OPSB		
Nameplate Data		460 V, 60 Hz: High Voltage Connection			
Rated Output (HP)	15HP//11KW	Full Load Torque	66.62 LB-FT		
Volts	208-230/460//190/380	Start Configuration	direct on line		
Full Load Amps	42-40/20//46/23	Breakdown Torque	230 LB-FT		
R.P.M.	1180//980	Pull-up Torque	127 LB-FT		
Hz	60//50	Phase	3	Locked-rotor Torque	139 LB-FT
NEMA Design Code	A	KVA Code	J	Starting Current	140 A
Service Factor (S.F.)	1.15			No-load Current	11.4 A
NEMA Nom. Eff.	91.7	Power Factor	75	Line-line Res. @ 25°C	0.47156 Ω
Rating - Duty	40C	AMB-CONT	Temp. Rise @ Rated Load		23°C
S.F. Amps	48-50/25//52/26			Temp. Rise @ S.F. Load	27°C
		Locked-rotor Power Factor			31

Load Characteristics 460 V, 60 Hz, 15 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	33	53	66	73	77	79	75
Efficiency	87.9	92.4	93.4	93.5	93.1	92.4	93.3
Speed	1196.3	1192.5	1189.1	1185.2	1180.7	1175.4	1182
Line amperes	12.3	14.4	17.2	20.7	24.6	28.9	23


ABB Motors and Mechanical Inc.

WINDING # 40WGX502

Typical performance - not guaranteed values.

15 HP 3 PH 60 HZ 1185.2 RPM 460 V 4056M

TORQUES (LB-FT): PO=230 PU=127 LR=139 LRA=140



AC Induction Motor Performance Data

Record # 105138

Typical performance - not guaranteed values

Winding: 40WGX502-R001		Type: 4056M	Enclosure: OPSB			
Nameplate Data			380 V, 50 Hz: High Voltage Connection			
Rated Output (HP)	15HP//11KW		Full Load Torque	79.1 LB-FT		
Volts	208-230/460//190/380		Start Configuration	direct on line		
Full Load Amps	44-42/21//48/24		Breakdown Torque	226 LB-FT		
R.P.M.	1185//980		Pull-up Torque	124 LB-FT		
Hz	60//50	Phase	3	Locked-rotor Torque	137 LB-FT	
NEMA Design Code	A		KVA Code	J	Starting Current	139 A
Service Factor (S.F.)			1.15	No-load Current	11.1 A	
NEMA Nom. Eff.	91.7	Power Factor	73	Line-line Res. @ 25°C	0.47155 Ω	
Rating - Duty			40C AMB-CONT	Temp. Rise @ Rated Load	34°C	
S.F. Amps			49-46/23//52/26	Temp. Rise @ S.F. Load	39°C	
			Locked-rotor Power Factor			34.4
			Rotor inertia			6.86 lb-ft²

Load Characteristics 380 V, 50 Hz, 15 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	38	60	71	77	79	79	78
Efficiency	89.2	92.5	92.8	92.2	91.6	91.1	91.8
Speed	995.3	990.6	985.6	979.8	976.3	973.8	978
Line amperes	12.4	15.2	19	23.7	26.7	28.8	25.5


ABB Motors and Mechanical Inc.


WINDING # 40WGX502

Typical performance - not guaranteed values.




15 HP 3 PH 50 HZ 979.8 RPM 380 V 4056M

TORQUES (LB-FT): PO=226 PU=124 LR=137 LRA=139





CD0180

LOW VOLTAGE
(2D)HIGH VOLTAGE
(1D)

NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CD0180

REV. DESC: ADD CLASS CONN00000007

REV. LTR: D

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\148

REVISED: 10: 25: 29 02/19/2019

BY: ENBRIRO

MTL: —

**BALDOR - RELIANCE®**

3PH, DV, 9 LEADS, DELTA CONNECTION

SH 1 of 1