



Customer information packet

GNEM3309T-G

5HP//3.7KW, 1160//955RPM, 3PH, 60//50HZ, 215

Class - None

Division - Not Applicable

Specifications

Enclosure	OPSB
Frame	215T
Frame Material	Steel
Frequency	50.00 Hz 60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	5.000 HP @ 60 HZ 3.700 KW @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	190.0 V @ 50 HZ 208.0 V @ 60 HZ 230.0 V @ 60 HZ 380.0 V @ 50 HZ 460.0 V @ 60 HZ
Agency Approvals	CE WEEE UKCA CURUSEEV IE3 NEMA PREMIUM
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	8.600 A @ 380.0 V 7.400 A @ 460.0 V 17.200 A @ 190.0 V 15.200 A @ 208.0 V

Part detail

Revision	C
Type	AC
Mech. spec.	37J839
Base	
Status	PRD/A
Elec. spec.	37WGS521
Layout	37LYJ839
Eff. date	06-26-2025
CD Diagram	CD0005
Poles	06
Leads	9#14
Proprietary	False
Created date	09-01-2023

	14.800 A @ 230.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	89.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	7.4 a
Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	K
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 14 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3744M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	17.45 IN
Power Factor	71
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	1.375 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger

Speed	1160 rpm
	955 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4304L									
CAT.NO.	GNEM3309T-G								
SPEC.	37J839S521G2								
HP	5HP//3.7KW					PH	3		
VOLTS	208-230/460//190/380								
AMPS	15.2-14.8/7.4//17.2/8.6								
R.P.M. (1/MIN)	1160//955					WT.	64KG		KG
FRAME	215T		HZ	60//50			I.P.	22	
SER.F.	1.15	CODE	K	DES.	A	CLASS	H		
NOM.EFF.	89.5//86.5		% (100%)						
P.F.	71	IC01, 10:1 VT							
RATING	40C AMB-S1 CONT				CC	010A			
DE	6307		ODE	6206					
ENCL	OPSB	SN							
	SFA 15.2-8.6/8.3//20/10								
	IE3-50HZ-88.9(75%),87.8(50%)								
	IE3-60HZ-90.1(75%),89.4(50%)								



