



Customer information packet

GNEM3313T

10HP//7.5KW, 1770//1470 1/MINRPM, 3PH, 60//

Class - None

Division - Not Applicable

Specifications

Enclosure	OPSB
Frame	215T
Frame Material	Steel
Frequency	50.00 Hz 60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	10.000 HP @ 60 HZ 7.500 KW @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	380.0 V @ 50 HZ 230.0 V @ 60 HZ 208.0 V @ 60 HZ 460.0 V @ 60 HZ 190.0 V @ 50 HZ
Agency Approvals	WEEE UR IE3 CSA CE
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	31.600 A @ 190.0 V 27.600 A @ 208.0 V 27.400 A @ 230.0 V 15.800 A @ 380.0 V 13.700 A @ 460.0 V

Part detail

Revision	G
Type	AC
Mech. spec.	37F614
Base	
Status	PRD/A
Elec. spec.	37WGZ674
Layout	37LYF614
Eff. date	05-10-2024
CD Diagram	CD0005
Poles	04
Leads	9#14
Proprietary	False
Created date	04-12-2023

Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.7 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	13.7 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	K
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 14 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3744M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	17.45 IN
Power Factor	75
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	1.375 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1470 rpm

	1770 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4304L									
CAT.NO.	GNEM3313T								
SPEC.	37F614Z674G1								
HP	10HP/7.5KW						PH	3	
VOLTS	208-230/460//190/380								
AMPS	28-26.8/13.4//32/16								
R.P.M. (1/MIN)	1770//1470						WT.	65KG	KG
FRAME	215T		HZ	60//50			I.P.	22	
SER.F.	1.15	CODE	L	DES.	A	CLASS	F		
NOM.EFF.	91.7//90.4		% (100%)						
P.F.	76	IC01, 10:1 VT							
RATING	40C AMB-S1 CONT				CC	010A			
DE	6307		ODE	6206					
ENCL	OPSB	SN							
	IE3-60HZ-92.5(75%)91.5(50%)								
	IE3-50HZ-91.7(75%)91.6(50%)								
	SFA 31-30/15//34/17								

AC Induction Motor Performance Data

Record # 102535

Typical performance - not guaranteed values

Winding: 37WGZ674-R001		Type: 3748M	Enclosure: OPSB		
Nameplate Data			460 V, 60 Hz: High Voltage Connection		
Rated Output (HP)	10HP//7.5KW		Full Load Torque	29.7 LB-FT	
Volts	208-230/460//190/380		Start Configuration	direct on line	
Full Load Amps	28-26.8/13.4//32/16		Breakdown Torque	131 LB-FT	
R.P.M.	1770//1470		Pull-up Torque	58.7 LB-FT	
Hz	60//50	Phase	3	Locked-rotor Torque	77.9 LB-FT
NEMA Design Code	A	KVA Code	L	Starting Current	119 A
Service Factor (S.F.)	1.15		No-load Current	7.22 A	
NEMA Nom. Eff.	91.7	Power Factor	76	Line-line Res. @ 25°C	0.85311 Ω
Rating - Duty	40C AMB-CONT		Temp. Rise @ Rated Load	33°C	
S.F. Amps	31-30/15//34/17		Temp. Rise @ S.F. Load	40°C	
			Locked-rotor Power Factor	36.5	
			Rotor inertia	1.18 lb-ft²	

Load Characteristics 460 V, 60 Hz, 10 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	35	56	69	76	80	82	78
Efficiency	86.5	91.5	92.5	92.5	92	91.2	92.2
Speed	1793.9	1788.5	1782.5	1776.1	1769.6	1762.5	1772
Line amperes	7.79	9.19	11.1	13.4	16	18.8	15


ABB Motors and Mechanical Inc.

WINDING # 37WGZ674

Typical performance - not guaranteed values.

10 HP 3 PH 60 HZ 1776.1 RPM 460 V 3748M

TORQUES (LB-FT): PO=131 PU=58.7 LR=77.9 LRA=119



AC Induction Motor Performance Data

Record # 102536

Typical performance - not guaranteed values

Winding: 37WGZ674-R001			Type: 3748M		Enclosure: OPSB			
Nameplate Data				380 V, 50 Hz: High Voltage Connection				
Rated Output (HP)		10HP//7.5KW		Full Load Torque		35.86 LB-FT		
Volts		208-230/460//190/380		Start Configuration		direct on line		
Full Load Amps		28-26.8/13.4//32/16		Breakdown Torque		113 LB-FT		
R.P.M.		1770//1470		Pull-up Torque		53.7 LB-FT		
Hz		60//50	Phase	3	Locked-rotor Torque		77.9 LB-FT	
NEMA Design Code		A		KVA Code	L	Starting Current		109 A
Service Factor (S.F.)		1.15		No-load Current		6.92 A		
NEMA Nom. Eff.		91.7	Power Factor		76	Line-line Res. @ 25°C		0.85035 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		47°C		
S.F. Amps		31-30/15//34/17		Temp. Rise @ S.F. Load		54°C		
				Locked-rotor Power Factor		36.5		
				Rotor inertia		1.18 lb-ft²		

Load Characteristics 380 V, 50 Hz, 10 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	42	64	75	80	82	83	81
Efficiency	88.2	91.6	91.7	90.9	90.2	89.6	90.5
Speed	1492.1	1484.7	1476.6	1468.1	1462.5	1457.9	1465
Line amperes	7.8	9.74	12.4	15.5	17.6	19.1	16.8


ABB Motors and Mechanical Inc.

WINDING # 37WGZ674

Typical performance - not guaranteed values.

10 HP 3 PH 50 HZ 1468.1 RPM 380 V 3748M

TORQUES (LB-FT): PO=113 PU=53.7 LR=77.9 LRA=109



12/22/2025 ACPERF, record # 102536

