



Customer information packet

GNEM3558T

2/1.5KWHP, 1765//1460RPM, 3PH, 60//50HZ, 145

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	145T
Frame Material	Steel
Frequency	50.00 Hz 60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	2.000 HP @ 60 HZ 2.000 HP @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	190.0 V @ 50 HZ 208.0 V @ 60 HZ 230.0 V @ 60 HZ 380.0 V @ 50 HZ 460.0 V @ 60 HZ
Agency Approvals	CE WEEE UKCA CURUSEEV IE3 NEMA PREMIUM
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	6.400 A @ 190.0 V 5.700 A @ 208.0 V 5.600 A @ 230.0 V 3.200 A @ 380.0 V

Part detail

Revision	C
Type	AC
Mech. spec.	35A001
Base	
Status	PRD/A
Elec. spec.	35WGZ806
Layout	35LYA001
Eff. date	06-04-2024
CD Diagram	CD0005
Poles	04
Leads	9#18
Proprietary	False
Created date	08-24-2023

2.800 A @ 460.0 V

Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	86.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	2.8 a
Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	L
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3530M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	14.17 IN
Power Factor	77
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	0.875 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger

Speed	1460 rpm
	1765 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4304L									
CAT.NO.	GNEM3558T								
SPEC.	35A001Z806G1								
HP	2/1.5KW					PH	3		
VOLTS	208-230/460//190/380								
AMPS	5.7-5.6/2.8//6.4/3.2								
R.P.M. (1/MIN)	1765//1460					WT.	22KG		KG
FRAME	145T		HZ	60//50			I.P.	44	
SER.F.	1.15	CODE	L	DES.	B	CLASS	F		
NOM.EFF.	86.5//85.3		% (100%)						
P.F.	77	IC411, 10:1 VT							
RATING	40C AMB-S1 CONT				CC	010A			
DE	6205		ODE	6203					
ENCL	TEFC	SN							
	SFA 6.5-6.3/3.15//7.4/3.7								
	IE3-50HZ-86.6(75%),86.0(50%)								
	IE3-60HZ-86.9(75%),85.1(50%)								

AC Induction Motor Performance Data

Record # 100960

Typical performance - not guaranteed values

Winding: 35WGZ806-R025		Type: 3530M	Enclosure: TEFC			
Nameplate Data		460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)	2	Full Load Torque	5.94 LB-FT			
Volts	208-230/460//190/380	Start Configuration	direct on line			
Full Load Amps	5.7-5.6/2.8//6.4/3.2	Breakdown Torque	24.53 LB-FT			
R.P.M.	1765//1460	Pull-up Torque	14.6 LB-FT			
Hz	60//50	Phase	3	Locked-rotor Torque	17.66 LB-FT	
NEMA Design Code	B	KVA Code	L	Starting Current	25.08 A	
Service Factor (S.F.)	1.15	No-load Current	1.76 A			
NEMA Nom. Eff.	86.5	Power Factor	77	Line-line Res. @ 25°C	9.23 Ω	
Rating - Duty	40C	AMB-CONT	Temp. Rise @ Rated Load			47°C
S.F. Amps	6.5-6.3/3.15//7.4/3.7	Temp. Rise @ S.F. Load			57°C	
		Locked-rotor Power Factor			58.4	
		Rotor inertia			0.217 lb-ft²	

Load Characteristics 460 V, 60 Hz, 2 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	33	54	67	75	80	84	78
Efficiency	77.3	85	87.3	87.7	87.2	86.1	87.4
Speed	1794	1787	1780	1772	1763	1754	1767
Line amperes	1.84	2.07	2.42	2.85	3.35	3.9	3.15


ABB Motors and Mechanical Inc.

WINDING # 35WGZ806

Typical performance - not guaranteed values.

2 HP 3 PH 60 HZ 1772 RPM 460 V 3530M

TORQUES (LB-FT): PO=24.53 PU=14.6 LR=17.66 LRA=25.08



AC Induction Motor Performance Data

Record # 100961

Typical performance - not guaranteed values

Winding: 35WGZ806-R025		Type: 3530M	Enclosure: TEFC		
Nameplate Data		380 V, 50 Hz: High Voltage Connection			
Rated Output (HP)	2	Full Load Torque	7.19 LB-FT		
Volts	208-230/460//190/380	Start Configuration	direct on line		
Full Load Amps	5.7-5.6/2.8//6.4/3.2	Breakdown Torque	22.3 LB-FT		
R.P.M.	1765//1460	Pull-up Torque	14 LB-FT		
Hz	60//50	Phase	3	Locked-rotor Torque	16.9 LB-FT
NEMA Design Code	B	KVA Code	L	Starting Current	23.4 A
Service Factor (S.F.)	1.15			No-load Current	1.61 A
NEMA Nom. Eff.	86.5	Power Factor	77	Line-line Res. @ 25°C	9.23 Ω
Rating - Duty	40C	AMB-CONT	Temp. Rise @ Rated Load		72°C
S.F. Amps	6.5-6.3/3.15//7.4/3.7			Temp. Rise @ S.F. Load	90°C
				Locked-rotor Power Factor	63.9
				Rotor inertia	0.217 lb-ft²

Load Characteristics 380 V, 50 Hz, 2 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	41	63	76	82	86	88	84
Efficiency	80.6	86	86.6	85.3	83.1	80.4	84
Speed	1491	1482	1472	1461	1450	1435	1454
Line amperes	1.74	2.09	2.59	3.23	4	4.79	3.69


ABB Motors and Mechanical Inc.

WINDING # 35WGZ806

Typical performance - not guaranteed values.

2 HP 3 PH 50 HZ 1461 RPM 380 V 3530M

TORQUES (LB-FT): PO=22.3 PU=14 LR=16.9 LRA=23.4



AC Induction Motor Performance Data

Record # 104460

Typical performance - not guaranteed values

Winding: 35WGZ806-R025		Type: 3530M	Enclosure: TEFC	
Nameplate Data		208 V, 60 Hz: Low Voltage Connection		
Rated Output (HP)	2	Full Load Torque	5.96 LB-FT	
Volts	208-230/460//190/380	Start Configuration	direct on line	
Full Load Amps	5.7-5.6/2.8//6.4/3.2	Breakdown Torque	19.7 LB-FT	
R.P.M.	1765//1460	Pull-up Torque	11.5 LB-FT	
Hz	60//50 Phase	Locked-rotor Torque	13.9 LB-FT	
NEMA Design Code	B KVA Code	Starting Current	44.5 A	
Service Factor (S.F.)	1.15	No-load Current	2.92 A	
NEMA Nom. Eff.	86.5 Power Factor	Line-line Res. @ 25°C	2.31 Ω	
Rating - Duty	40C AMB-CONT	Temp. Rise @ Rated Load	47°C	
S.F. Amps	6.5-6.3/3.15//7.4/3.7	Temp. Rise @ S.F. Load	59°C	
		Locked-rotor Power Factor	58.4	
		Rotor inertia	0.217 lb-ft²	

Load Characteristics 208 V, 60 Hz, 2 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	41	63	75	81	85	87	83
Efficiency	80.8	86.8	88.1	87.6	86.5	84.7	86.9
Speed	1792	1784	1775	1765	1754	1742	1758
Line amperes	3.17	3.82	4.74	5.83	7.08	8.46	6.58


ABB Motors and Mechanical Inc.


WINDING # 35WGZ806

Typical performance - not guaranteed values.




2 HP 3 PH 60 HZ 1765 RPM 208 V 3530M

TORQUES (LB-FT): PO=19.7 PU=11.5 LR=13.9 LRA=44.5





CD0005



- NOTES:
- 1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
 - 2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
 - 3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
 - 4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: REVISE TO SHOW OPTIONAL COLORS			
REV. LTR: E	BY: JLP	REVISED: 01/19/99 10:15	TDR: 0171435
900000		FILE: AAA00005140	MDL: -
		MTL: -	

BALDOR ELECTRIC Co.

3PH, DV, 9 LEADS

CD0005