



Customer information packet

GNEM3714T-G

10HP//7.5KW, 1770//1460RPM, 3PH, 60//50HZ, 2

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	215T
Frame Material	Steel
Frequency	50.00 Hz 60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	7.500 KW @ 50 HZ 10.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1500 RPM @ 50 HZ
Voltage @ Frequency	190.0 V @ 50 HZ 208.0 V @ 60 HZ 230.0 V @ 60 HZ 380.0 V @ 50 HZ 460.0 V @ 60 HZ
Agency Approvals	CE WEEE UKCA CURUSEEV IE3 NEMA PREMIUM
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	30.000 A @ 190.0 V 27.000 A @ 208.0 V 26.000 A @ 230.0 V 15.000 A @ 380.0 V

Part detail

Revision	B
Type	AC
Mech. spec.	37J838
Base	
Status	PRD/A
Elec. spec.	37WGZ676
Layout	37LYJ838
Eff. date	09-23-2024
CD Diagram	CD0005
Poles	04
Leads	9#14
Proprietary	False
Created date	01-17-2024

13.000 A @ 460.0 V

Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.7 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	13.0 a
Insulation Class	H
Inverter Code	Inverter Ready
KVA Code	K
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 14 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3756M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	20.51 IN
Power Factor	78
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	1.375 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger

Speed	1460 rpm
	1770 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4304L									
CAT.NO.	GNEM3714T-G								
SPEC.	37J838Z676G1								
HP	10HP//7.5KW					PH	3		
VOLTS	208-230/460//190/380								
AMPS	27-26/13//30/15								
R.P.M. (1/MIN)	1770//1460					WT.	75KG		KG
FRAME	215T		HZ	60//50			I.P.	44	
SER.F.	1.15	CODE	K	DES.	A	CLASS	H		
NOM.EFF.	91.7		% (100%)						
P.F.	78	IC411, 10:1 VT							
RATING	40C AMB-S1 CONT				CC	010A			
DE	6307		ODE	6206					
ENCL	TEFC	SN							
	IE3-60HZ 92.7(75%),91.9(50%)								
	IE3-50HZ 91.6(75%),91.9(50%)								
	SFA 31-30/15//34/17								

AC Induction Motor Performance Data

Record # 103292

Typical performance - not guaranteed values

Winding: 05WGX509-R031			Type: 0526M		Enclosure: TEAO		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		2 AO	Full Load Torque		5.976 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		5.6/2.8	Breakdown Torque		23.5 LB-FT		
R.P.M.		1760	Pull-up Torque		11.5 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		15.6 LB-FT	
NEMA Design Code		B	KVA Code	L	Starting Current		22.7 A
Service Factor (S.F.)		1.15	No-load Current		1.69 A		
NEMA Nom. Eff.		86.5	Power Factor	76	Line-line Res. @ 25°C		9.5456 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		
					Locked-rotor Power Factor		58
					Rotor inertia		0.188 lb-ft²

Load Characteristics 460 V, 60 Hz, 2 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	34	55	68	77	81	84	79
Efficiency	77.5	85.2	86.9	86.8	85.8	84.3	86.2
Speed	1789.9	1781.4	1772.2	1762.2	1751.3	1739.3	1756
Line amperes	1.75	1.99	2.37	2.83	3.36	3.96	3.15


ABB Motors and Mechanical Inc.

WINDING # 05WGX509

Typical performance - not guaranteed values.

2 HP 3 PH 60 HZ 1760 RPM 460 V 0526M

TORQUES (LB-FT): PO=23.5 PU=11.5 LR=15.6 LRA=22.7



AC Induction Motor Performance Data

Record # 103293

Typical performance - not guaranteed values

Winding: 37WGZ676-R002			Type: 3756M		Enclosure: TEFC		
Nameplate Data			380 V, 50 Hz: High Voltage Connection				
Rated Output (HP)		10HP//7.5KW		Full Load Torque		36.28 LB-FT	
Volts		208-230/460//190/380		Start Configuration		direct on line	
Full Load Amps		27-26/13//30/15		Breakdown Torque		112 LB-FT	
R.P.M.		1770//1460		Pull-up Torque		57.6 LB-FT	
Hz	60//50	Phase	3	Locked-rotor Torque		80.9 LB-FT	
NEMA Design Code		A	KVA Code	K	Starting Current		107 A
Service Factor (S.F.)		1.15		No-load Current		6.3 A	
NEMA Nom. Eff.		91.7	Power Factor	78	Line-line Res. @ 25°C		0.81636 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		85°C	
S.F. Amps		31-30/15//34/17		Temp. Rise @ S.F. Load		99°C	
				Locked-rotor Power Factor		38.9	
				Rotor inertia		1.38 lb-ft²	

Load Characteristics 380 V, 50 Hz, 10 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	45	67	78	83	84	85	84
Efficiency	89.3	91.9	91.6	90.5	89.5	88.8	89.9
Speed	1489.8	1479.5	1468.1	1456.3	1448.4	1442.5	1452
Line amperes	7.19	9.25	12	15.3	17.4	18.9	16.6


ABB Motors and Mechanical Inc.


WINDING # 37WGZ676

Typical performance - not guaranteed values.

10 HP 3 PH 50 HZ 1456.3 RPM 380 V 3756M

TORQUES (LB-FT): PO=112 PU=57.6 LR=80.9 LRA=107





CD0005



- NOTES:
- 1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
 - 2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
 - 3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
 - 4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: REVISE TO SHOW OPTIONAL COLORS			
REV. LTR: E	BY: JLP	REVISED: 01/19/99 10:15	TDR: 0171435
900000		FILE: AAA00005140	MDL: -
		MTL: -	

BALDOR ELECTRIC Co.

3PH, DV, 9 LEADS

CD0005