



Customer information packet

IDVSM3665T

5HP, 1750RPM, 3PH, 60HZ, 184TC, 0641M, TEFC, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	184TC
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	5.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	13.200 A @ 230.0 V 6.600 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	89.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Encoder/Feedback Device
Front Shaft Indicator	No Key Or Flat
Heater Indicator	No Heater
High Voltage Full Load Amps	6.6 a

Part detail

Revision	Q
Type	AC
Mech. spec.	06H926
Base	
Status	PRD/A
Elec. spec.	06WGX182
Layout	06LYH926
Eff. date	09-30-2025
CD Diagram	CD0005
Poles	04
Leads	9#16
Proprietary	False
Created date	09-05-2012

Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	J
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	4000 rpm
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0642M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	20.23 IN
Power Factor	79
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.00
Shaft Diameter	1.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1750 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None

Winding Thermal 2	None
--------------------------	-------------

Nameplate

NP4615L									
CAT NO	IDVSM3665T								
SPEC.	06H926X182G1							ENCL	TEFC
FRAME	184TC		HP	5 TE					
VOLTS	230/460								
MAG CUR	6.4/3.2			FLA	13.2/6.6				
RPM	1750		RPM MAX	4000					
HZ	60		PH	3	CLASS	F			
SER.F.	1.00			SL HZ	1.7				
NEMA-NOM-EFF	89.5		WK2	0.39					
RATING	40C AMB-CONT								
DE BRG	6206		ODE BRG	6206					
CC	010A	SN							
	1.5:1 CHP PWM								
	1000:1 CT/VT								

REL S.O.	IDVSM3665T	VOLTS	460	ENCLOSURE	TEFC	WYE CONN	EQ	CKT	OHMS PER PHASE
FRAME	184TC	AMPS	6.6	MAX SAFE RPM	4000				(AT BASE RATING, 25°C)
HP	5	DUTY	CONT	In (AMPS)	3.2	R1	1.3080	X1	3.6930
BASE SPEED	1750	S.F.	1.0	P.F. @NL/FL	6/79	R2	1.0000	X2	3.2200
PHASE/HZ	3/60	AMB°C/INSUL	40/F	WK ² (lb-ft ²)	0.382			XM	81.0550

Rated Full Load Data

	RPM	HP	Torque	Volts	Freq-Hz	Amps
Base Speed	1749	5.0	15.00	460	60	6.63
Max Speed	2622	5.0	10.10	460	90	6.00
Min Speed	0	0.0	15.15	36.44	1.70	6.63

Load Performance at Base Speed

	RPM	HP	Torque	Volts	Freq-Hz	Amps
No Load	1799	0.0	0.00	460	60	3.20
1/4	1788	1.3	3.75	460	60	3.48
1/2	1775	2.5	7.52	460	60	4.26
3/4	1763	3.8	11.20	460	60	5.34
Full Load	1749	5.0	15.00	460	60	6.63
O/L	1679	11.0	34.50	460	60	14.50

Blower Data


Volts	Ph/Hz	FL Amps	LR Amps	Frame	CFM

Remarks: Calculated Data
Vector PWM Inverter Duty

BALDOR A MEMBER OF THE ABB GROUP		DR BY Michael Williamson CK BY Michael Williamson APP BY Michael Williamson DATE 8/27/2012	A-C MOTOR PERFORMANCE CURVES ISSUE DATE 8/27/2012
		06G938X182Z1	

REL S.O.	IDVSM3665T	VOLTS	460	ENCLOSURE	TEFC	WYE CONNECT OHMS PER PHASE
FRAME	184TC	AMPS	6.6	MAX SAFE RPM	4000	(AT BASE RATING, 25°C)
HP	5	DUTY	CONT	In (AMPS)	3.2	R1 1.3080 X1 3.6930
BASE SPEED	1750	S.F.	1.00	P.F. @NL/FL	6/79	R2 1.0000 X2 3.2200
PHASE/HZ	3/60	AMB°C/INSUL.	40/F	WK² (lb-ft²)	0.382	XM 81.0550

Vector PWM Inverter Duty
Variable Speed AC Motor Curves



Calculated Data

Data Valid For Nameplate Speed Range only

BALDOR
A MEMBER OF THE ABB GROUP


DR BY Michael Williamson
CK BY Michael Williamson
APP BY Michael Williamson
DATE 8/27/2012

A-C MOTOR PERFORMANCE
CURVES

06G938X182Z1
SH 1 of 2
ISSUE DATE 8/27/2012

REL S.O.	IDVSM3665T	VOLTS	460	ENCLOSURE	TEFC	WYE CONN EQ CKT OHMS PER PHASE (AT BASE RATING, 25°C)
FRAME	184TC	AMPS	6.6	MAX SAFE RPM	4000	
HP	5	DUTY	CONT	In (AMPS)	3.2	X1 3.6930
BASE SPEED	1750	S.F.	1.00	P.F. @NL/FL	6/79	R2 1.0000 X2 3.2200
PHASE/HZ	3/60	AMB°C/INSUL.	40/F	WK ² (Lb-Ft ²)	0.382	XM 81.0550

Vector PWM Inverter Duty
Variable Speed AC Motor Curves



Calculated Data

Data Valid For Nameplate Speed Range only

BALDOR
A MEMBER OF THE ABB GROUP

DR BY
CK BY
APP BY
DATE

06G938X182Z1
SH 1 of 2
ISSUE DATE

Michael Williams
Michael Williams
Michael Williams
8/27/2012

A-C MOTOR
PERFORMANCE CURVES

8/27/2012

