



Customer information packet

IDWNM3611T

3HP, 1760RPM, 3PH, 60HZ, 184TC, 3640M, TENV, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TENV
Frame	184TC
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	3.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	4.100 A @ 460.0 V 8.200 A @ 230.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	89.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Encoder/Feedback Device
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	4.1 a

Part detail

Revision	N
Type	AC
Mech. spec.	36J565
Base	
Status	PRD/A
Elec. spec.	36WGS952
Layout	36LYJ565
Eff. date	09-27-2024
CD Diagram	CD0005
Poles	04
Leads	9#16
Proprietary	False
Created date	05-31-2012

Insulation Class	H
Inverter Code	Inverter Duty
KVA Code	K
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	6000 rpm
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3640M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	19.27 IN
Power Factor	78
Product Family	Wash Down
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	1.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1760 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3956L									
CAT.NO.	IDWNM3611T								
SPEC.	36J565S952G1								
FRAME	184TC			H.P.	3 TE				
VOLTS	230/460								
MAG. CUR.	4.2/2.1			F.L. AMPS			8.2/4.1		
R.P.M.	1760			R.P.M. MAX			6000		
HZ.	60		PH.	3		CLASS	H		
SER.F.	1.00		DES.	B		SL HZ	1.4		
NEMA NOM. EFF.	89.5		WK2	0.372					
BLWR V		PH		HZ		AMPS			
RATING	40C AMB-CONT								
DE BRG	6206		ODE BRG		6205				
CC	010A	SN							



AC Induction Motor Performance Data
 Record # 39007
 Typical performance - not guaranteed values

Winding: 36WGS952	Type: 3640M	Enclosure: TENV
--------------------------	--------------------	------------------------

Nameplate Data			General Characteristics at 460 V, 60 Hz: High Volt Connection				
Rated Output (HP)	3		Full Load Torque	9.1 LB-FT			
Volts	208-230/460		Start Configuration	DOL			
Full Load Amps	8.6-8.2/4.1		Break Down Torque	35 LB-FT			
R.P.M.	1760		Pull-Up Torque	18.8 LB-FT			
Hz	60	Phase	Locked-rotor Torque	22.7 LB-FT			
NEMA Design Code	B	KV/A Code	Starting Current	32.9 Amps			
Service Factor	1		No-load Current	2.09 Amps			
NEMA Nom. Eff.	89.5	P.F.	Line-line Res. @ 25°C.	3.3157 Ohms			
Rating - Duty	40C AMB-CONT		Temp. Rise @ Rated Load	74°C			
S.F. Amps			Temp. Rise @ S.F. Load				


Load Characteristics at 460 Volts, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	38	60	71	78	82	84	
Efficiency	83.8	89.3	90.4	90.3	89.6	88.5	
Speed	1790.1	1780.3	1769.9	1758.7	1746.6	1732.6	
Line Amperes	2.29	2.72	3.34	4.05	4.86	5.75	


Baldor Electric Company Fort Smith, Arkansas



Catalog	IDWNM3611T	NP VOLTS	230/460	ENCLOSURE	TENV	WYE CONN EQ CKT OHMS PER PHASE (BASE RATING, 20C)			
FRAME	184TC	NP AMPS	8.2/4.1	Base Volts	460	R1	1.640	X1	5.143
HP	3 HP	DUTY	Cont	Base AMPS	4.05	R2	1.260	X2	4.486
BASE SPEED	1800	MAX SAFE RPM	6000	Slip Hz	1.37	XM		120.167	
PHASE/HZ	3/60	AMB°C/INSUL	40/H	WK ² (lb-ft ²)	0.372				



Remarks: Calculated Data



BALDOR
A MEMBER OF THE ABB GROUP

DR BY ENR
CK BY
APP BY ENR
DATE 3/6/2013

A-C MOTOR
PERFORMANCE CURVES

36J565S952G1

ISSUE DATE 3/6/2013

