



Customer information packet

JL3510A

1HP, 1750RPM, 1PH, 60HZ, 56J, 3528L, TEFC, F1, N

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	56J
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Cap Start, Induction Run
Output @ Frequency	1.000 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	115.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	C UR US
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	12.900 A @ 115.0 V 6.700 A @ 230.0 V
Design Code	L
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	74.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	6.7 a
Insulation Class	F
Inverter Code	Not Inverter

Part detail

Revision	F
Type	AC
Mech. spec.	35F083
Base	
Status	PRD/A
Elec. spec.	35WGG240
Layout	35LYF083
Eff. date	04-09-2025
CD Diagram	CD0094
Poles	04
Leads	4#16 A&J,1#14 #4TH
Proprietary	False
Created date	11-14-2024

KVA Code	J
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	4 @ 16 AWG, A&J
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3528L
Mounting Arrangement	F1
Number of Poles	4
Overall Length	13.72 IN
Power Factor	68
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Ext Thread
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Fixed Opposite Standard
Shaft Slinger Indicator	No Slinger
Speed	1750 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Do Not Use Eve-Not Valid
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	Automatic Thermal Overload
Winding Thermal 1 Location	SB
Winding Thermal 2	None

Nameplate

NP1257L									
CAT.NO.	JL3510A								
SPEC.	35F083G240G2								
HP	1								
VOLTS	115/230								
AMP	12.9/6.7								
RPM	1750								
FRAME	56J			HZ	60		PH	1	
SER.F.	1.00	CODE	J	DES	L	CL	F		
NEMA-NOM-EFF	74	PF	68						
RATING	40C AMB-CONT								
CC									
DE	6205	ODE	6203						
ENCL	TEFC	SN							

AC Induction Motor Performance Data

Record # 88865

Typical performance - not guaranteed values

Winding: 35WGG240-R005			Type: 3528L		Enclosure: OPEN		
Nameplate Data			115 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		1	Full Load Torque		3.01 LB-FT		
Volts		115/230	Start Configuration		direct on line		
Full Load Amps		12.5/6.3	Breakdown Torque		9.7 LB-FT		
R.P.M.		1750	Pull-up Torque		9.3 LB-FT		
Hz	60	Phase	1	Locked-rotor Torque		16.5 LB-FT	
NEMA Design Code		L	KVA Code	J	Starting Current		96.2 A
Service Factor (S.F.)		1	No-load Current		9.53 A		
NEMA Nom. Eff.		74	Power Factor	68	Line-line Res. @ 25°C		0.525 Ω A Ph 1.17 Ω B Ph
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		36°C	
				Locked-rotor Power Factor		94.8	
				Rotor inertia		0.203 lb-ft²	

Load Characteristics 115 V, 60 Hz, 1 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	33	48	60	69	76	80
Efficiency	53.1	67.5	72.9	74.8	74.6	72.8
Speed	1786	1775	1763	1750	1735	1714
Line amperes	9.3	9.98	11.06	12.51	14.28	16.82

ABB Motors and Mechanical Inc.

WINDING # 35WGG240

Typical performance - not guaranteed values.

1 HP 1 PH 60 HZ 1750 RPM 115 V 3528L

TORQUES (LB-FT): PO=9.7 PU=9.3 LR=16.5 LRA=96.2





