



Customer information packet

JMEWDM3550T

1.5HP, 3500RPM, 3PH, 60HZ, 143JM, 3528M, TENV

Class - None

Division - Not Applicable

Specifications

Enclosure	TENV
Frame	143JM
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	1.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 208.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	2.000 A @ 230.0 V 4.000 A @ 208.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	85.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater

Part detail

Revision	N
Type	AC
Mech. spec.	35E2990
Base	
Status	PRD/A
Elec. spec.	35WGR445
Layout	35LYE2990
Eff. date	01-17-2025
CD Diagram	CD0005
Poles	02
Leads	9#18
Proprietary	False
Created date	12-04-2014

High Voltage Full Load Amps	2.0 a
Insulation Class	F
Inverter Code	Not Inverter
KVA Code	N
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3528M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	14.28 IN
Power Factor	87
Product Family	Wash Down
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	C-Face
Pulley Shaft Indicator	Tapped & Key
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	0.875 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	3500 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None

Winding Thermal 2

None

Nameplate

NP2179L									
CAT.NO.	JMEWDM3550T								
SPEC.	35E2990R445G1								
HP	1.5								
VOLTS	208-230/460								
AMP	4/2								
RPM	3500								
FRAME	143JM		HZ	60			PH	3	
SER.F.	1.15	CODE	N	DES	B	CLASS	F		
NEMA-NOM-EFF	85.5	PF	87						
RATING	40C AMB-CONT								
CC	010A								
DE	6206		ODE	6203					
ENCL	TENV	SN							
BLANK	20:1CT, 20:1VT, 1.00SF								

AC Induction Motor Performance Data

Record # 20327

Typical performance - not guaranteed values

Winding: 35WGR445-R006			Type: 3528M		Enclosure: TENV			
Nameplate Data			460 V, 60 Hz: High Voltage Connection					
Rated Output (HP)		1.5	Full Load Torque		2.3 LB-FT			
Volts		208-230/460	Start Configuration		direct on line			
Full Load Amps		4/2	Breakdown Torque		12 LB-FT			
R.P.M.		3500	Pull-up Torque		8.2 LB-FT			
Hz	60	Phase	3	Locked-rotor Torque		11 LB-FT		
NEMA Design Code		B	KVA Code	N	Starting Current		23.5 A	
Service Factor (S.F.)		1.15	No-load Current		0.9 A			
NEMA Nom. Eff.		85.5	Power Factor		87	Line-line Res. @ 25°C		6.95 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		73°C	
S.F. Amps			Temp. Rise @ S.F. Load		84°C			
			Locked-rotor Power Factor		48.4			

Load Characteristics 460 V, 60 Hz, 1.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	51	71	81	87	90	91	89
Efficiency	73.8	82.5	85.2	86.1	86	85.4	86
Speed	3568	3544	3519	3493	3466	3434	3477
Line amperes	1.1	1.3	1.6	1.9	2.3	2.8	2.14

ABB Motors and Mechanical Inc.

WINDING # 35WGR445

Typical performance - not guaranteed values.

1.5 HP 3 PH 60 HZ 3500 RPM 460 V 3528M

TORQUES (LB-FT) : PO=12 PU=8.2 LR=11 LRA=23.5





