



Customer information packet

JSM3155

2HP, 3450RPM, 3PH, 60HZ, 56YZ, 3430M, OPEN, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	OPEN
Frame	56YZ
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	2.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	2.700 A @ 460.0 V 5.400 A @ 230.0 V 6.400 A @ 208.0 V
Design Code	B
Drip Cover	Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	82.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Drip Cover Mounting
Front Shaft Indicator	None
Heater Indicator	No Heater

Part detail

Revision	S
Type	AC
Mech. spec.	34L408
Base	
Status	PRD/A
Elec. spec.	34WGX636
Layout	34LYL408
Eff. date	10-28-2024
CD Diagram	CD0005
Poles	02
Leads	9#18
Proprietary	False
Created date	08-05-2009

High Voltage Full Load Amps	2.7 a
Insulation Class	B
Inverter Code	Not Inverter
KVA Code	L
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Terminal Panel Or Lead Hole
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3430M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	13.40 IN
Power Factor	86
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Pool Pump
Pulley Shaft Indicator	Ext Thread & Tapped Hole
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.20
Shaft Diameter	0.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3450 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None

Winding Thermal 2

None

Nameplate

NP1256L									
CAT.NO.	JSM3155								
SPEC.	34L408X636								
HP	2								
VOLTS	230/460								
AMP	5.4/2.7								
RPM	3450								
FRAME	56YZ		HZ	60			PH	3	
SER.F.	1.20	CODE	L	DES	B	CLASS		B	
NEMA-NOM-EFF	82.5	PF	86						
RATING	40C AMB-CONT								
CC									
DE	6203		ODE	6203					
ENCL	OPEN	SN							
	SFA 6.2/3.1								

AC Induction Motor Performance Data

Record # 7504

Typical performance - not guaranteed values

Winding: 34WGX636-R001			Type: 3430M		Enclosure: OPSB		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		2	Full Load Torque		3 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		5.4/2.7	Breakdown Torque		13 LB-FT		
R.P.M.		3450	Pull-up Torque		11.5 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		15.1 LB-FT	
NEMA Design Code		B	KVA Code		L		
Service Factor (S.F.)		1.2	Starting Current		24.5 A		
NEMA Nom. Eff.		82.5	Power Factor		86		
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		42°C
S.F. Amps		6.2/3.1	Temp. Rise @ S.F. Load		52°C		

Load Characteristics 460 V, 60 Hz, 2 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	51	70	80	86	90	92	89
Efficiency	71.7	80	82.3	82.6	81.8	80.2	82
Speed	3550	3511	3470	3427	3376	3321	3386
Line amperes	1.5	1.8	2.2	2.7	3.2	3.9	3.1

ABB Motors and Mechanical Inc.

WINDING # 34WGX636

Typical performance - not guaranteed values.

2 HP 3 PH 60 HZ 3450 RPM 460 V 3430M

TORQUES (LB-FT): PO=13 PU=11.5 LR=15.1 LRA=24.5





