



Customer information packet

JXL050722A

0.75HP, 3500RPM, 1PH, 60HZ, 56J, 3524L, XPFC, F

Class - CLI GP D; CLII GP F,G

Division - Division I

Specifications

Enclosure	XPFC
Frame	56J
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	CLI GP D; CLII GP F,G
Haz Area Division	Division I
Motor Letter Type	Cap Start, Induction Run
Output @ Frequency	.750 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	115.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	CSA UL
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	4.600 A @ 230.0 V 9.300 A @ 115.0 V
Design Code	-
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	66.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Haz Area Temp Code	T4
Heater Indicator	No Heater
High Voltage Full Load Amps	4.6 a
Insulation Class	B

Part detail

Revision	D
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	35WG0498
Layout	35LYE382
Eff. date	05-01-2024
CD Diagram	CD0008
Poles	02
Leads	6#18,1#14 #4TH
Proprietary	False
Created date	03-29-2021

Inverter Code	Not Inverter
IP Rating	NONE
KVA Code	N
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3524L
Mounting Arrangement	F1
Number of Poles	2
Overall Length	15.66 IN
Power Factor	77
Product Family	General Purpose
Pulley Face Code	C-Face
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Speed	3500 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 1 Location	EP
Winding Thermal 2	None

Nameplate

NP0016XPSL					
NO.		CC			
SER. #					
SPEC	35-0000-1064				
CAT.NO.	JXL050722A				
H.P.	.75	T. CODE	T4		
VOLTS	115/230				
AMPS	9.3/4.6				
R.P.M.	3500 35WG0498				
HZ	60	PH	1	CLASS	B
SER.F.	1.00	DES	-	CODE	N
RATING	40C AMB-CONT				
FRAME	56J	NEMA NOM. EFF			66
	PF	77			
BLANK	NEMA MG-1 PART 5, IP54				

AC Induction Motor Performance Data

Record # 88186

Typical performance - not guaranteed values

Winding: 35WG0498			Type: 3524L		Enclosure: XPFC	
Nameplate Data			115 V, 60 Hz: Low Voltage Connection			
Rated Output (HP)		0.75	Full Load Torque		1.12 LB-FT	
Volts		115/230	Start Configuration		Unknown	
Full Load Amps		9.3/4.6	Breakdown Torque		3.63 LB-FT	
R.P.M.		3500	Pull-up Torque		3.18 LB-FT	
Hz	60	Phase	1	Locked-rotor Torque	5 LB-FT	
NEMA Design Code		- KVA Code	N	Starting Current	64.2 A	
Service Factor (S.F.)			1	No-load Current	5.62 A	
NEMA Nom. Eff.	66	Power Factor	77	Line-line Res. @ 25°C	0.62 Ω A Ph 1.76 Ω B Ph	
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load	39°C	
				Locked-rotor Power Factor	93.9	
				Rotor inertia	0.0664 lb-ft ²	

Load Characteristics 115 V, 60 Hz, 0.75 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	49	63	72	79	83	85
Efficiency	40.9	56.5	64.3	68.3	70.4	71.1
Speed	3570	3552	3533	3513	3491	3466
Line amperes	6.11	6.87	7.88	9.08	10.5	12

ABB Motors and Mechanical Inc.

WINDING # 35WG0498

Typical performance - not guaranteed values.

0.75 HP 1 PH 60 HZ 3500 RPM 115 V 3524L

TORQUES (LB-FT): PO=3.63 PU=3.18 LR=5 LRA=64.2





