



Customer information packet

KM3454

.25HP, 1735RPM, 3PH, 60HZ, 56C, 3410M, TEFC, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	56C
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	.250 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	.600 A @ 460.0 V 1.100 A @ 208.0 V 1.200 A @ 230.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	62.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	0.6 a

Part detail

Revision	D
Type	AC
Mech. spec.	34A063
Base	
Status	PRD/A
Elec. spec.	34WGR713
Layout	34LYA063
Eff. date	02-10-2025
CD Diagram	CD0005
Poles	04
Leads	9#18
Proprietary	False
Created date	11-20-2020

Insulation Class	B
Inverter Code	Not Inverter
KVA Code	L
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3410M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	11.35 IN
Power Factor	63
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.35
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1735 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1256L											
CAT.NO.	KM3454										
SPEC.	34A063R713										
HP	.25										
VOLTS	230/460										
AMP	1.2/.6										
RPM	1735										
FRAME	56C			HZ	60			PH	3		
SER.F.	1.35	CODE		L	DES	B	CLASS	B			
NEMA-NOM-EFF	62	PF		63							
RATING	40C AMB-CONT										
CC											
DE	6203			ODE	6203						
ENCL	TEFC	SN									
	SFA 1.32/0.66A										

AC Induction Motor Performance Data

Record # 85600

Preliminary Data Sheet

Winding: 34WGR713-R001			Type: 3410M		Enclosure: TEFC		
Nameplate Data				460 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		0.25		Full Load Torque		0.76 LB-FT	
Volts		230/460		Start Configuration		direct on line	
Full Load Amps		1.2/0.6		Breakdown Torque		2.77 LB-FT	
R.P.M.		1735		Pull-up Torque		1.83 LB-FT	
Hz	60	Phase	3	Locked-rotor Torque		2.03 LB-FT	
NEMA Design Code		B		KVA Code	L	Starting Current	2.89 A
Service Factor (S.F.)		1.35		No-load Current		0.545 A	
NEMA Nom. Eff.		63.4	Power Factor	63	Line-line Res. @ 25°C		98.9 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		57°C	
S.F. Amps		1.32/0.66		Temp. Rise @ S.F. Load		70°C	
				Locked-rotor Power Factor		84.1	
				Rotor inertia		0.0238 lb-ft²	

Load Characteristics 460 V, 60 Hz, 0.25 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	33	43	54	63	71	78	75
Efficiency	34.9	50.2	58.6	63.4	65.6	66.1	65.8
Speed	1781	1767	1751	1733	1713	1690	1697
Line amperes	0.547	0.552	0.568	0.598	0.64	0.695	0.662

ABB Motors and Mechanical Inc.

WINDING # 34WGR713

Typical performance - not guaranteed values.

0.25 HP 3 PH 60 HZ 1735 RPM 460 V 3410M

TORQUES (LB-FT): PO=2.77 PU=1.83 LR=2.03 LRA=2.89





