



Customer information packet

L1206-50

.33/KW .25, 1440RPM, 1PH, 50HZ, 48, 3418LC, OP

Class - None

Division - Not Applicable

Specifications

Enclosure	OPEN
Frame	48
Frame Material	Steel
Frequency	50.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Cap Start, Cap Run
Output @ Frequency	.330 HP @ 50 HZ
Phase	1
Synchronous Speed @ Frequency	1500 RPM @ 50 HZ
Voltage @ Frequency	110.0 V @ 50 HZ 220.0 V @ 50 HZ
Agency Approvals	CURUSEEV CE WEEE
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Design Code	-
Drip Cover	No Drip Cover
Duty Rating	CONT
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
Insulation Class	B
Inverter Code	Not Inverter
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing

Part detail

Revision	E
Type	AC
Mech. spec.	34F351
Base	
Status	PRD/A
Elec. spec.	34WGR753
Layout	34LYF351
Eff. date	07-07-2025
CD Diagram	CD0055
Poles	04
Leads	6#18
Proprietary	False
Created date	04-26-2023

Motor Lead Quantity/Wire Size	6 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3418LC
Mounting Arrangement	F1
Number of Poles	4
Overall Length	9.76 IN
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.35
Shaft Diameter	0.500 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1425 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4310L									
CAT.NO.	L1206-50								
SPEC.	34F351R753								
HP	.33/KW .25						PH	1	
VOLTS	110/220								
AMPS	4/2								
R.P.M. (1/MIN)	1440								
FRAME	48		HZ	50		I.P.	23		
SER.F.	1.35	CODE	K	DES.	-	CLASS	B		
F.L. AVG. EFF.	68.5		P.F.	81					
CC	USABLE AT 208V					N/A			
RATING	40C AMB-S1 CONT				WT.	11KG			
DE	6203		ODE	6203					
ENCL	OPEN	SN							
	SFA 5/2.5 IC01								
	IE2-50HZ 67 (75%),59 (50%)								

AC Induction Motor Performance Data

Record # 101558

Typical performance - not guaranteed values

Winding: 34WGR753-R001			Type: 3418LC		Enclosure: OPEN		
Nameplate Data			220 V, 50 Hz: High Voltage Connection				
Rated Output (KW)		.25	Full Load Torque		1.219 LB-FT		
Volts		110/220	Start Configuration		direct on line		
Full Load Amps		4/2	Breakdown Torque		3.6 LB-FT		
R.P.M.		1440	Pull-up Torque		3.51 LB-FT		
Hz	50	Phase	1	Locked-rotor Torque		4.85 LB-FT	
NEMA Design Code		-	KVA Code	K	Starting Current		13.4 A
Service Factor (S.F.)		1.35		No-load Current		1.28 A	
NEMA Nom. Eff.		68.5	Power Factor	81	Line-line Res. @ 25°C		7.0277 Ω A Ph 4.2595 Ω B Ph
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		33°C	
S.F. Amps		5/2.5		Temp. Rise @ S.F. Load		43°C	

Load Characteristics 220 V, 50 Hz, 0.25 KW

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	51	65	75	81	86	88	87
Efficiency	42.3	59.1	67.6	71.3	72.3	71.9	72.1
Speed	1485.9	1475.4	1462.6	1448.8	1433.1	1415	1426
Line amperes	1.33	1.46	1.69	1.96	2.29	2.67	2.44


ABB Motors and Mechanical Inc.

WINDING # 34WGR753

Typical performance - not guaranteed values.

0.25 KW 1 PH 50 HZ 1440 RPM 220 V 3418LC

TORQUES (LB-FT): PO=3.6 PU=3.51 LR=4.85 LRA=13.4



12/22/2025 ACPERF, record # 101558

