



Customer information packet

L3712T

10HP, 1740RPM, 1PH, 60HZ, 215T, 3748LC, TEFC, F

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	215T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Cap Start, Cap Run
Output @ Frequency	10.000 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	38.000 A @ 230.0 V
Design Code	L
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	86.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	38.0 a
Insulation Class	F
Inverter Code	Not Inverter

Part detail

Revision	S
Type	AC
Mech. spec.	37M293
Base	
Status	PRD/A
Elec. spec.	37WGT875
Layout	37LYM293
Eff. date	05-13-2024
CD Diagram	CD1084
Poles	04
Leads	2#10 A PH,2#14 B PH
Proprietary	False
Created date	01-07-2010

KVA Code	F
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Exit	Cap Box
Motor Lead Quantity/Wire Size	2 @ 10 AWG, A PH
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3748LC
Mounting Arrangement	F1
Number of Poles	4
Overall Length	20.52 IN
Power Factor	98
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	1.375 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1740 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1256L									
CAT.NO.	L3712T								
SPEC.	37M293T875								
HP	10								
VOLTS	230								
AMP	38								
RPM	1740								
FRAME	215T		HZ	60			PH	1	
SER.F.	1.00	CODE	F	DES	L	CLASS	F		
NEMA-NOM-EFF	86.5	PF	98						
RATING	40C AMB-CONT								
CC									
DE	6307		ODE	6206					
ENCL	TEFC	SN							

AC Induction Motor Performance Data

Record # 37141

Typical performance - not guaranteed values

Winding: 37WGT875-R001			Type: 3748LC		Enclosure: TEFC			
Nameplate Data			230 V, 60 Hz: Single Voltage Motor					
Rated Output (HP)		10	Full Load Torque		29.8 LB-FT			
Volts		230	Start Configuration		direct on line			
Full Load Amps		38	Breakdown Torque		84 LB-FT			
R.P.M.		1740	Pull-up Torque		56.4 LB-FT			
Hz	60	Phase	1	Locked-rotor Torque		76.8 LB-FT		
NEMA Design Code		L	KVA Code	F	Starting Current		234 A	
Service Factor (S.F.)		1		No-load Current		4.37 A		
NEMA Nom. Eff.		86.5	Power Factor		98	Line-line Res. @ 25°C		0.17 Ω A Ph 0.488 Ω B Ph
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		96°C		

Load Characteristics 230 V, 60 Hz, 10 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	96	98	98	98	97	95
Efficiency	75.4	86.2	87.7	86.8	84.1	79.4
Speed	1788	1775	1759	1741	1720	1696
Line amperes	10.7	18.9	28	37.7	49.1	64.9

ABB Motors and Mechanical Inc.

WINDING # 37WGT875

Typical performance - not guaranteed values.

10 HP 1 PH 60 HZ 1740 RPM 230 V 3748LC

TORQUES (LB-FT): PO=84 PU=56.4 LR=76.8 LRA=234





