



Customer information packet

M1504T

1-.5HP, 1715-870RPM, 3PH, 60HZ, 143T, 3524M, T

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	143T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	.500 HP @ 60 HZ 1.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	900 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 208.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	3.540 A @ 230.0 V 2.740 A @ 208.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	2.7 a
Insulation Class	F

Part detail

Revision	E
Type	AC
Mech. spec.	35AA001
Base	
Status	PRD/A
Elec. spec.	35WGG366
Layout	35LYAA001
Eff. date	10-28-2025
CD Diagram	CD0011
Poles	04/08
Leads	6#18
Proprietary	False
Created date	02-23-2023

Inverter Code	Not Inverter
KVA Code	H
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Quantity/Wire Size	6 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3524M
Mounting Arrangement	F1
Number of Poles	4 8
Overall Length	13.31 IN
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	0.875 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1715 rpm 870 rpm
Speed Code	2S-1W-CT
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1256L											
CAT.NO.	M1504T										
SPEC.	35AA001G366G1										
HP	1/.5										
VOLTS	208-230										
AMP	2.7-3.5										
RPM	1715-870										
FRAME	143T		HZ	60			PH	3			
SER.F.	1.15	CODE	H	DES	B	CLASS	F				
NEMA-NOM-EFF		PF									
RATING	40C AMB-CONT										
CC											
DE	6205		ODE	6203							
ENCL	TEFC	SN									
	SFA 3.43-3.09										

Accessories

Part number	Description	Multiplier
35-8762	C FACE KIT	A8
35EP1506A01SP	D-FLANGE KIT	A8

AC Induction Motor Performance Data

Record # 87900

Typical performance - not guaranteed values

Winding: 35WGG366-R001			Type: 3524M		Enclosure: TEFC			
Nameplate Data			230 V, 60 Hz: Low Speed Connection					
Rated Output (HP)		1/.5	Full Load Torque		3.01 LB-FT			
Volts		208-230	Start Configuration		direct on line			
Full Load Amps		2.74/3.54	Breakdown Torque		12.8 LB-FT			
R.P.M.		1715/870	Pull-up Torque		8.21 LB-FT			
Hz	60 Phase	3	Locked-rotor Torque		9.46 LB-FT			
NEMA Design Code		B	KVA Code	H	Starting Current		12.8 A	
Service Factor (S.F.)		1.15	No-load Current		3.51 A			
NEMA Nom. Eff.		0	Power Factor		0	Line-line Res. @ 25°C		10.2 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load				
				Locked-rotor Power Factor		80.4		
				Rotor inertia		0.173 lb-ft²		

Load Characteristics 230 V, 60 Hz, 0.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	23	30	37	44	50	56	48
Efficiency	29	44.5	53.7	59.4	62.9	64.9	61.5
Speed	893.2	887.2	880.9	874.1	866.9	858.9	870
Line amperes	3.5	3.51	3.55	3.61	3.72	3.86	3.68


ABB Motors and Mechanical Inc.


WINDING # 35WGG366

Typical performance - not guaranteed values.


0.5 HP 3 PH 60 HZ 874.1 RPM 230 V 3524M

TORQUES (LB-FT): PO=12.8 PU=8.21 LR=9.46 LRA=12.8






CD0011




LOW SPEED
(1D)



LINE

HIGH SPEED
(2Y)



LINE

- NOTES:
- 1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
 - 2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
 - 3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
 - 4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: REVISE TO SHOW OPTIONAL COLORS

REV. LTR: F

BY: JLP

REVISED: 01/21/99 5:04

TDR: 0171435

CD0011

FILE: DWG\142.wg

MDL: -

MTL: -

BALDOR ELECTRIC Co.

3PH, SV, 6 LEADS, 2-SPEED 1-WINDING CONSTANT TORQUE

CD0011