



Customer information packet

M1558T

5/1.3HP, 1725/850RPM, 3PH, 60HZ, 184T, 3640M

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	184T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	5.000 HP @ 60 HZ 1.300 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	900 RPM @ 60 HZ
Voltage @ Frequency	208.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	13.500 A @ 208.0 V 5.200 A @ 230.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	5.2 a

Part detail

Revision	AE
Type	AC
Mech. spec.	36A001
Base	
Status	PRD/A
Elec. spec.	36WGX366
Layout	36LYA001
Eff. date	05-20-2025
CD Diagram	CD0032
Poles	04/08
Leads	6#14
Proprietary	False
Created date	01-01-0001

Insulation Class	H
Inverter Code	Not Inverter
KVA Code	K
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	6 @ 14 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3640M
Mounting Arrangement	F1
Number of Poles	4
	8
Overall Length	18.04 IN
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1725 rpm
	850 rpm
Speed Code	2S-1W-VT
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1256L											
CAT.NO.	M1558T										
SPEC.	36A01X366										
HP	5/1.3										
VOLTS	208-230										
AMP	13.5/5.2										
RPM	1725/850										
FRAME	184T		HZ	60			PH	3			
SER.F.	1.15	CODE	K	DES	B		CLASS	H			
NEMA-NOM-EFF		PF									
RATING	40C AMB-CONT										
CC											
DE	6206		ODE	6205							
ENCL	TEFC	SN									

Accessories

Part number	Description	Multiplier
36-3301	C FACE KIT	A8
36EP1304A62SP	FLANGE MTD ENDPLATE 182-4TD -ENCL (LESS	A8

AC Induction Motor Performance Data

Record # 36966

Typical performance - not guaranteed values

Winding: 36WGX366-R004			Type: 3640M		Enclosure: TEFC			
Nameplate Data			230 V, 60 Hz: High Speed Connection					
Rated Output (HP)		5/1.3	Full Load Torque		15.1 LB-FT			
Volts		208-230	Start Configuration		direct on line			
Full Load Amps		13.5/5.2	Breakdown Torque		58 LB-FT			
R.P.M.		1725/850	Pull-up Torque		34 LB-FT			
Hz	60	Phase	3	Locked-rotor Torque		34 LB-FT		
NEMA Design Code		B	KVA Code	K	Starting Current		108 A	
Service Factor (S.F.)		1.15	No-load Current		7.1 A			
NEMA Nom. Eff.		0	Power Factor		0	Line-line Res. @ 25°C		0.936 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		96°C	
S.F. Amps					Temp. Rise @ S.F. Load		114°C	

Load Characteristics 230 V, 60 Hz, 5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	42	63	75	81	85	85	83
Efficiency	74.1	83	85.3	86	85.1	83.7	85.5
Speed	1785	1771	1756	1741	1721	1701	1729
Line amperes	7.7	9.1	11.1	13.5	16.1	19.3	15.1


ABB Motors and Mechanical Inc.

WINDING # 36WGX366

Typical performance - not guaranteed values.

5 HP 3 PH 60 HZ 1741 RPM 230 V 3640M

TORQUES (LB-FT): PO=58 PU=34 LR=34 LRA=108



AC Induction Motor Performance Data

Record # 36967

Typical performance - not guaranteed values

Winding: 36WGX366-R004			Type: 3640M	Enclosure: TEFC			
Nameplate Data			230 V, 60 Hz: Low Speed Connection				
Rated Output (HP)		5/1.3	Full Load Torque		7.7 LB-FT		
Volts		208-230	Start Configuration		direct on line		
Full Load Amps		13.5/5.2	Breakdown Torque		19.8 LB-FT		
R.P.M.		1725/850	Pull-up Torque		12.5 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		13 LB-FT	
NEMA Design Code		B	KVA Code	K	Starting Current		22 A
Service Factor (S.F.)		1.15	No-load Current		4.2 A		
NEMA Nom. Eff.		0	Power Factor	0	Line-line Res. @ 25°C		3.75 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		64°C	
S.F. Amps				Temp. Rise @ S.F. Load		74°C	

Load Characteristics 230 V, 60 Hz, 1.3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	27	40	53	63	67	70	65
Efficiency	52.2	65.8	70.8	72.3	72.2	71.1	72.2
Speed	890	881	871	862	847	834	853
Line amperes	4.4	4.6	4.8	5.2	6	6.9	5.68


ABB Motors and Mechanical Inc.


WINDING # 36WGX366

Typical performance - not guaranteed values.


1.3 HP 3 PH 60 HZ 862 RPM 230 V 3640M

TORQUES (LB-FT): PO=19.8 PU=12.5 LR=13 LRA=22





CD0032



- NOTES:
- 1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
 - 2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
 - 3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
 - 4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: REVISE TO SHOW OPTIONAL COLORS			
REV. LTR: E	BY: JLP	REVISED: 01/22/99 8:27	TDR: 0171435
CD0032		FILE: AAA00005145	MDL: -
		MTL: -	

BALDOR ELECTRIC Co.	
3PH, SV, 6 LEADS, 2-SPEED 1-WINDING VARIABLE TORQUE	

CD0032