



Customer information packet

M1719

.75/.33HP, 1720/1160RPM, 3PH, 60HZ, 56, 3520M

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	56
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	.750 HP @ 60 HZ .330 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	1.260 A @ 460.0 V
Design Code	-
Drip Cover	No Drip Cover
Duty Rating	CONT
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	0.9 a
Insulation Class	F
Inverter Code	Not Inverter
KVA Code	J

Part detail

Revision	D
Type	AC
Mech. spec.	35A011
Base	
Status	PRD/A
Elec. spec.	35WGG354
Layout	35LYA011
Eff. date	06-24-2025
CD Diagram	CD0013
Poles	04/06
Leads	6#18
Proprietary	False
Created date	02-23-2023

Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Quantity/Wire Size	6 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3520M
Mounting Arrangement	F1
Number of Poles	4 6
Overall Length	12.23 IN
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.25
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1160 rpm 1720 rpm
Speed Code	2S-2W-VT
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1256L									
CAT.NO.	M1719								
SPEC.	35A011G354								
HP	.75/.33								
VOLTS	460								
AMP	1.26/.89								
RPM	1720/1160								
FRAME	56		HZ	60		PH	3		
SER.F.	1.25	CODE	J	DES	-	CLASS	F		
NEMA-NOM-EFF		PF							
RATING	40C AMB-CONT								
CC									
DE	6205		ODE	6203					
ENCL	TEFC	SN							
	SFA 1.45/.93								

Accessories

Part number	Description	Multiplier
35-8762	C FACE KIT	A8
35EP1506A01SP	D-FLANGE KIT	A8

AC Induction Motor Performance Data

Record # 87827

Preliminary Data Sheet

Winding: 35WGG354-R001			Type: 3520M		Enclosure: TEFC			
Nameplate Data				460 V, 60 Hz: High Speed Connection				
Rated Output (HP)		.75/.33		Full Load Torque		2.29 LB-FT		
Volts		460		Start Configuration		direct on line		
Full Load Amps		1.26/.89		Breakdown Torque		6.93 LB-FT		
R.P.M.		1720/1160		Pull-up Torque		4.25 LB-FT		
Hz		60	Phase	3	Locked-rotor Torque		5.54 LB-FT	
NEMA Design Code		- KVA Code		J	Starting Current		7.21 A	
Service Factor (S.F.)		1.25		No-load Current		0.865 A		
NEMA Nom. Eff.		0	Power Factor		0	Line-line Res. @ 25°C		44.1 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		60°C		
S.F. Amps		1.45/.93		Temp. Rise @ S.F. Load		77°C		
				Locked-rotor Power Factor		89.5		
				Rotor inertia		0.144 lb-ft²		

Load Characteristics 460 V, 60 Hz, 0.75 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	37	54	69	76	83	87	83
Efficiency	54.3	67.9	71.9	73	72	69.5	72
Speed	1781	1763	1744	1722	1695	1662	1695
Line amperes	0.907	0.994	1.08	1.26	1.45	1.69	1.45


ABB Motors and Mechanical Inc.

WINDING # 35WGG354

Typical performance - not guaranteed values.

0.75 HP 3 PH 60 HZ 1722 RPM 460 V 3520M

TORQUES (LB-FT) : PO=6.93 PU=4.25 LR=5.54 LRA=7.21



AC Induction Motor Performance Data

Record # 87828

Preliminary Data Sheet

Winding: 35WGG354-R001			Type: 3520M		Enclosure: TEFC			
Nameplate Data			460 V, 60 Hz: Low Speed Connection					
Rated Output (HP)		.75/.33	Full Load Torque		1.48 LB-FT			
Volts		460	Start Configuration		direct on line			
Full Load Amps		1.26/.89	Breakdown Torque		5.93 LB-FT			
R.P.M.		1720/1160	Pull-up Torque		2.76 LB-FT			
Hz	60	Phase	3	Locked-rotor Torque		4.06 LB-FT		
NEMA Design Code		-	KVA Code	J	Starting Current		4.11 A	
Service Factor (S.F.)		1.25		No-load Current		0.846 A		
NEMA Nom. Eff.		0	Power Factor		0	Line-line Res. @ 25°C		81.1 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load				
S.F. Amps		1.45/.93		Temp. Rise @ S.F. Load				
				Locked-rotor Power Factor		89.5		
				Rotor inertia		0.144 lb-ft²		

Load Characteristics 460 V, 60 Hz, 0.33 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	27	36	45	54	61	68	61
Efficiency	34.1	50.2	58.9	63.9	66.7	68.1	66.7
Speed	1192	1186	1179	1172	1164	1155	1164
Line amperes	0.844	0.851	0.87	0.901	0.944	1	0.944

ABB Motors and Mechanical Inc.

WINDING # 35WGG354

Typical performance - not guaranteed values.

0.33 HP 3 PH 60 HZ 1172 RPM 460 V 3520M

TORQUES (LB-FT): PO=5.93 PU=2.76 LR=4.06 LRA=4.11

