



Customer information packet

M1723T

3/1.3HP, 1725/1140RPM, 3PH, 60HZ, 184T, 3634M

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	184T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	3.000 HP @ 60 HZ 1.300 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	4.000 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	2.6 a
Insulation Class	F
Inverter Code	Not Inverter

Part detail

Revision	AB
Type	AC
Mech. spec.	36A001
Base	
Status	PRD/A
Elec. spec.	36WGY048
Layout	36LYA001
Eff. date	05-20-2025
CD Diagram	CD0013
Poles	04/06
Leads	6#16
Proprietary	False
Created date	01-01-0001

KVA Code	G
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	6 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3634M
Mounting Arrangement	F1
Number of Poles	4 6
Overall Length	16.54 IN
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1140 rpm 1725 rpm
Speed Code	2S-2W-VT
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1256L											
CAT.NO.	M1723T										
SPEC.	36A01Y48										
HP	3/1.3										
VOLTS	460										
AMP	4/2.6										
RPM	1725/1140										
FRAME	184T		HZ	60			PH	3			
SER.F.	1.15	CODE	G	DES	B	CLASS	F				
NEMA-NOM-EFF		PF									
RATING	40C AMB-CONT										
CC											
DE	6206		ODE	6205							
ENCL	TEFC	SN									

Accessories

Part number	Description	Multiplier
36-3301	C FACE KIT	A8
36EP1304A62SP	FLANGE MTD ENDPLATE 182-4TD -ENCL (LESS	A8

AC Induction Motor Performance Data

Record # 15218

Typical performance - not guaranteed values

Winding: 36WGY048-R002			Type: 3634M		Enclosure: TEFC		
Nameplate Data			460 V, 60 Hz: High Speed Connection				
Rated Output (HP)		3/1.3	Full Load Torque		9.2 LB-FT		
Volts		460	Start Configuration		direct on line		
Full Load Amps		4/2.6	Breakdown Torque		28 LB-FT		
R.P.M.		1725/1140	Pull-up Torque		13 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		19 LB-FT	
NEMA Design Code		B	KVA Code	G	Starting Current		24 A
Service Factor (S.F.)		1.15		No-load Current		1.5 A	
NEMA Nom. Eff.		0	Power Factor	0	Line-line Res. @ 25°C		9.85 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load			

Load Characteristics 460 V, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	54	75	85	90	92	92	91
Efficiency	74.3	81.5	82.4	81.2	78.7	75.2	79.7
Speed	1781	1763	1742	1718	1690	1655	1701
Line amperes	1.75	2.3	3	3.85	4.85	6.1	4.45


ABB Motors and Mechanical Inc.

WINDING # 36WGY048

Typical performance - not guaranteed values.

3 HP 3 PH 60 HZ 1718 RPM 460 V 3634M

TORQUES (LB-FT): PO=28 PU=13 LR=19 LRA=24



AC Induction Motor Performance Data

Record # 15219

Typical performance - not guaranteed values

Winding: 36WGY048-R002			Type: 3634M		Enclosure: TEFC		
Nameplate Data			460 V, 60 Hz: Low Speed Connection				
Rated Output (HP)		3/1.3	Full Load Torque		5.9 LB-FT		
Volts		460	Start Configuration		direct on line		
Full Load Amps		4/2.6	Breakdown Torque		17 LB-FT		
R.P.M.		1725/1140	Pull-up Torque		9.2 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		10.3 LB-FT	
NEMA Design Code		B	KVA Code	G	Starting Current		12 A
Service Factor (S.F.)		1.15	No-load Current		1.95 A		
NEMA Nom. Eff.		0	Power Factor	0	Line-line Res. @ 25°C		17.7 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		

Load Characteristics 460 V, 60 Hz, 1.3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	29	43	55	65	72	78	69
Efficiency	52.3	66.9	72.7	75	75.5	74.9	75.3
Speed	1190	1181	1172	1161	1150	1137	1154
Line amperes	2	2.1	2.25	2.5	2.8	3.1	2.7

ABB Motors and Mechanical Inc.

WINDING # 36WGY048

Typical performance - not guaranteed values.

1.3 HP 3 PH 60 HZ 1161 RPM 460 V 3634M

TORQUES (LB-FT): PO=17 PU=9.2 LR=10.3 LRA=12

