



Customer information packet

PSC3416A

.33HP, 1625RPM, 1PH, 60HZ, 48Z, 3414C, TEAO, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEAO
Frame	48Z
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Oil Capacitor Start and Run
Output @ Frequency	.330 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	115.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	1.800 A @ 230.0 V 3.600 A @ 115.0 V
Design Code	N
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	62.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Terminal Panel
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	1.8 a

Part detail

Revision	S
Type	AC
Mech. spec.	34G144
Base	
Status	PRD/A
Elec. spec.	34WGW426
Layout	34LYG144
Eff. date	04-30-2025
CD Diagram	CD0028
Poles	04
Leads	7#18
Proprietary	False
Created date	01-01-0001

Insulation Class	B
Inverter Code	Not Inverter
KVA Code	-
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Exit	Terminal Panel Or Lead Hole
Motor Lead Quantity/Wire Size	7 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3414C
Mounting Arrangement	F1
Number of Poles	4
Overall Length	11.34 IN
Power Factor	95
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	0.500 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1625 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	Automatic Thermal Overload
Winding Thermal 1 Location	SB

Nameplate

NP1257L											
CAT.NO.	PSC3416A										
SPEC.	34G144W426										
HP	.33 AIR OVER										
VOLTS	115/230										
AMP	3.6/1.8										
RPM	1625										
FRAME	48Z			HZ	60			PH	1		
SER.F.	1.00	CODE	-	DES	N	CL	B				
NEMA-NOM-EFF	62	PF	95								
RATING	40C AMB-CONT										
CC											
DE	6203	ODE	6203								
ENCL	TEAO	SN									

AC Induction Motor Performance Data

Record # 6977

Typical performance - not guaranteed values

Winding: 34WGW426-R001			Type: 3414C		Enclosure: TEAO		
Nameplate Data			230 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		.33 AIR OVER	Full Load Torque		1 LB-FT		
Volts		115/230	Start Configuration		direct on line		
Full Load Amps		3.6/1.8	Breakdown Torque		2 LB-FT		
R.P.M.		1625	Pull-up Torque		0.7 LB-FT		
Hz	60	Phase	1	Locked-rotor Torque		0.7 LB-FT	
NEMA Design Code		N	KVA Code	-	Starting Current		5.5 A
Service Factor (S.F.)		1		No-load Current		0.9 A	
NEMA Nom. Eff.		62	Power Factor	95	Line-line Res. @ 25°C		10.7 Ω A Ph 10.7 Ω B Ph
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load			

Load Characteristics 230 V, 60 Hz, 0.33 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	94	97	99	99	99	99
Efficiency	25.8	42.5	53.6	60.7	64.7	65.6
Speed	1759	1734	1705	1671	1628	1570
Line amperes	1.1	1.3	1.5	1.75	2.05	2.45

ABB Motors and Mechanical Inc.

WINDING # 34WG426

Typical performance - not guaranteed values.

0.33 HP 1 PH 60 HZ 1625 RPM 230 V 3414C

TORQUES (LB-FT) : PO=2 PU=0.7 LR=0.7 LRA=5.5





