



Customer information packet

SPJMM3611T-G

3HP, 1765RPM, 3PH, 60HZ, 182JM, 3642M, TEFC, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	182JM
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	3.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	WEEE
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	4.200 A @ 460.0 V 8.400 A @ 230.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	4.2 a
Insulation Class	H
Inverter Code	Inverter Duty

Part detail

Revision	A
Type	AC
Mech. spec.	36EE007
Base	
Status	PRD/A
Elec. spec.	36WGZ631
Layout	36LYEE007
Eff. date	11-19-2025
CD Diagram	CD0005
Poles	04
Leads	9#16
Proprietary	False
Created date	08-12-2025

KVA Code	L
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	2700 rpm
Motor Lead Quantity/Wire Size	9 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3642M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	19.55 IN
Power Factor	74
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Tapped & Key
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.25
Shaft Diameter	0.875 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1765 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4423A01A01L												
CAT #	SPJMM3611T-G					WGT	93	LBS				
SPEC	36EE007Z631					ENCL	TEFC					
SER #						CC	010A	IP	54			
HP	3					MAG CUR	5.6/2.8					
VOLTS	230/460					NEMA NOM. EFF					91	
AMPS	8.4/4.2					PF	74					
RATING	40C AMB-CONT											
RPM	1765					MAX RPM	2700					
FRAME	182JM	HZ	60			CODE	L	CLASS	H			
SER.F.	1.25	SF AMP	10.2/5.1				PH	3	DES	A		
DE	6207		ODE	6205								
LUBRICATION	POLYREX EM											
ID LOGO	INVERTER TYPE		VPWM		CHP	60	TO	90	1.5:1			
ID LOGO	WK2	0.39	CT	6	TO	60	10:1					
ID LOGO	SL HZ	1.2	VT	3	TO	60	20:1					

AC Induction Motor Performance Data

Record # 112292

Preliminary Data Sheet

Winding: 36WGZ631-R004			Type: 3642M		Enclosure: TEFC			
Nameplate Data			460 V, 60 Hz: High Voltage Connection					
Rated Output (HP)		3	Full Load Torque		8.92 LB-FT			
Volts		230/460	Start Configuration		direct on line			
Full Load Amps		8.4/4.2	Breakdown Torque		45.1 LB-FT			
R.P.M.		1765	Pull-up Torque		23 LB-FT			
Hz	60	Phase	3	Locked-rotor Torque		28.5 LB-FT		
NEMA Design Code		A	KVA Code	L	Starting Current		41.8 A	
Service Factor (S.F.)		1.25	No-load Current		2.76 A			
NEMA Nom. Eff.		91	Power Factor		74	Line-line Res. @ 25°C		2.78 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		39°C	
S.F. Amps		10.2/5.1	Temp. Rise @ S.F. Load		49°C			
			Locked-rotor Power Factor		40			
			Rotor inertia		0.391 lb-ft²			

Load Characteristics 460 V, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	30	49	62	71	76	80	76
Efficiency	81.5	88.6	90.6	91.2	91.1	90.6	91.1
Speed	1792	1786	1779	1772	1765	1757	1765
Line amperes	2.91	3.26	3.75	4.37	5.07	5.83	5.07

ABB Motors and Mechanical Inc.

WINDING # 36WGZ631

Typical performance - not guaranteed values.

3 HP 3 PH 60 HZ 1765 RPM 460 V 3642M

TORQUES (LB-FT): PO=45.1 PU=23 LR=28.5 LRA=41.8





