



Customer information packet

SPM44256T-4

250HP, 1190RPM, 3PH, 60HZ, L449T, A44208M, TEF

Class - CLI GP A,B,C,D; CLII GP F,G

Division - Division II

Specifications

Enclosure	TEFC
Frame	L449T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CLI GP A,B,C,D; CLII GP F,G
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	250.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	NEMA PREMIUM CURUSEEV CCSAUSEEV
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Current @ Voltage	293.000 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	96.2 %
Feedback Device	NO FEEDBACK
Frame Prefix	L
Heater Indicator	No Heater
High Voltage Full Load Amps	293.0 a
Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	G
Lifting Lugs	Standard Lifting Lugs
Max Speed	1800 rpm

Part detail

Revision	F
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	A44WG6758
Layout	617439-185
Eff. date	01-28-2025
CD Diagram	416820-008
Poles	06
Leads	6#1 (02 per group) Y
Proprietary	False
Created date	11-02-2023


Motor Lead Quantity/Wire Size	12 @ 1 AWG
Motor Standards	NEMA
Motor Type	A44208M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	60.34 IN
Power Factor	83
Product Family	General Industrial
Pulley End Bearing Type	Ball
Service Factor	1.15
Shaft Diameter	3.375 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1190 rpm
Speed Code	Single Speed
Starting Method	Wye Start - Delta Run
Thermal Device - Winding	None

Nameplate

NP2496L	
MOBIL POLYREX EM	

NP4562L



CAT NO	SPM44256T-4			SPEC NO.			A44-5011-6758			I.P.		55																
HP	250		AMPS		292		VOLTS		460		DESIGN		A															
FRAME SIZE	L449T		RPM		1190		MAX RPM		1800		HZ		60															
D.E. BRG.	110BC02J30X			PH.3		3		DUTY		CONT		INSUL.CLASS		F														
O.D.E. BRG.	90BC03J30X				TYPE P		P		ENCL		TEFC		SF		1.15		CODE		K									
POWER FACTOR	83		MAX CORR KVAR			65.38			NEMA NOM EFFICIENCY				96.2		MOTOR WEIGHT			LBS										
CL.I,DIV 2,GRP:	A,B,C,D		T.CODE		T3C		CL.1,ZONE 2,GRP:					IIA,IIB,IIC		T=		160		INVERTER T.CODE		T2D								
CL.II,DIV 2,GRP:	F,G		T.CODE		T3C		CL II ZONE 22 GRPS IIIB					T=		160		INVERTER T.CODE		T3C										
ID LOGO	INV TYPE:		VPWM		CT		30		TO		60		VT		3		TO		60		CHP		60		TO		90	
ID LOGO	1.0 SF VPWM			WK2		187		LBFT2		SL HZ		0.36		MAG CUR		105												
SER.NO.				MEETS INTENT OF IEEE-45						FOR WEATHER PROTECTION																		



416820-008

A-C MOTOR
CONNECTION DIAGRAM

STANDARD 6 LEAD Y START – DELTA RUN



< N. P. 1767-DC >

REV. DESC: ADDED T4 TO Y CONNECT DIAGRAM		
REV. LTR: D	VERSION: 04	TDR: 000000847713
FILE: \RAG\00001\808	REVISED: 10: 41: 26 04/08/2014	BY: RAGJSS1
MTL: —		

BALDOR

CONNECT DIAGRAM STD 6 LEAD Y START DELTA RUN
SH 1 of 1

416820-008