



Customer information packet

SUM76004-4

60HP, RPM, 3PH, 60HZ, 320TY, XPNV, V1

Class - CLI GP C,D

Division - Not Applicable

Specifications

Enclosure	XPNV
Frame	320TY
Frequency	60.00 Hz
Haz Area Class and Group	CLI GP C,D
Haz Area Division	Not Applicable
Phase	3
Agency Approvals	C UR US CCSA US
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Cable Length	25 FOOT
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Haz Area Temp Code	T3C
Heater Indicator	No Heater
Insulation Class	F
Inverter Code	Not Inverter
IP Rating	NONE
KVA Code	G
Lifting Lugs	Standard Lifting Lugs
Motor Standards	NEMA
Mounting Arrangement	V1
Number of Poles	4
Product Family	Pump - Centrifugal
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Service Factor	1.15
Shaft Diameter	2.499 IN
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Starting Method	Direct on line

Part detail

Revision	E
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	85944
Layout	619738-007
Eff. date	12-10-2024
CD Diagram	416820-036
Poles	///
Leads	
Proprietary	False
Created date	05-06-2021

Thermal Device - Winding

Normally Closed Thermostat

Nameplate

000613007MS											
CAT.NO.	SUM76004-4		SPEC NO.		S32-CWS0-0009						
SER.NO.				FRAME SIZE		320TY					
CONSTANT HP RPM	HP	RPM	VOLTS		AMPS		HZ		S.F.		
	60	1775	460		76		6-60		1.00		
	60	1775	460		76		60		1.15		
			@		HZ	CODE	G				
	TYPE	P	INSUL.CLASS		F	TORQUE		10:1_VT		DESIGN	B
D.E. BRG.	85BJ33J30X		ENCL	TENV		DUTY	15 MIN		PH	3	
O.D.E. BRG.	50BC03JPG30A		MOTOR WEIGHT					AMB	40		
	*15 MIN IN AIR ;SUB. IN										
	SEWAGE / WATER ONLY										

000613007RC		
CLASS I GROUP	C D X	NO.
CLASS II GROUP	X X X	
OPERATING TEMP CODE	T3C	

000692000MB	
SUITABLE FOR OPERATION ON PWM	
INVERTER EQUIPPED WITH IGBT	
DEVICES AND CAPABLE OF	
CARRIER	
FREQUENCY OF 2 KHZ MINIMUM	

000613007MS

CAT.NO.	SUM76004-4		SPEC NO.		S32-CWS0-0009				
SER.NO.				FRAME SIZE	320TY				
	HP	RPM	VOLTS	AMPS	HZ	S.F.			
	60	1775	460		76	6-60	1.00		
	60	1775	460		76	60	1.15		
CONSTANT HP RPM		@		HZ	CODE	G			
TYPE	P	INSUL.CLASS		F	TORQUE	10:1_VT		DESIGN	B
D.E. BRG.	85BJ33J30X			ENCL	TENV	DUTY	15 MIN	PH	3
O.D.E. BRG.	50BC03JPG30A			MOTOR WEIGHT			AMB	40	
	*15 MIN IN AIR ;SUB. IN								
	SEWAGE / WATER ONLY								

AC induction motor performance data

Record #85944 - Typical performance - not guaranteed values

Winding	12WGA0156
Type	1272M
Enclosure	XPNV

Nameplate data

Rated Output	60
Volts	460
Full Load Amps	76
R.P.M.	1775
Hz	60
Phase	3
KVA Code	G
S.F.	1.15
NEMA Nom. Eff.	94.5
Power Factor	79
Duty	15 MIN
S.F. Amps	

460 V, 60 Hz:

Single Voltage Motor

Full Load Torque	178 LB-FT
Start Configuration	direct on line
Breakdown Torque	412 LB-FT
Pull-up Torque	192 LB-FT
Locked-rotor Torque	266 LB-FT
Starting Current	431 A
No-load Current	32.82
Line-line Res. @ 25°C	0.131 Ω
Temp. Rise @ Rated Load	41°C
Temp. Rise @ S.F. Load	50°C
Locked-rotor Power Factor	27.3
Rotor inertia	7.19 lb-ft ²

Load Characteristics 460 V, 60 Hz, 60 HP


% of Rated Load	NL	25	50	75	100	125	150	SF
Power Factor	4	41	62	74	79	81	81	87
Efficiency	0	91.4	94.2	94.4	94.5	93.3	92	92.9
Speed	1799	1794	1788	1781	1774	1766	1755	1773
Line amperes	32.82	37.36	47.43	60.09	75.5	92.53	116	101


SPEED TORQUE / SPEED CURRENT CURVES

BALDOR • RELIANCE

12WGA0156


60HP 460V 60HZ





416820-036

A-C MOTOR
CONNECTION DIAGRAM
STANDARD 3 LEAD CONNECTED



(N.P. 1575-BA)




416820-036

REV. DESC: LOADED TO BUS, C/R 335225		
REV. LTR: -	VERSION: 00	TDR: 000000538207
FILE: \MGA\00000\682		REVISED: 11: 54: 06 04/30/2010
MTL: -		BY: RAGRA

BALDOR

CONN DIAG - STANDARD 3 LEAD
SH 1 of 1

CD0006



- NOTES:
- 1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
 - 2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
 - 3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
 - 4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
 - 5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007		
REV. LTR: E	VERSION: 01	TDR: 000001099922
FILE: \AAA\00005\141	REVISED: 10: 24: 49 02/19/2019	BY: ENBRIRO
MTL: —		

BALDOR - RELIANCE®

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1