



Customer information packet

UCC10150

10-15HP, 3450RPM, 1PH, 60HZ, 215Z, 3740C, OPEN

Class - None

Division - Not Applicable

Specifications

Enclosure	OPEN
Frame	215Z
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Oil Capacitor Start and Run
Output @ Frequency	15.000 HP @ 60 HZ 10.000 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	41.000 A @ 230.0 V
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	83.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	41.0 a
Insulation Class	F
Inverter Code	Not Inverter

Part detail

Revision	AT
Type	AC
Mech. spec.	37E764
Base	
Status	PRD/A
Elec. spec.	37WGW977
Layout	37LYE764
Eff. date	01-02-2025
CD Diagram	CD0127
Poles	02
Leads	2#8 A PH,2#14 B PH 32" LG Y
Proprietary	False
Created date	01-01-0001

KVA Code	C
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Pipe Or Pipe Adaptor
Motor Lead Quantity/Wire Size	2 @ 8 AWG, A PH
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3740C
Mounting Arrangement	F1
Number of Poles	2
Overall Length	18.57 IN
Power Factor	98
Product Family	General Purpose
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	Standard
Pulley Shaft Indicator	Tapped & Key
Rodent Screen	Included
Service Factor	1.00
Shaft Diameter	1.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3450 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1279L									
CAT.NO.	UCC10150								
SPEC.	37E764W977								
HP	10-15 AIR OVER								
VOLTS	230								
AMP	41-57								
RPM	3450								
FRAME	215Z		HZ	60		PH	1		
SER.F.	1.00		CODE	C		DES	-		CL F
NEMA-NOM-EFF	83		PF	98					
RATING	40C AMB-CONT								
CC									
DE	6307		ODE	6206					
ENCL	OPEN	SN							

NP1263L

CAT.NO.	UCC10150									
SPEC.	37E764W977									
HP	10-15 AIR OVER									
VOLTS	230									
AMP	41-57									
RPM	3450									
FRAME	215Z				HZ	60			PH	1
SER.F.	1.00		CODE	C		DES	-		CL	F
NEMA-NOM-EFF	83		PF	98						
RATING	40C AMB-CONT									
CC										
DE	6307		ODE		6206					
ENCL	OPEN		SN							

AC Induction Motor Performance Data

Record # 11959

Typical performance - not guaranteed values

Winding: 37WGW977-R001			Type: 3740C		Enclosure: OPAO		
Nameplate Data			230 V, 60 Hz: Single Voltage Motor				
Rated Output (HP)		10-15 AIR OVER	Full Load Torque		22.8 LB-FT		
Volts		230	Start Configuration		direct on line		
Full Load Amps		41-57	Breakdown Torque		46 LB-FT		
R.P.M.		3450	Pull-up Torque		5.3 LB-FT		
Hz	60	Phase	1	Locked-rotor Torque		6.5 LB-FT	
NEMA Design Code		-	KVA Code	C	Starting Current		245 A
Service Factor (S.F.)		1		No-load Current		16.3 A	
NEMA Nom. Eff.		83	Power Factor	98	Line-line Res. @ 25°C		0.196 Ω A Ph 0.344 Ω B Ph
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load			

Load Characteristics 230 V, 60 Hz, 15 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	78	92	98	99	99	99
Efficiency	68.7	81.5	85.1	85.2	83.2	79.1
Speed	3565	3533	3496	3453	3400	3324
Line amperes	22.7	32.4	43.9	57.4	73.1	93.2

ABB Motors and Mechanical Inc.

WINDING # 37WGW977

Typical performance - not guaranteed values.

15 HP 1 PH 60 HZ 3450 RPM 230 V 3740C

TORQUES (LB-FT): PO=46 PU=5.3 LR=6.5 LRA=245





