



Customer information packet

UCC7100

7.5HP, 3450RPM, 1PH, 60HZ, 184TZ, 3640C, OPEN

Class - None

Division - Not Applicable

Specifications

Enclosure	OPEN
Frame	184TZ
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Oil Capacitor Start and Run
Output @ Frequency	7.500 HP @ 60 HZ 10.000 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	28.000 A @ 230.0 V
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	85.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	28.0 a
Insulation Class	F
Inverter Code	Not Inverter

Part detail

Revision	AP
Type	AC
Mech. spec.	36F548
Base	
Status	PRD/A
Elec. spec.	36WGW881
Layout	36LYF548
Eff. date	01-02-2025
CD Diagram	CD0127
Poles	02
Leads	2#10 A PH,2#16 B PH 30" LG Y
Proprietary	False
Created date	01-01-0001

KVA Code	D
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Pipe Or Pipe Adaptor
Motor Lead Quantity/Wire Size	2 @ 10 AWG, A PH
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3640C
Mounting Arrangement	F1
Number of Poles	2
Overall Length	16.88 IN
Power Factor	95
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Tapped & Key
Rodent Screen	Included
Service Factor	1.00
Shaft Diameter	1.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3450 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1279L									
CAT.NO.	UCC7100								
SPEC.	36F548W881								
HP	7.5-10 AIR OVER								
VOLTS	230								
AMP	28-39								
RPM	3450								
FRAME	184TZ	HZ		60		PH		1	
SER.F.	1.00	CODE		D	DES		-	CL	F
NEMA-NOM-EFF	85.5	PF		95					
RATING	40C AMB-CONT								
CC									
DE	6206	ODE		6205					
ENCL	OPEN	SN							

NP1263L

CAT.NO.	UCC7100									
SPEC.	36F548W881									
HP	7.5-10 AIR OVER									
VOLTS	230									
AMP	28-39									
RPM	3450									
FRAME	184TZ			HZ	60		PH	1		
SER.F.	1.00	CODE	D	DES	-	CL	F			
NEMA-NOM-EFF	85.5	PF	95							
RATING	40C AMB-CONT									
CC										
DE	6206	ODE	6205							
ENCL	OPEN	SN								

AC Induction Motor Performance Data

Record # 10869

Typical performance - not guaranteed values

Winding: 36WGW881-R001			Type: 3640C		Enclosure: OPAO			
Nameplate Data			230 V, 60 Hz: Single Voltage Motor					
Rated Output (HP)		7.5-10 AIR OVER	Full Load Torque		15.3 LB-FT			
Volts		230	Start Configuration		direct on line			
Full Load Amps		28-39	Breakdown Torque		30 LB-FT			
R.P.M.		3450	Pull-up Torque		2.3 LB-FT			
Hz	60	Phase	1	Locked-rotor Torque		2.6 LB-FT		
NEMA Design Code		-	KVA Code	D	Starting Current		187 A	
Service Factor (S.F.)		1		No-load Current		7 A		
NEMA Nom. Eff.		85.5	Power Factor		95	Line-line Res. @ 25°C		0.229 Ω A Ph 0.877 Ω B Ph
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load				

Load Characteristics 230 V, 60 Hz, 10 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	87	94	96	96	95	94
Efficiency	72.4	82.3	84.4	83.9	81.7	78
Speed	3564	3529	3490	3445	3390	3319
Line amperes	12.9	21	30.2	40.4	52	66.1

ABB Motors and Mechanical Inc.

WINDING # 36GW881

Typical performance - not guaranteed values.

10 HP 1 PH 60 HZ 3450 RPM 230 V 3640C

TORQUES (LB-FT): PO=30 PU=2.3 LR=2.6 LRA=187





