



Customer information packet

VBM3154

1.5HP, 1735RPM, 3PH, 60HZ, 56C, 3518M, OPEN, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	OPEN
Frame	56C
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	1.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	208.0 V @ 60 HZ 230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	5.200 A @ 230.0 V 5.000 A @ 208.0 V 2.600 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	80.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater

Part detail

Revision	C
Type	AC
Mech. spec.	35E056
Base	
Status	PRD/A
Elec. spec.	35WGZ926
Layout	35LYE056
Eff. date	06-17-2024
CD Diagram	CD0005
Poles	04
Leads	9#18
Proprietary	False
Created date	03-11-2022

High Voltage Full Load Amps	2.6 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	L
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3518M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	15.26 IN
Power Factor	66
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1735 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1256L									
CAT.NO.	VBM3154								
SPEC.	35E056Z926G1								
HP	1.5								
VOLTS	208-230/460								
AMP	5-5.2/2.6								
RPM	1735								
FRAME	56C		HZ	60			PH	3	
SER.F.	1.15		CODE	L	DES	B	CLASS	F	
NEMA-NOM-EFF	80		PF	66					
RATING	40C AMB-CONT								
CC									
DE	6205		ODE	6203					
ENCL	OPEN		SN						
	SFA 5.56-5.6/2.8								

AC Induction Motor Performance Data

Record # 88676

Typical performance - not guaranteed values

Winding: 35WGZ926-R001			Type: 3518M		Enclosure: OPEN		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		1.5	Full Load Torque		4.54 LB-FT		
Volts		208-230/460	Start Configuration		direct on line		
Full Load Amps		5-5.2/2.6	Breakdown Torque		19.18 LB-FT		
R.P.M.		1735	Pull-up Torque		15.17 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		17.41 LB-FT	
NEMA Design Code		B	KVA Code	L	Starting Current		18.38 A
Service Factor (S.F.)		1.15		No-load Current		1.86 A	
NEMA Nom. Eff.		80	Power Factor	66	Line-line Res. @ 25°C		12.8 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		52°C	
S.F. Amps		5.56-5.6/2.8		Temp. Rise @ S.F. Load		60°C	
				Locked-rotor Power Factor		71.8	
				Rotor inertia		0.13 lb-ft²	

Load Characteristics 460 V, 60 Hz, 1.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	29	45	57	66	73	78	70
Efficiency	65	76.6	80.2	81.4	81	79.7	81.4
Speed	1783	1769	1752	1735	1717	1697	1733
Line amperes	1.9	2.06	2.29	2.6	2.96	3.39	2.8

ABB Motors and Mechanical Inc.

WINDING # 35WGZ926

Typical performance - not guaranteed values.

1.5 HP 3 PH 60 HZ 1735 RPM 460 V 3518M

TORQUES (LB-FT): PO=19.18 PU=15.17 LR=17.41 LRA=18.38





