



Customer information packet

VECP2332T

10HP, 1180RPM, 3PH, 60HZ, 256TC, 0960M, TEFC, F

Class - CLI GP A,B,C,D

Division - Division II

Specifications

Enclosure	TEFC
Frame	256TC
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CL I GP A,B,C,D
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	10.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	CCSA US CSA EEV NEMA PREMIUM NEMA_PREMIUM UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	1.0
Current @ Voltage	30.000 A @ 208.0 V 28.400 A @ 230.0 V 14.200 A @ 460.0 V
Design Code	A
Drip Cover	Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.0 %
Electrically Isolated Bearing	Not Electrically Isolated

Part detail

Revision	AV
Type	AC
Mech. spec.	09H181
Base	
Status	PRD/A
Elec. spec.	09WGX826
Layout	09LYH181
Eff. date	09-16-2025
CD Diagram	CD0180
Poles	06
Leads	9#12
Proprietary	False
Created date	10-15-2006

Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	14.2 a
Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	J
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	1800 rpm
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 12 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0960M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	27.41 IN
Power Factor	72
Product Family	Super-E Chemical Processing
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1180 rpm
Speed Code	Single Speed

Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3995ABEL																			
CAT #		VECP2332T					SER					CC		010A					
SPEC		09H181X826					RATING		40C AMB-CONT										
HZ		VOLTS			AMPS			RPM		HP	CODE		SF	DES	PF	NEMA NOM. EFF			
60		230/460			28.4/14.2			1180		10	J		1.15	A	72	%	91	%	
																%		%	
PH	3	CL	F	MAX RPM		1800		MAX CORR KVAR			5.21		USABLE AT 208V				N/A		
IP55		FR		256TC		ENCL	TEFC		DE BRG		6309		ODE BRG		6309				
GREASE		POLYREX EM									MTR WT		356	LBS					
USABLE AT		50HZ 7.5HP 190/380V 26.4/13.2A									SF1.0								
CL I DIV 2 GRPS A,B,C,D										CL I ZONE 2 GRPS			IIA,IIB,IIC			TEMP T		160	C
1.0 SF ON PWM INVERTER					POWER			INV TEMP CL			180	C							
CHP		60-90		HZ	1.5:1	CT	1.0-60		HZ	60:1		VT	0-60		HZ	1000:1			
SPACE HEATER LEADS H1-H2:							TIE LIKE NUMBERS				TOGETHER								
V			A			W			MAX SPACE HEATER TEMP										

AC Induction Motor Performance Data

Record # 47262

Typical performance - not guaranteed values

Winding: 09WGX826-R026			Type: 0960M		Enclosure: TEFC			
Nameplate Data				460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		10		Full Load Torque		44.4 LB-FT		
Volts		230/460		Start Configuration		direct on line		
Full Load Amps		28.4/14.2		Breakdown Torque		144 LB-FT		
R.P.M.		1180		Pull-up Torque		54.6 LB-FT		
Hz		60	Phase	3	Locked-rotor Torque		75 LB-FT	
NEMA Design Code		A	KVA Code		J	Starting Current		93 A
Service Factor (S.F.)		1.15		No-load Current		7.15 A		
NEMA Nom. Eff.		91	Power Factor		72	Line-line Res. @ 25°C		0.676 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		44°C		
S.F. Amps				Temp. Rise @ S.F. Load		58°C		
				Locked-rotor Power Factor		24.9		
				Rotor inertia		4.82 LB-FT2		

Load Characteristics 460 V, 60 Hz, 10 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	35	55	66	72	74	76	73
Efficiency	84.4	90.2	91.6	91.6	91.2	90.3	91.4
Speed	1196	1191	1186	1181	1175	1168	1177
Line amperes	8	9.39	11.57	14.2	17.24	20.55	16.02


ABB Motors and Mechanical Inc.

WINDING # 09WGX826


Typical performance - not guaranteed values.

10 HP 3 PH 60 HZ 1180 RPM 460 V 0960M




TORQUES (LB-FT): PO=144 PU=54.6 LR=75 LRA=93



12/22/2025 ACPERF, record # 47262



CD0180

LOW VOLTAGE
(2D)HIGH VOLTAGE
(1D)

NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CD0180

REV. DESC: ADD CLASS CONN00000007

REV. LTR: D

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\148

REVISED: 10: 25: 29 02/19/2019

BY: ENBRIRO

MTL: —

**BALDOR - RELIANCE®**

3PH, DV, 9 LEADS, DELTA CONNECTION

SH 1 of 1