



Customer information packet

VEL11301A

.33HP, 1740RPM, 1PH, 60HZ, 56C, 3418LC, ODP, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	ODP
Frame	56C
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Cap Start, Cap Run
Output @ Frequency	.330 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	115.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	1.700 A @ 230.0 V 2.100 A @ 208.0 V 3.400 A @ 115.0 V
Design Code	N
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	72.4 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	Standard
Heater Indicator	No Heater

Part detail

Revision	H
Type	AC
Mech. spec.	34L588
Base	
Status	PRD/A
Elec. spec.	34WGR213
Layout	34LYL588
Eff. date	10-29-2024
CD Diagram	CD0703
Poles	04
Leads	7#18
Proprietary	False
Created date	02-13-2015

High Voltage Full Load Amps	1.7 a
Insulation Class	F
Inverter Code	Not Inverter
KVA Code	K
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Terminal Panel
Motor Lead Quantity/Wire Size	7 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3418LC
Mounting Arrangement	F1
Number of Poles	4
Overall Length	11.00 IN
Power Factor	85
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.35
Shaft Diameter	0.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1740 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	Automatic Thermal Overload

Winding Thermal 1 Location	SB
Winding Thermal 2	None

Nameplate

NP1257L											
CAT.NO.	VEL11301A										
SPEC.	34L588R213G1										
HP	.33										
VOLTS	115/230										
AMP	3.4/1.7										
RPM	1740										
FRAME	56C			HZ	60			PH	1		
SER.F.	1.35	CODE	K	DES	N	CL	F				
NEMA-NOM-EFF	72.4	PF	85								
RATING	40C AMB-CONT										
CC											
DE	6203		ODE	6203							
ENCL	ODP	SN									
	SFA 4.4/2.2										

AC Induction Motor Performance Data

Record # 62087

Typical performance - not guaranteed values

Winding: 34WGR213-R005			Type: 3418LC		Enclosure: OPEN		
Nameplate Data			115 V, 60 Hz: Low Voltage Connection				
Rated Output (HP)		.33	Full Load Torque		0.996 LB-FT		
Volts		115/230	Start Configuration		direct on line		
Full Load Amps		3.4/1.7	Breakdown Torque		3.18 LB-FT		
R.P.M.		1740	Pull-up Torque		2.29 LB-FT		
Hz	60	Phase	1	Locked-rotor Torque		4.26 LB-FT	
NEMA Design Code		N	KVA Code	K	Starting Current		24.1 A
Service Factor (S.F.)		1.35	No-load Current		1.69 A		
NEMA Nom. Eff.		72.4	Power Factor	85	Line-line Res. @ 25°C		1.7428 Ω A Ph 5.5858 Ω B Ph
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		35°C
S.F. Amps		4.4/2.2	Temp. Rise @ S.F. Load		42°C		

Load Characteristics 115 V, 60 Hz, 0.33 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	62	72	81	85	87	89	88
Efficiency	32.1	64.5	69.3	73.5	76.7	73.7	75.5
Speed	1780.3	1770	1754.7	1739.9	1725.3	1703.3	1716
Line amperes	1.96	2.31	2.87	3.43	3.99	4.81	4.32


ABB Motors and Mechanical Inc.


WINDING # 34WGR213

Typical performance - not guaranteed values.

0.33 HP 1 PH 60 HZ 1740 RPM 115 V 3418LC

TORQUES (LB-FT): PO=3.18 PU=2.29 LR=4.26 LRA=24.1





CD0703

