



Customer information packet

VEM2394T

15HP, 3500RPM, 3PH, 60HZ, 254TC, 0750M, TEFC, F

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	254TC
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	15.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	NEMA PREMIUM CURUSEEV
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	16.900 A @ 460.0 V 33.800 A @ 230.0 V 36.000 A @ 208.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater

Part detail

Revision	G
Type	AC
Mech. spec.	07H299
Base	
Status	PRD/A
Elec. spec.	07WGR536
Layout	07LYH299
Eff. date	05-02-2024
CD Diagram	CD0005
Poles	02
Leads	9#14
Proprietary	False
Created date	02-04-2016

High Voltage Full Load Amps	16.9 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 14 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0750M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	20.32 IN
Power Factor	91
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	1.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3500 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None

Winding Thermal 2

None

Nameplate

NP1259L											
CAT.NO.	VEM2394T										
SPEC.	07H299R536G1										
HP	15										
VOLTS	230/460										
AMP	33.8/16.9										
RPM	3500										
FRAME	254TC		HZ	60			PH	3			
SER.F.	1.15	CODE	H	DES	A	CL	F				
NEMA-NOM-EFF	91	PF	91								
RATING	40C AMB-CONT										
CC	010A										
DE	6309		ODE	6307							
ENCL	TEFC	SN									

AC Induction Motor Performance Data

Record # 57257

Typical performance - not guaranteed values

Winding: 07WGR536-R002			Type: 0750M		Enclosure: TEFC			
Nameplate Data			460 V, 60 Hz: High Voltage Connection					
Rated Output (HP)		15	Full Load Torque		22.6 LB-FT			
Volts		230/460	Start Configuration		direct on line			
Full Load Amps		33.8/16.9	Breakdown Torque		87.7 LB-FT			
R.P.M.		3500	Pull-up Torque		29.6 LB-FT			
Hz	60	Phase	3	Locked-rotor Torque		43.2 LB-FT		
NEMA Design Code		A	KVA Code	H	Starting Current		133 A	
Service Factor (S.F.)		1.15	No-load Current		4.61 A			
NEMA Nom. Eff.		91	Power Factor		91	Line-line Res. @ 25°C		0.54448 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		66°C		
S.F. Amps				Temp. Rise @ S.F. Load		84°C		
				Locked-rotor Power Factor		30		

Load Characteristics 460 V, 60 Hz, 15 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	65	83	88	91	92	91	92
Efficiency	90.2	92.6	92.5	91.6	90.2	88.6	90.8
Speed	3572	3546.2	3519.8	3490.6	3457.2	3421.4	3471
Line amperes	6.18	9.3	12.9	16.9	21.4	26	19.6

ABB Motors and Mechanical Inc.

WINDING # 07WGR536

Typical performance - not guaranteed values.

15 HP 3 PH 60 HZ 3500 RPM 460 V 0750M

TORQUES (LB-FT): PO=87.7 PU=29.6 LR=43.2 LRA=133





