



---

# Customer information packet

## VEUHM3554

1.5HP, 1770RPM, 3PH, 60HZ, 56C, 3524M, TEFC, F3

Class - None

Division - Not Applicable

## Specifications

|                                |                                                             |
|--------------------------------|-------------------------------------------------------------|
| Enclosure                      | TEFC                                                        |
| Frame                          | 56C                                                         |
| Frame Material                 | Steel                                                       |
| Frequency                      | 60.00 Hz                                                    |
| Haz Area Class and Group       | None                                                        |
| Haz Area Division              | Not Applicable                                              |
| Motor Letter Type              | Three Phase                                                 |
| Output @ Frequency             | 1.500 HP @ 60 HZ                                            |
| Phase                          | 3                                                           |
| Synchronous Speed @ Frequency  | 1800 RPM @ 60 HZ                                            |
| Voltage @ Frequency            | 460.0 V @ 60 HZ<br>230.0 V @ 60 HZ                          |
| Agency Approvals               | CE<br>CSA EEV<br>NEMA PREMIUM<br>NEMA_PREMIUM<br>UR<br>WEEE |
| Ambient Temperature            | 40 °C                                                       |
| Auxiliary Box                  | NO AUXILLARY BOX                                            |
| Auxiliary Box Lead Termination | None                                                        |
| Base Indicator                 | No Mounting                                                 |
| Bearing Grease Type            | Polyrex EM (-20F +300F)                                     |
| Blower                         | None                                                        |
| Current @ Voltage              | 4.640 A @ 208.0 V<br>4.600 A @ 230.0 V<br>2.300 A @ 460.0 V |
| Design Code                    | B                                                           |
| Drip Cover                     | No Drip Cover                                               |
| Duty Rating                    | CONT                                                        |
| Efficiency @ 100% Load         | 86.5 %                                                      |
| Electrically Isolated Bearing  | Not Electrically Isolated                                   |

## Part detail

|              |            |
|--------------|------------|
| Revision     | E          |
| Type         | AC         |
| Mech. spec.  | 35X042     |
| Base         |            |
| Status       | PRD/A      |
| Elec. spec.  | 35WGL955   |
| Layout       | 35LYX042   |
| Eff. date    | 04-16-2024 |
| CD Diagram   | CD0005     |
| Poles        | 04         |
| Leads        | 9#18       |
| Proprietary  | False      |
| Created date | 01-10-2022 |

|                                      |                     |
|--------------------------------------|---------------------|
| <b>Feedback Device</b>               | NO FEEDBACK         |
| <b>Front Shaft Indicator</b>         | None                |
| <b>Heater Indicator</b>              | No Heater           |
| <b>High Voltage Full Load Amps</b>   | 2.3 a               |
| <b>Insulation Class</b>              | F                   |
| <b>Inverter Code</b>                 | Inverter Ready      |
| <b>KVA Code</b>                      | M                   |
| <b>Lifting Lugs</b>                  | No Lifting Lugs     |
| <b>Locked Bearing Indicator</b>      | Locked Bearing      |
| <b>Motor Lead Quantity/Wire Size</b> | 9 @ 18 AWG          |
| <b>Motor Lead Termination</b>        | Flying Leads        |
| <b>Motor Standards</b>               | NEMA                |
| <b>Motor Type</b>                    | 3524M               |
| <b>Mounting Arrangement</b>          | F3                  |
| <b>Number of Poles</b>               | 4                   |
| <b>Overall Length</b>                | 13.23 IN            |
| <b>Power Factor</b>                  | 72                  |
| <b>Product Family</b>                | General Purpose     |
| <b>Pulley End Bearing Type</b>       | Ball                |
| <b>Pulley Face Code</b>              | C-Face              |
| <b>Pulley Shaft Indicator</b>        | Standard            |
| <b>Rodent Screen</b>                 | None                |
| <b>Service Factor</b>                | 1.15                |
| <b>Shaft Diameter</b>                | 0.625 IN            |
| <b>Shaft Ground Indicator</b>        | No Shaft Grounding  |
| <b>Shaft Rotation</b>                | Reversible          |
| <b>Shaft Slinger Indicator</b>       | No Slinger          |
| <b>Speed</b>                         | 1770 rpm            |
| <b>Speed Code</b>                    | Single Speed        |
| <b>Starting Method</b>               | Direct on line      |
| <b>Thermal Device - Bearing</b>      | None                |
| <b>Thermal Device - Winding</b>      | None                |
| <b>Vibration Sensor Indicator</b>    | No Vibration Sensor |
| <b>Winding Thermal 1</b>             | None                |

|                          |             |
|--------------------------|-------------|
| <b>Winding Thermal 2</b> | <b>None</b> |
|--------------------------|-------------|

---

## Nameplate

| NP2934L        |               |  |      |      |     |    |    |   |  |
|----------------|---------------|--|------|------|-----|----|----|---|--|
| CAT.NO.        | VEUHM3554     |  |      |      |     |    |    |   |  |
| SPEC.          | 35X042L955G1  |  |      |      |     |    |    |   |  |
| HP             | 1.5           |  |      |      |     |    |    |   |  |
| VOLTS          | 230/460       |  |      |      |     |    |    |   |  |
| AMP            | 4.6/2.3       |  |      |      |     |    |    |   |  |
| R.P.M. (1/MIN) | 1770          |  |      |      |     |    |    |   |  |
| FRAME          | 56C           |  | HZ   | 60   |     | PH | 3  |   |  |
| SER.F.         | 1.15          |  | CODE | M    | DES | B  | CL | F |  |
| NEMA-NOM-EFF   | 86.5          |  | PF   | 72   |     |    |    |   |  |
| RATING         | 40C AMB-CONT  |  |      |      |     |    |    |   |  |
| CC             | 010A          |  |      |      |     |    |    |   |  |
| DE             | 6205          |  | ODE  | 6203 |     |    |    |   |  |
| ENCL           | TEFC          |  | SN   |      |     |    |    |   |  |
|                | SFA 4.72/2.36 |  |      |      |     |    |    |   |  |

## AC Induction Motor Performance Data

Record # 95387

Typical performance - not guaranteed values

| Winding: 35WGL955-R001 |    |         | Type: 3524M                              |                     | Enclosure: TEFC         |            |        |
|------------------------|----|---------|------------------------------------------|---------------------|-------------------------|------------|--------|
| Nameplate Data         |    |         | 460 V, 60 Hz:<br>High Voltage Connection |                     |                         |            |        |
| Rated Output (HP)      |    | 1.5     | Full Load Torque                         |                     | 4.48 LB-FT              |            |        |
| Volts                  |    | 230/460 | Start Configuration                      |                     | direct on line          |            |        |
| Full Load Amps         |    | 4.6/2.3 | Breakdown Torque                         |                     | 18.8 LB-FT              |            |        |
| R.P.M.                 |    | 1770    | Pull-up Torque                           |                     | 9.6 LB-FT               |            |        |
| Hz                     | 60 | Phase   | 3                                        | Locked-rotor Torque |                         | 12.6 LB-FT |        |
| NEMA Design Code       |    | B       | KVA Code                                 | M                   | Starting Current        |            | 19.7 A |
| Service Factor (S.F.)  |    | 1.15    | No-load Current                          |                     | 1.51 A                  |            |        |
| NEMA Nom. Eff.         |    | 86.5    | Power Factor                             | 72                  | Line-line Res. @ 25°C   |            | 11.8 Ω |
| Rating - Duty          |    | 40C     | AMB-CONT                                 |                     | Temp. Rise @ Rated Load |            | 48°C   |
| S.F. Amps              |    | 5/2.5   | Temp. Rise @ S.F. Load                   |                     | 57°C                    |            |        |
|                        |    |         | Locked-rotor Power Factor                |                     | 58.4                    |            |        |
|                        |    |         | Rotor inertia                            |                     | 0.173 lb-ft²            |            |        |

## Load Characteristics 460 V, 60 Hz, 1.5 HP

| % of Rated Load | 25   | 50   | 75   | 100  | 125  | 150  | S.F. |
|-----------------|------|------|------|------|------|------|------|
| Power Factor    | 31   | 49   | 63   | 72   | 78   | 81   | 76   |
| Efficiency      | 75.1 | 83.5 | 86   | 86.5 | 85.8 | 84.8 | 86.1 |
| Speed           | 1792 | 1785 | 1777 | 1769 | 1760 | 1750 | 1764 |
| Line amperes    | 1.56 | 1.72 | 1.97 | 2.28 | 2.65 | 3.06 | 2.5  |

ABB Motors and Mechanical Inc.

WINDING # 35WGL955

Typical performance - not guaranteed values.

1.5 HP 3 PH 60 HZ 1770 RPM 460 V 3524M

TORQUES (LB-FT): PO=18.8 PU=9.6 LR=12.6 LRA=19.7





