



Customer information packet

VFSWDL3506

.75HP, 3450RPM, 1PH, 60HZ, 56C, 3516L, TEFC, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	56C
Frame Material	Stainless Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Cap Start, Induction Run
Output @ Frequency	.750 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	115.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	4.600 A @ 230.0 V 4.800 A @ 208.0 V 9.200 A @ 115.0 V
Design Code	N
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	64.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater

Part detail

Revision	F
Type	AC
Mech. spec.	35E4628
Base	
Status	PRD/A
Elec. spec.	35WGL342
Layout	35LYE4628
Eff. date	08-30-2023
CD Diagram	CD0648
Poles	02
Leads	7#18
Proprietary	False
Created date	06-28-2017

High Voltage Full Load Amps	4.6 a
Insulation Class	F
Inverter Code	Not Inverter
KVA Code	K
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Finish	UNPAINTED
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	@ 0 AWG 7 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3516L
Mounting Arrangement	F1
Number of Poles	2
Overall Length	13.96 IN
Power Factor	81
Product Family	WD All SD Non-Encapsulated
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.25
Shaft Diameter	0.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3450 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None

Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4427ALG30													
CAT #	VFSWDL3506				WT	33		LBS					
SPEC	35E4628L342G1				ENCL	TEFC							
SER #					CC			IP	69				
HP	.75				NEMA NOM. EFF								64
VOLTS	115/230												
AMPS	9.2/4.6						PF	81					
RATING	40C AMB-CONT												
RPM	3450												
FRAME	56C	HZ	60	CODE	K	CLASS			F				
SER.F.	1.25	SF AMP	11.2/5.6			PH	1	DES	N				
DE	6205		ODE	6205									
LUBRICATION	POLYREX EM												

AC Induction Motor Performance Data

Record # 51974

Typical performance - not guaranteed values

Winding: 35WGL342-R001			Type: 3516L		Enclosure: TEFC		
Nameplate Data			230 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		.75	Full Load Torque		1.14 LB-FT		
Volts		115/230	Start Configuration		direct on line		
Full Load Amps		9.2/4.6	Breakdown Torque		2.42 LB-FT		
R.P.M.		3450	Pull-up Torque		2.02 LB-FT		
Hz	60	Phase	1	Locked-rotor Torque		4.59 LB-FT	
NEMA Design Code		N	KVA Code	K	Starting Current		29.3 A
Service Factor (S.F.)		1.25	No-load Current		2.68 A		
NEMA Nom. Eff.		64	Power Factor	81	Line-line Res. @ 25°C		3.4258 Ω A Ph 1.1305 Ω B Ph
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		69°C
S.F. Amps		11.2/5.6	Temp. Rise @ S.F. Load		92°C		

Load Characteristics 230 V, 60 Hz, 0.75 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	48	64	74	81	85	87	85
Efficiency	46.1	59.7	64.7	65.5	64.1	59.7	64.1
Speed	3557.8	3528.3	3494.3	3452.4	3397.8	3316.2	3398
Line amperes	2.84	3.24	3.81	4.59	5.61	7.06	5.61


ABB Motors and Mechanical Inc.

WINDING # 35WGL342


Typical performance - not guaranteed values.

0.75 HP 1 PH 60 HZ 3450 RPM 230 V 3516L

TORQUES (LB-FT): PO=2.42 PU=2.02 LR=4.59 LRA=29.3



35LYE4628



FRONT END DETAIL

PULLEY END DETAIL

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION

REV. DESC: REMOVE FACE DRAINS & DRAIN FTG; ADD DRAIN PLUG

REV: A VERSION: 01 REVISED: 09:14:42 01/26/2023 TDR: 000001202627

35LYE4628

MODEL NO. 35LYE4628

BY: ENSTEK0

REF: -

BALDOR

STD VER 56C TEFC 35L WD11/12

35LYE4628

