



Customer information packet

VFSWDNM3611T-4E

3HP, 1750RPM, 3PH, 60HZ, 182TC, 3646M, TENV, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TENV
Frame	182TC
Frame Material	Stainless Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	3.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	CURUSEEV NEMA PREMIUM WEEE
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	4.000 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	89.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	4.0 a
Insulation Class	H
Inverter Code	Inverter Ready

Part detail

Revision	B
Type	AC
Mech. spec.	36R540
Base	
Status	PRD/A
Elec. spec.	36WGZ637
Layout	36LYR540
Eff. date	07-21-2025
CD Diagram	CD0006
Poles	04
Leads	3#16
Proprietary	False
Created date	05-22-2024

KVA Code	K
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	2700 rpm
Motor Lead Quantity/Wire Size	3 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3646M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	17.05 IN
Power Factor	79
Product Family	WD All SD Non-Encapsulated
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	Y
Service Factor	1.15
Shaft Diameter	1.125 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1750 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4427AAA02													
CAT #	VFSWDNM3611T-4E				WGT		LBS						
SPEC	36R540RZ637				ENCL	TENV							
SER #					CC	010A	IP	69					
HP	3	MAG CUR											
VOLTS	460	NEMA NOM. EFF						89.5					
AMPS	4	PF				79							
RATING	40C AMB-CONT												
RPM	1750	MAX RPM					2700						
FRAME	182TC	HZ	60	CODE		K	CLASS	H					
SER.F.	1.15	SF AMP	PH				3	DES	B				
DE	6206	ODE		6206									
LUBRICATION	POLYREX EM												
ID LOGO	INVERTER TYPE			VPWM	CHP	60	TO	90	1.5:1				
ID LOGO	WK2	0.428	CT	15	TO	60	4:1						
ID LOGO	SL HZ		VT	3	TO	60	20:1						

AC Induction Motor Performance Data

Record # 105471

Typical performance - not guaranteed values

Winding: 36WGZ637-R001				Type: 3646M		Enclosure: TENV	
Nameplate Data				460 V, 60 Hz: Single Voltage Motor			
Rated Output (HP)		3		Full Load Torque		9.03 LB-FT	
Volts		460		Start Configuration		direct on line	
Full Load Amps		4		Breakdown Torque		33.1 LB-FT	
R.P.M.		1750		Pull-up Torque		19.1 LB-FT	
Hz		60		Phase		3	
NEMA Design Code		B		KVA Code		K	
Service Factor (S.F.)		1.15		No-load Current		30.9 A	
NEMA Nom. Eff.		89.5		Power Factor		79	
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		101°C	
S.F. Amps				Temp. Rise @ S.F. Load		125°C	
				Locked-rotor Power Factor		38.8	
				Rotor inertia		0.428 lb-ft²	

Load Characteristics 460 V, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	40	61	72	79	82	84	81
Efficiency	85.2	89.7	90.2	89.7	88.5	86.9	89
Speed	1788.3	1777.8	1766	1753.9	1740.2	1724.1	1746
Line amperes	2.17	2.62	3.3	4	4.85	5.82	4.51


ABB Motors and Mechanical Inc.

WINDING # 36WGZ637


Typical performance - not guaranteed values.

3 HP 3 PH 60 HZ 1750 RPM 460 V 3646M

TORQUES (LB-FT): PO=33.1 PU=19.1 LR=22.4 LRA=30.9



CD0006



- NOTES:
- 1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
 - 2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
 - 3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
 - 4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
 - 5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007		
REV. LTR: E	VERSION: 01	TDR: 000001099922
FILE: \AAA\00005\141	REVISED: 10: 24: 49 02/19/2019	BY: ENBRIRO
MTL: —		

BALDOR - RELIANCE®

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1