



Customer information packet

VJPFPM2538T

40//30HP, 3500//2910RPM, 3PH, 60//50HZ, 286J

Class -

Division - Not Applicable

Specifications

Enclosure	OPSB
Frame	286JP
Frame Material	Steel
Frequency	50.00 Hz 60.00 Hz
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	30.000 HP @ 50 HZ 40.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3000 RPM @ 50 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 380.0 V @ 50 HZ 230.0 V @ 60 HZ 190.0 V @ 50 HZ
Agency Approvals	CSA EEV UL
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	90.000 A @ 230.0 V 84.000 A @ 190.0 V 45.000 A @ 460.0 V 42.000 A @ 380.0 V
Design Code	B
Drip Cover	Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.7 %
Electrically Isolated Bearing	Not Electrically Isolated

Part detail

Revision	T
Type	AC
Mech. spec.	39T043
Base	
Status	PRD/A
Elec. spec.	39WGX928
Layout	39LYT043
Eff. date	06-26-2024
CD Diagram	CD0104
Poles	02
Leads	12#10
Proprietary	False
Created date	01-13-2016

Feedback Device	NO FEEDBACK
Front Face Code	Drip Cover Mounting
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	42.0 a
Insulation Class	F
Inverter Code	Not Inverter
KVA Code	G
Lifting Lugs	Vertical Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	12 @ 10 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3954M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	31.44 IN
Power Factor	91
Product Family	Fire Pump Motor
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Tapped & Key
Rodent Screen	Included
Service Factor	1.15
Shaft Diameter	1.750 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	2910 rpm 3500 rpm
Speed Code	Single Speed
Starting Method	Wye Start - Delta Run

Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor

Nameplate

NP3454L															
CAT.NO.	VJPFPM2538T				CUST P/N							I.P.	23		
SPEC.	39T043X928H2				SER.NO.							FRAME	286JP		
HZ	60	HP	40		RPM	3500		HZ	50		HP	30		RPM	2910
VOLTS	230/460				CODE	G		VOLTS	190/380				CODE	G	
AMPS	90/45				DES	B		AMPS	84/42				DES	B	
EFF	91.7	SER.F.	1.15		PF	91		EFF	91		SER.F.	1.15		PF	91
RATING	40C AMB-CONT				DE BRG				6312			GREASE	POLYREX EM		
BLANK					ODE BRG				6208			MTR. WT.	332		
					CLASS		F		PH		3				
					ENCL		OPSB		CC		010A				
HTR-VOLTS	HTR-AMPS				HTR-WATTS										

AC Induction Motor Performance Data

Record # 54883

Typical performance - not guaranteed values

Winding: 39WGX928-R001		Type: 3954M	Enclosure: OPSB				
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)	40//30		Full Load Torque	60.6 LB-FT			
Volts	230/460//190/380		Start Configuration	direct on line			
Full Load Amps	90/45//84/42		Breakdown Torque	191 LB-FT			
R.P.M.	3500//2910		Pull-up Torque	71.3 LB-FT			
Hz	60//50	Phase	3	Locked-rotor Torque	90.5 LB-FT		
NEMA Design Code	B		KVA Code	G	Starting Current	285 A	
Service Factor (S.F.)	1.15		No-load Current			10.5 A	
NEMA Nom. Eff.	91.7		Power Factor	91	Line-line Res. @ 25°C	0.23 Ω	
Rating - Duty	40C		AMB-CONT			Temp. Rise @ Rated Load	63°C
S.F. Amps						Temp. Rise @ S.F. Load	79°C
						Locked-rotor Power Factor	27.2
						Rotor inertia	1.38 LB-FT2

Load Characteristics 460 V, 60 Hz, 40 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	68	85	90	91	91	90	91
Efficiency	93.2	94	93.4	91.9	90.3	88.5	91
Speed	3580	3557	3532	3503	3471	3436	3484
Line amperes	15.3	23.9	34	45.3	57.7	70.7	52.7


ABB Motors and Mechanical Inc.

WINDING # 39WGX928

Typical performance - not guaranteed values.

40 HP 3 PH 60 HZ 3503 RPM 460 V 3954M

TORQUES (LB-FT): PO=191 PU=71.3 LR=90.5 LRA=285



AC Induction Motor Performance Data

Record # 54884

Typical performance - not guaranteed values

Winding: 39WGX928-R001			Type: 3954M		Enclosure: OPSB			
Nameplate Data				380 V, 50 Hz: High Voltage Connection				
Rated Output (HP)		40//30		Full Load Torque		54.6 LB-FT		
Volts		230/460//190/380		Start Configuration		direct on line		
Full Load Amps		90/45//84/42		Breakdown Torque		184 LB-FT		
R.P.M.		3500//2910		Pull-up Torque		75.2 LB-FT		
Hz		60//50	Phase	3	Locked-rotor Torque		95.4 LB-FT	
NEMA Design Code		B		KVA Code	G	Starting Current		278 A
Service Factor (S.F.)		1.15		No-load Current		10.2 A		
NEMA Nom. Eff.		91.7	Power Factor		91	Line-line Res. @ 25°C		0.23 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		55°C		
S.F. Amps				Temp. Rise @ S.F. Load		70°C		
				Locked-rotor Power Factor		30.6		
				Rotor inertia		1.38 LB-FT2		

Load Characteristics 380 V, 50 Hz, 30 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	66	84	89	91	91	91	91
Efficiency	93.5	94	93.1	91.6	89.9	87.9	90.6
Speed	2982	2961	2939	2913	2885	2855	2896
Line amperes	14.4	22	31.1	41.3	52.5	64.1	48

ABB Motors and Mechanical Inc.

WINDING # 39WGX928

Typical performance - not guaranteed values.

30 HP 3 PH 50 HZ 2913 RPM 380 V 3954M

TORQUES (LB-FT): PO=184 PU=75.2 LR=95.4 LRA=278

