



Customer information packet

VLECP3663T

5HP, 3490RPM, 3PH, 60HZ, 184LP, 0632M, TEFC, F1

Class - CLI GP A,B,C,D

Division - Division II

Specifications

Enclosure	TEFC
Frame	184LP
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CL I GP A,B,C,D
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	5.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	CCSA US CSA EEV UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	6
Current @ Voltage	11.400 A @ 230.0 V 5.700 A @ 460.0 V
Design Code	A
Drip Cover	Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	90.2 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None

Part detail

Revision	E
Type	AC
Mech. spec.	06F063
Base	
Status	PRD/A
Elec. spec.	06WGW730
Layout	06LYF063
Eff. date	03-10-2021
CD Diagram	CD0005
Poles	02
Leads	9#16
Proprietary	False
Created date	07-09-2015

Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	5.7 a
Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	M
Lifting Lugs	Vertical Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	5400 rpm
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0632M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	22.18 IN
Power Factor	90
Product Family	Super-E Chemical Processing
Pulley End Bearing Type	Thrust
Pulley Face Code	P-Base
Pulley Shaft Indicator	P-Base Groove & Key
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3490 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None

Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3258									
CAT.NO.	VLECP3663T								
SPEC.	06F063W730G1								
HP	5 TE								
VOLTS	230/460								
AMP	11.4/5.7								
RPM	3490								
FRAME	184LP	HZ	60		PH	3			
SER.F.	1.15	CODE	M	DES	A	CL	F		
RATING	40C AMB-CONT								
SN									
DE	QJ307	ODE	6206						
NEMA-NOM-EFF	90.2	PF	90						
G.MIN.EFF	88.5	CC	010A						
T. CODE	T3C	T=	160						

NP3261				
SPEC.	06F063W730G1			
D.E. BRG.	35BZ03X00X			
O.D.E. BRG.	30BC02X30X			
GREASE	POLYREX EM			
RPM MAX	5400	MAX. KVAR		
BLANK				
INV.TYPE	PWM			
T=	160			
C HP FR	60	C HP TO	90	
CT HZ FROM	6	CT HZ TO	60	
VT HZ FROM	3	VT HZ TO	60	
HTR-VOLTS	N/A	HTR-AMPS	N/A	
HTR-WATTS	N/A	MAX. SPACE HEATER TEMP.	N/A	

AC Induction Motor Performance Data

Record # 47071

Typical performance - not guaranteed values

Winding: 06WGW730-R030			Type: 0632M		Enclosure: TEFC			
Nameplate Data				460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		5		Full Load Torque		7.54 LB-FT		
Volts		230/460		Start Configuration		direct on line		
Full Load Amps		11.4/5.7		Breakdown Torque		40.1 LB-FT		
R.P.M.		3490		Pull-up Torque		30.6 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		36.9 LB-FT		
NEMA Design Code		A	KVA Code	M	Starting Current		64.8 A	
Service Factor (S.F.)		1.15		No-load Current		2.08 A		
NEMA Nom. Eff.		90.2	Power Factor	90	Line-line Res. @ 25°C		1.93 Ω	
Rating - Duty		40C		AMB-CONT		Temp. Rise @ Rated Load		51°C
S.F. Amps						Temp. Rise @ S.F. Load		62°C

Load Characteristics 460 V, 60 Hz, 5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	55	76	85	90	93	93	92
Efficiency	84.5	89.4	90.8	90.6	90	89	90.2
Speed	3570	3544	3517	3489	3458	3426	3470
Line amperes	2.54	3.47	4.6	5.76	7.03	8.46	6.52

ABB Motors and Mechanical Inc.

WINDING # 06WGW730

Typical performance - not guaranteed values.

5 HP 3 PH 60 HZ 3490 RPM 460 V 0632M

TORQUES (LB-FT): PO=40.1 PU=30.6 LR=36.9 LRA=64.8





