



Customer information packet

VLECP4107T

25HP, 3520RPM, 3PH, 60HZ, 284LP, 1048M, TEFC, F

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	284LP
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	25.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	CSA CSA EEV UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	6
Current @ Voltage	28.000 A @ 460.0 V 56.000 A @ 230.0 V
Design Code	B
Drip Cover	Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.7 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None

Part detail

Revision	R
Type	AC
Mech. spec.	10M69
Base	
Status	PRD/A
Elec. spec.	10WGZ273
Layout	10LYM069
Eff. date	11-03-2025
CD Diagram	CD0180
Poles	02
Leads	9#10
Proprietary	False
Created date	07-13-2015

Haz Area Temp Code	T3
Heater Indicator	No Heater
High Voltage Full Load Amps	28.0 a
Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	F
Lifting Lugs	Vertical Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	5400 rpm
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 10 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	1048M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	32.44 IN
Power Factor	90
Product Family	Super-E Chemical Processing
Pulley End Bearing Type	Thrust
Pulley Face Code	P-Base
Pulley Shaft Indicator	P-Base Groove & Key
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.750 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	3520 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	NONE (OLD)
Thermal Device - Winding	None

Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3241

CAT.NO.	VLECP4107T			P/N					ENCLOSURE	TEFC			
SPEC.	10M069Z273G1		CC	010A	FRAME	284LP		S/N					
HP	25			CLASS	F	HZ	60	DES	B				
RPM	3520			RPM MAX	5400		PH	3	KVA-CODE	F			
VOLT	230/460			MOTOR WEIGHT			400						
AMP	56/28			SER.F.	1.15		PF	90	ODE BRG	6309	DE BRG	QJ213	
RATING	40C AMB-CONT			NEMA-NOM-EFF			91.7		GREASE	POLYREX EM			
							INV.TYPE		PWM				
TEMP CODE	T3	INVERTER-TEMP-CODE			200								
TEMP =	200	C HP FR	60		C HP TO	90							
CT HZ FROM	6		CT HZ TO	60									
HTR-VOLTS			HTR-AMPS			HTR-WATTS			MAX. SPACE HEATER TEMP.				
									VT HZ FROM		3	VT HZ TO	60

AC Induction Motor Performance Data

Record # 47234

Typical performance - not guaranteed values

Winding: 10WGZ273-R002			Type: 1048M		Enclosure: TEFC			
Nameplate Data				460 V, 60 Hz: Single Voltage Motor				
Rated Output (HP)		25		Full Load Torque		37.3 LB-FT		
Volts		230/460		Start Configuration		direct on line		
Full Load Amps		56/28		Breakdown Torque		103 LB-FT		
R.P.M.		3520		Pull-up Torque		42.1 LB-FT		
Hz		60	Phase	3	Locked-rotor Torque		54 LB-FT	
NEMA Design Code		B		KVA Code	F	Starting Current		171 A
Service Factor (S.F.)		1.15		No-load Current		6.99 A		
NEMA Nom. Eff.		91.7	Power Factor		90	Line-line Res. @ 25°C		0.295 Ω
Rating - Duty		40C		AMB-CONT		Temp. Rise @ Rated Load		57°C
S.F. Amps						Temp. Rise @ S.F. Load		72°C
						Locked-rotor Power Factor		23.3
						Rotor inertia		2.06 LB-FT ²

Load Characteristics 460 V, 60 Hz, 25 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	69	83	88	90	90	90	90
Efficiency	87.7	91.6	92.1	91.7	90.8	89.7	91.3
Speed	3580	3563	3543	3521	3497	3470	3507
Line amperes	10.1	15.4	21.7	28.3	35.7	43.5	32.7


ABB Motors and Mechanical Inc.


WINDING # 10WGZ273

Typical performance - not guaranteed values.

25 HP 3 PH 60 HZ 3520 RPM 460 V 1048M

TORQUES (LB-FT): PO=103 PU=42.1 LR=54 LRA=171





CD0180

LOW VOLTAGE
(2D)HIGH VOLTAGE
(1D)

NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: ADD CLASS CONN00000007

REV. LTR: D

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\148

REVISED: 10: 25: 29 02/19/2019

BY: ENBRIRO

MTL: —



BALDOR - RELIANCE®

3PH, DV, 9 LEADS, DELTA CONNECTION

SH 1 of 1

CD0180