



---

# Customer information packet

## VLECP82394T-4

15HP, 3520RPM, 3PH, 60HZ, 254LP, TEFC, V1

Class - CLI GP A,B,C,D

Division - Division II

## Specifications

|                                |                                          |
|--------------------------------|------------------------------------------|
| Enclosure                      | TEFC                                     |
| Frame                          | 254LP                                    |
| Frame Material                 | Iron                                     |
| Frequency                      | 60.00 Hz                                 |
| Haz Area Class and Group       | CL I GP A,B,C,D                          |
| Haz Area Division              | Division II                              |
| Motor Letter Type              | Three Phase                              |
| Output @ Frequency             | 15.000 HP @ 60 HZ                        |
| Phase                          | 3                                        |
| Synchronous Speed @ Frequency  | 3600 RPM @ 60 HZ                         |
| Voltage @ Frequency            | 460.0 V @ 60 HZ                          |
| Agency Approvals               | CCSA US<br>CSA EEV<br>NEMA PREMIUM<br>UR |
| Ambient Temperature            | 40 °C                                    |
| Auxiliary Box                  | NO AUXILLARY BOX                         |
| Auxiliary Box Lead Termination | None                                     |
| Base Indicator                 | No Mounting                              |
| Bearing Grease Type            | Polyrex EM (-20F +300F)                  |
| Blower                         | None                                     |
| Constant Torque Speed Range    | 6                                        |
| Current @ Voltage              | 17.000 A @ 460.0 V                       |
| Design Code                    | B                                        |
| Drip Cover                     | Drip Cover                               |
| Duty Rating                    | CONT                                     |
| Efficiency @ 100% Load         | 91.0 %                                   |
| Electrically Isolated Bearing  | Not Electrically Isolated                |
| Enclosure Modification         | 841                                      |
| Feedback Device                | NO FEEDBACK                              |
| Haz Area Temp Code             | T3C                                      |
| Heater Indicator               | No Heater                                |

## Part detail

|              |              |
|--------------|--------------|
| Revision     | P            |
| Type         | AC           |
| Mech. spec.  |              |
| Base         |              |
| Status       | PRD/A        |
| Elec. spec.  | 09WGY948     |
| Layout       | 09LY-000-166 |
| Eff. date    | 02-01-2024   |
| CD Diagram   | CD0006       |
| Poles        | 02           |
| Leads        | 3#12         |
| Proprietary  | False        |
| Created date | 03-27-2019   |

|                             |                                |
|-----------------------------|--------------------------------|
| High Voltage Full Load Amps | 17.0 a                         |
| Insulation Class            | F                              |
| Inverter Code               | Inverter Duty                  |
| IP Rating                   | IP56                           |
| KVA Code                    | G                              |
| Lifting Lugs                | Vertical Lifting Lugs          |
| Locked Bearing Indicator    | Locked Bearing                 |
| Max Speed                   | 5400 rpm                       |
| Motor Lead Termination      | Ring Terminals                 |
| Motor Standards             | NEMA                           |
| Motor Type                  | 0934M                          |
| Mounting Arrangement        | V1                             |
| Number of Poles             | 2                              |
| Overall Length              | 29.53 IN                       |
| Power Factor                | 89                             |
| Product Family              | Chem Process S/P 32-8 IEEE 841 |
| Pulley Face Code            | P-Base                         |
| Rodent Screen               | None                           |
| Service Factor              | 1.15                           |
| Shaft Diameter              | 1.625 IN                       |
| Shaft Ground Indicator      | No Shaft Grounding             |
| Shaft Rotation              | Reversible                     |
| Speed                       | 3520 rpm                       |
| Speed Code                  | Single Speed                   |
| Starting Method             | Direct on line                 |
| Thermal Device - Winding    | None                           |
| Vibration Sensor Indicator  | No Vibration Sensor            |
| Winding Thermal 1           | None                           |
| Winding Thermal 2           | None                           |

## Nameplate

## NP4332

|              |               |                    |      |              |           |        |                         |             |            |            |            |      |          |    |
|--------------|---------------|--------------------|------|--------------|-----------|--------|-------------------------|-------------|------------|------------|------------|------|----------|----|
| STK.NO.      | VLECP82394T-4 |                    |      | P/N          |           |        |                         |             | ENCLOSURE  |            | TEFC       |      |          |    |
| SPEC.        | 09-0000-1150  |                    |      | CC           | 010A      | FRAME  |                         | 254LP       | S/N        |            |            |      |          |    |
| HP           | 15            |                    |      | CLASS        | F         | HZ     | 60                      | ODE BRG     |            | 7308       | DE BRG     | 6213 |          |    |
| RPM          | 3520          | RPM MAX            | 5400 | PH           | 3         | DES    | B                       | D.E. BRG.   |            | 65BC02X30X |            |      |          |    |
| VOLT         | 460           |                    |      | KVA-CODE     |           | G      |                         | O.D.E. BRG. |            | 40BT03X30X |            |      |          |    |
| AMP          | 17            |                    |      | MOTOR WEIGHT |           |        | 240                     | GREASE      | POLYREX EM |            |            |      |          |    |
| RATING       | 40C AMB-CONT  |                    |      |              | MAX. KVAR |        | 2.2                     | BLANK       |            |            |            |      |          |    |
| NEMA-NOM-EFF | 91            | # OF ROTOR BARS    |      |              | 28        | SER.F. | 1.15                    | IP          | 56         |            |            |      |          |    |
| G.MIN.EFF    | 89.5          | # OF STATOR SLOTS  |      |              | 36        | PF     | 89                      | INV.TYPE    | PWM        |            |            |      |          |    |
| TEMP CODE    | T3C           | INVERTER-TEMP-CODE |      |              | 180       |        |                         |             |            |            |            |      |          |    |
| TEMP =       | 160           | C HP FR            | 60   | C HP TO      | 90        |        |                         |             |            |            |            |      |          |    |
| CT HZ FROM   | 1.3           | CT HZ TO           | 60   |              |           |        |                         |             |            |            |            |      |          |    |
| HTR-VOLTS    |               | HTR-AMPS           |      | HTR-WATTS    |           |        | MAX. SPACE HEATER TEMP. |             |            |            | VT HZ FROM | 0-   | VT HZ TO | 60 |

## AC Induction Motor Performance Data

Record # 49591

Typical performance - not guaranteed values

| Winding: 09WGY948-R035 |    |              | Type: 0934M                           |                           | Enclosure: TEFC  |                       |       |         |
|------------------------|----|--------------|---------------------------------------|---------------------------|------------------|-----------------------|-------|---------|
| Nameplate Data         |    |              | 460 V, 60 Hz:<br>Single Voltage Motor |                           |                  |                       |       |         |
| Rated Output (HP)      |    | 15           | Full Load Torque                      |                           | 22.4 LB-FT       |                       |       |         |
| Volts                  |    | 460          | Start Configuration                   |                           | direct on line   |                       |       |         |
| Full Load Amps         |    | 17           | Breakdown Torque                      |                           | 87.8 LB-FT       |                       |       |         |
| R.P.M.                 |    | 3520         | Pull-up Torque                        |                           | 26 LB-FT         |                       |       |         |
| Hz                     | 60 | Phase        | 3                                     | Locked-rotor Torque       |                  | 32.7 LB-FT            |       |         |
| NEMA Design Code       |    | B            | KVA Code                              | G                         | Starting Current |                       | 114 A |         |
| Service Factor (S.F.)  |    | 1.15         | No-load Current                       |                           | 5.1 A            |                       |       |         |
| NEMA Nom. Eff.         |    | 91           | Power Factor                          |                           | 89               | Line-line Res. @ 25°C |       | 0.622 Ω |
| Rating - Duty          |    | 40C AMB-CONT |                                       | Temp. Rise @ Rated Load   |                  | 54°C                  |       |         |
| S.F. Amps              |    |              |                                       | Temp. Rise @ S.F. Load    |                  | 67°C                  |       |         |
|                        |    |              |                                       | Locked-rotor Power Factor |                  | 28.4                  |       |         |
|                        |    |              |                                       | Rotor inertia             |                  | 0.868 lb-ft²          |       |         |

## Load Characteristics 460 V, 60 Hz, 15 HP

| % of Rated Load | 25   | 50   | 75   | 100  | 125  | 150  | S.F. |
|-----------------|------|------|------|------|------|------|------|
| Power Factor    | 61   | 80   | 88   | 89   | 90   | 90   | 90   |
| Efficiency      | 87.4 | 91.1 | 91.7 | 91.3 | 90.1 | 88.7 | 90.5 |
| Speed           | 3581 | 3563 | 3544 | 3522 | 3499 | 3472 | 3508 |
| Line amperes    | 6.66 | 9.71 | 13.1 | 17.3 | 21.7 | 26.5 | 19.9 |


ABB Motors and Mechanical Inc.


WINDING # 09WGY948

Typical performance - not guaranteed values.

15 HP 3 PH 60 HZ 3520 RPM 460 V 0934M



TORQUES (LB-FT): PO=87.8 PU=26 LR=32.7 LRA=114






CD0006

TYPICAL WYE-CONNECTED MOTOR



TYPICAL DELTA-CONNECTED MOTOR



## NOTES:

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007

REV. LTR: E

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\141

REVISED: 10:24:49 02/19/2019

BY: ENBRIRO

MTL: —

**BALDOR - RELIANCE®**

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1