



Customer information packet

VLECP84104T-4

60M 4P TEFC VER 286LP IEEE841 32-8 DRIP

Class - CLI GP A,B,C,D

Division - Division II

Specifications

Enclosure	TEFC
Frame	286LP
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CL I GP A,B,C,D
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	30.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	CCSA US CSA EEV UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	1
Current @ Voltage	36.000 A @ 460.0 V
Design Code	B
Drip Cover	Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	93.6 %
Electrically Isolated Bearing	Not Electrically Isolated
Enclosure Modification	841
Feedback Device	NO FEEDBACK
Front Shaft Indicator	Standard
Haz Area Temp Code	T3C
Heater Indicator	No Heater

Part detail

Revision	J
Type	AC
Mech. spec.	10K389
Base	
Status	PRD/A
Elec. spec.	10WGZ438
Layout	10LYK389
Eff. date	10-08-2025
CD Diagram	CD0006
Poles	04
Leads	3#10
Proprietary	False
Created date	03-25-2019

High Voltage Full Load Amps	36.0 a
Insulation Class	F
Inverter Code	Inverter Duty
IP Rating	IP56
KVA Code	G
Lifting Lugs	Vertical Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	2700 rpm
Motor Lead Quantity/Wire Size	3 @ 10 AWG
Motor Lead Termination	Ring Terminals
Motor Standards	NEMA
Motor Type	1060M
Mounting Arrangement	V1
Number of Poles	4
Overall Length	36.31 IN
Power Factor	84
Product Family	Chem Process S/P 32-8 IEEE 841
Pulley End Bearing Type	Ball
Pulley Face Code	P-Base
Pulley Shaft Indicator	P-Base Groove & Key
Rodent Screen	None
RoHS Status	ROHS NON-COMPLIANT
Service Factor	1.15
Shaft Diameter	2.125 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1770 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None

Winding Thermal 2

None

Nameplate

NP4332

STK.NO.	VLECP84104T-4			P/N					ENCLOSURE	TEFC	
SPEC.	10K389Z438G1			CC	010A	FRAME	286LP		S/N		
HP	30			CLASS	F	HZ	60	ODE BRG	7309	DE BRG	6213
RPM	1770	RPM MAX	2700	PH	3	DES	B	D.E. BRG.	65BC02X30X		
VOLT	460			KVA-CODE	G		O.D.E. BRG.		45BT03X30X		
AMP	35.6			MOTOR WEIGHT			619	GREASE	POLYREX EM		
RATING	40C AMB-CONT			MAX. KVAR			7.7	BLANK			
NEMA-NOM-EFF	93.6	# OF ROTOR BARS			40	SER.F.	1.15	IP	56		
G.MIN.EFF	92.4	# OF STATOR SLOTS			48	PF	84	INV.TYPE	PWM		
TEMP CODE	T3	INVERTER-TEMP-CODE			200						
TEMP =	200	C HP FR	60	C HP TO	90						
CT HZ FROM	30	CT HZ TO	60								
HTR-VOLTS		HTR-AMPS		HTR-WATTS				MAX. SPACE HEATER TEMP.			
										VT HZ FROM	30
										VT HZ TO	60

AC Induction Motor Performance Data

Record # 93188

Typical performance - not guaranteed values

Winding: 10WGZ438-R001			Type: 1060M		Enclosure: TEFC			
Nameplate Data			460 V, 60 Hz: Single Voltage Motor					
Rated Output (HP)		30	Full Load Torque		88.64 LB-FT			
Volts		460	Start Configuration		direct on line			
Full Load Amps		36	Breakdown Torque		267 LB-FT			
R.P.M.		1770	Pull-up Torque		116 LB-FT			
Hz	60	Phase	3	Locked-rotor Torque		142 LB-FT		
NEMA Design Code		B	KVA Code	G	Starting Current		217.5 A	
Service Factor (S.F.)		1.15	No-load Current		13.5 A			
NEMA Nom. Eff.		93.6	Power Factor		84	Line-line Res. @ 25°C		0.234 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		62°C	
S.F. Amps					Temp. Rise @ S.F. Load		76°C	
					Locked-rotor Power Factor		29.7	
					Rotor inertia		4.77 lb-ft²	

Load Characteristics 460 V, 60 Hz, 30 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	48	71	80	84	85	85	83
Efficiency	91	94	94.3	93.6	93.7	92	93.4
Speed	1793	1787	1779	1772	1764	1753	1769
Line amperes	15.8	21.1	27.8	35.6	44	53.5	41.5


ABB Motors and Mechanical Inc.


WINDING # 10WGZ438

Typical performance - not guaranteed values.

30 HP 3 PH 60 HZ 1770 RPM 460 V 1060M

TORQUES (LB-FT): PO=267 PU=116 LR=142 LRA=217.5





CD0006

TYPICAL WYE-CONNECTED MOTOR

1-BLU

J-BRN

OPTIONAL THERMOSTATS

J-BRN

3-ORG

2-WHT

TYPICAL DELTA-CONNECTED MOTOR

1-BLU

J-BRN

2-WHT

OPTIONAL THERMOSTATS

J-BRN

3-ORG

1

2

3

LINE

NOTES:

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.

2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.

3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.

4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.

5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007			BALDOR - RELIANCE® 3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED SH 1 of 1
REV. LTR: E	VERSION: 01	TDR: 000001099922	
FILE: \AAA\00005\141	REVISED: 10: 24: 49 02/19/2019	BY: ENBRIRO	
MTL: —			

10WGZ253: Electrical Design

Page 9 of 9