



Customer information packet

VP3605D

3.7KW, 1750RPM, DC, D112D, 3681P, TEFC, F1

Class - None

Division -

Specifications

Armature Voltage	180 V
Base Speed	1750 rpm
Enclosure	TEFC
Frame	D112D
Frame Material	Steel
Haz Area Class and Group	None
Output Power	5.000 HP
Agency Approvals	CE CSA UR
Ambient Temperature	40 °C
Armature Current	24.5 a
Armature Inertia	177.060 lb-ft ²
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Drip Cover	No Drip Cover
Duty Rating	CONT
Feedback Device	NO FEEDBACK
Frame Prefix	D
Heater Indicator	No Heater
Lifting Lugs	Standard Lifting Lugs
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	2 @ 12 AWG
Motor Lead Termination	Flying Leads
Motor Standards	IEC
Mounting Arrangement	B35
Overall Length	28.56 IN
Product Family	General Purpose
Pulley End Bearing Type	Sealed Bearing
Service Factor	1.00
Shaft Diameter	1.103 IN
Shaft Extension Location	Pulley End

Part detail

Revision	AA
Type	DC
Mech. spec.	36P184
Base	
Status	PRD/A
Elec. spec.	36WGZ509
Layout	36LYP184
Eff. date	11-12-2024
CD Diagram	CD0194
Poles	00
Leads	
Proprietary	False
Created date	01-01-0001

Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger

Nameplate

NP0891L					
CAT.NO.	VP3605D				
SPEC.	36P184Z509				
HP	3.7KW	ENCL		TEFC	
RPM	1750 1/MIN				
FRAME	D112D	TYPE		3681P	
ARM V	180	ARM A		24.5	
FLD V		FLD A			
INSUL	F	AMB.		40	
DUTY	CONT	SUPPLY		K	
BRG/DE	6206	BRG/ODE		6206	
BRUSHES	2/BP5027A01				
		BLANK		IP44	
SER.					
BLANK	IC411 30KG				
APRV-CE	Y	APRV-CSA	Y	APRV-UL	Y

Accessories

Part number	Description	Multiplier
TK3600PM	TACHO MOUNTING KIT FOR TK3600PM	A8

DC Motor Performance Data

Record # 312

Typical performance - not guaranteed values

Winding: 36WGZ509-R001		Type: 3681P	Enclosure: TEFC
Nameplate Data		General Characteristics	
Rated Output (HP)	5	Armature Resistance @ 25°C	0.16 Ω
R.P.M.	1750		
Armature Volts	180	Voltage Constant	91.78 v/krpm
Armature Amps	24.5		
Field Volts		Armature Inductance	3.677 mH
Field Amps		Armature Inertia	177.0597 LI ²
Rating - Duty	40C AMB-CONT		
Power Supply Code	K		

Load Characteristics at 180 Armature Volts

Load Point	1	2	3	4	5	6	7
Armature Amps	1.1	7.1	12.8	18.4	24.1	29.9	35.99
R.P.M.	1931	1915	1886	1870	1850	1832	1815
Torque (LB-FT)	0	3.8	7.57	11.39	15.18	19	22.81


ABB Motors and Mechanical Inc.


WINDING # 36WGZ509

5 HP DC 1750 RPM 180 V 3681P


Typical performance - not guaranteed values.

ENCL: TEFC DUTY: CONT CL: F





CD0194



NOTES:

1. CCW ROTATION AS SHOWN FACING COMMUTATOR END. TO REVERSE MOTOR ROTATION OR TACHOMETER OUTPUT POLARITY INTERCHANGE LEADS A1(RED) & A2(BLACK)
2. LEAD COLORS FOR REFERENCE ONLY & NOT SPECIFIED BY THIS DRAWING. LEAD COLORS SPECIFIED BY LAYOUT DRAWING & BILL OF MATERIAL ONLY.

MATL: -					BALDOR ELECTRIC Co.	
REV:	E	ADDED NOTE "LEAD COLORS FOR REFERENCE ONLY &....				
CD0194		SCALE: -	BY: CK	REVISED: 07/28/95	CD TYPE P DC PERMANENT MAGNET MOTORS AND TACHOMETERS	
		FILE: AAA00004503		TDR: 0078737		

CD0194