



Customer information packet

VPECP84310T-4

60HP, 3560RPM, 3PH, 60HZ, 364VP, TEFC, V1

Class - None

Division - Division II

Specifications

Enclosure	TEFC
Frame	364LP
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	60.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	CCSA US NEMA PREMIUM UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Constant Torque Speed Range	6-60
Current @ Voltage	66.000 A @ 460.0 V
Design Code	B
Drip Cover	Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	93.6 %
Enclosure Modification	841
Feedback Device	NO FEEDBACK
Haz Area Temp Code	T3
Heater Indicator	No Heater
High Voltage Full Load Amps	66.0 a
Insulation Class	F
Inverter Code	Inverter Ready
IP Rating	IP56

Part detail

Revision	D
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	A36WG1559
Layout	617428-660
Eff. date	03-15-2024
CD Diagram	416820-036
Poles	02
Leads	3#4
Proprietary	False
Created date	02-28-2019

KVA Code	G
Lifting Lugs	Vertical Lifting Lugs
Motor Lead Quantity/Wire Size	3 @ 4 AWG
Motor Standards	NEMA
Motor Type	A36056M
Mounting Arrangement	V1
No Load Current	14.9 a
Number of Poles	2
Overall Length	37.27 IN
Power Factor	91
Product Family	Pump - Centrifugal
Pulley End Bearing Type	Ball
Service Factor	1.15
Shaft Diameter	2.124 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3560 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Winding	None


Nameplate


000613007EX				
CAT NO	VPECP84310T-4	SPEC NO.	A36-7839-1559	
NO. ROTOR BARS	38	GREASE TYPE	POLYREX EM	
NO. SLOTS	48	NL AMPS AT RATED VOLTAGE		14.9
5 YEAR WARRANTY		WINDING RES @25 C	.1019	OHMS
MFG. DATE		SER.NO		
	SFA 76.1			


NP4566

CAT NO	VPECP84310T-4		SPEC NO.	A36-7839-1559			
HP	60	AMPS	66	VOLTS	460	DESIGN	B
FRAME SIZE	364VP	RPM	3560	HZ	60	AMB	40
D.E. BRG.DATA	6313	O.D.E. BRG.DATA	7310	PH	3	DUTY	CONT
D.E. BRG.	65BC03JP30X	TYPE	ENCL	TEFC	CODE	G	INSUL.CLASS
O.D.E. BRG.	BA2B_459310	POWER FACTOR	91	NEMA-NOM-EFFICIENCY	93.6		
3/4 LOAD EFF.	93.8	IP	56	MAX CORR KVAR	6.5	GUARANTEED EFFICIENCY	92.4
TEMP CODE	T3	TEMP =	200				
CHP HZ	60-75	CT HZ	6-60	VT HZ	0-60		
INVERTER-TEMP-CODE	T3						
SER.NO.		MOTOR WEIGHT					

REL. S.O.	FRAME	HP	TYPE	PHASE/HERTZ	RPM	VOLTS
	364TSC	60	P	3/60	3560	460
AMPS	DUTY	AMB °C/INSUL.	S.F.	NEMA DESIGN	CODE LETTER	ENCL.
66	CONT	40/F	1.15	B	G	TEFC
E/S	ROTOR	TEST S.O.	TEST DATE	STATOR RES. @25 °C OHMS (BETWEEN LINES)		
491281	418141005XE	---	---	.101		
PERFORMANCE						
LOAD	HP	AMPERES	RPM	% POWER FACTOR	% EFFICIENCY	
NO LOAD	0	14.9	3600	11.0	0	
1/4	15.0	21.9	3590	72.1	88.8	
2/4	30.0	34.9	3580	86.7	92.9	
3/4	45.0	49.9	3569	90.2	93.8	
4/4	60.0	66.0	3558	90.7	93.7	
5/4	75.0	82.8	3546	90.9	93.3	
SPEED TORQUE						
	RPM	TORQUE % FULL LOAD	TORQUE LB.-FT.	AMPERES		
LOCKED ROTOR	0	203	180	435		
PULL UP	1565	176	156	355		
BREAKDOWN	3397	233	206	212		
FULL LOAD	3558	100	88.6	66.0		
AMPERES SHOWN FOR 460. VOLT CONNECTION. IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE						
REMARKS: TYPICAL DATA XE MOTOR-NEMA NOM. EFF. 93.6 %						
BALDOR			DR. BY W. L. SMITH CR. BY C. E. JAMISON APP. BY E. J. CHRISTIAN DATE 05/04/16			
A MEMBER OF THE ABB GROUP			A-C MOTOR PERFORMANCE DATA A36WG1559-R028 ISSUE DATE 04/28/21			







416820-036

A-C MOTOR
CONNECTION DIAGRAM
STANDARD 3 LEAD CONNECTED



(N.P. 1575-BA)

416820-036

REV. DESC: LOADED TO BUS, C/R 335225		
REV. LTR: -	VERSION: 00	TDR: 000000538207
FILE: \MGA\00000\682		REVISED: 11: 54: 06 04/30/2010
MTL: -		BY: RAGRA

BALDOR

CONN DIAG - STANDARD 3 LEAD
SH 1 of 1