



Customer information packet

VSPM31109

.5HP, 1140RPM, 3PH, 60HZ, 56C, 3436M, ODP, F1, N

Class - None

Division - Not Applicable

Specifications

Enclosure	ODP
Frame	56C
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	WEEE CURUS
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	1.000 A @ 460.0 V 2.000 A @ 230.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	78.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	1.0 a
Insulation Class	F

Part detail

Revision	B
Type	AC
Mech. spec.	34B063
Base	
Status	PRD/A
Elec. spec.	34WGR776
Layout	34LYB063
Eff. date	12-30-2024
CD Diagram	CD0005
Poles	06
Leads	9#18
Proprietary	False
Created date	03-06-2024

Inverter Code	Not Inverter
KVA Code	K
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3436M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	12.63 IN
Power Factor	61
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.25
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1140 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4558A02LL											
CAT #	VSPM31109			WGT	40		LBS				
SER #				ENCL		ODP					
SPEC	34B063R776			CC		010A		IP		23	
HP	.5			NEMA NOM. EFF					78.5		
VOLTS	230/460			PF		61					
AMPS	2/1										
RATING	40C AMB-CONT										
RPM	1140			PH		3		DES		B	
FRAME	56C	HZ	60	CODE		K	CLASS		F		
SER.F.	1.25	SF AMP	2.2/1.1								
DE	6203		ODE	6203							
GREASE	POLYREX EM										
						QR					
YR											

AC Induction Motor Performance Data

Record # 100839

Preliminary Data Sheet

Winding: 34WGR776-R003			Type: 3436M		Enclosure: ODP		
Nameplate Data				460 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		.5		Full Load Torque		2.38 LB-FT	
Volts		230/460		Start Configuration		direct on line	
Full Load Amps		2/1		Breakdown Torque		8.4 LB-FT	
R.P.M.		1140		Pull-up Torque		5.4 LB-FT	
Hz	60	Phase	3	Locked-rotor Torque		6.5 LB-FT	
NEMA Design Code		B	KVA Code	K	Starting Current		5.4 A
Service Factor (S.F.)		1.25		No-load Current		0.73 A	
NEMA Nom. Eff.		78.5	Power Factor	61	Line-line Res. @ 25°C		25.8 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		27°C	
S.F. Amps		2.2/1.1		Temp. Rise @ S.F. Load		67°C	
				Locked-rotor Power Factor		53	
				Rotor inertia		0.0855 lb-ft²	

Load Characteristics 460 V, 60 Hz, 0.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	24	39	52	61	69	74	69
Efficiency	67	77	79.2	78.5	76.5	73.4	76.5
Speed	1185	1171	1156	1137	1117	1091	1117
Line amperes	0.75	0.8	0.89	1	1.13	1.3	1.13

ABB Motors and Mechanical Inc.

WINDING # 34WGR776

Typical performance - not guaranteed values.

0.5 HP 3 PH 60 HZ 1140 RPM 460 V 3436M

TORQUES (LB-FT): PO=8.4 PU=5.4 LR=6.5 LRA=5.4





