



Customer information packet

WCL1409T

5HP, 3450RPM, 1PH, 60HZ, 184TCZ, 3634L, OPEN

Class - None

Division - Not Applicable

Specifications

Enclosure	OPEN
Frame	184TCZ
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Cap Start, Induction Run
Output @ Frequency	5.000 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	24.000 A @ 208.0 V 23.000 A @ 230.0 V
Design Code	L
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	75.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	23.0 a
Insulation Class	F

Part detail

Revision	AH
Type	AC
Mech. spec.	36E775
Base	
Status	PRD/A
Elec. spec.	36WG0190
Layout	36LYE775
Eff. date	05-09-2024
CD Diagram	CD0017A01
Poles	02
Leads	2#10 A PH,2#16 B PH
Proprietary	False
Created date	01-01-0001

Inverter Code	Not Inverter
KVA Code	F
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	2 @ 10 AWG, A PH
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3634L
Mounting Arrangement	F1
Number of Poles	2
Overall Length	19.69 IN
Power Factor	88
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Tapped & Key
Rodent Screen	Included
Service Factor	1.15
Shaft Diameter	0.875 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3450 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1256L									
CAT.NO.	WCL1409T								
SPEC.	36E775-190								
HP	5								
VOLTS	230								
AMP	23								
RPM	3450								
FRAME	184TCZ		HZ	60			PH	1	
SER.F.	1.15		CODE	F	DES	L	CLASS	F	
NEMA-NOM-EFF	75		PF	88					
RATING	40C AMB-CONT								
CC									
DE	6207		ODE	6205					
ENCL	OPEN		SN						

AC Induction Motor Performance Data

Record # 20846

Typical performance - not guaranteed values

Winding: 36WG0190-R002			Type: 3634L	Enclosure: OPEN				
Nameplate Data			230 V, 60 Hz: Single Voltage Motor					
Rated Output (HP)		5	Full Load Torque		7.6 LB-FT			
Volts		230	Start Configuration		direct on line			
Full Load Amps		23	Breakdown Torque		18.7 LB-FT			
R.P.M.		3450	Pull-up Torque		16 LB-FT			
Hz	60	Phase	1	Locked-rotor Torque		18 LB-FT		
NEMA Design Code		L	KVA Code	F	Starting Current		125 A	
Service Factor (S.F.)		1.15	No-load Current		9 A			
NEMA Nom. Eff.		75	Power Factor		88	Line-line Res. @ 25°C		0.338 Ω A Ph 1.16 Ω B Ph
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		75°C		
S.F. Amps				Temp. Rise @ S.F. Load		90°C		

Load Characteristics 230 V, 60 Hz, 5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	59	76	84	88	90	90	0
Efficiency	63	74.5	77.7	78	76.5	73.6	0
Speed	3559	3524	3485	3440	3387	3318	0
Line amperes	10.9	14.3	18.6	23.6	29.6	36.8	27.2

ABB Motors and Mechanical Inc.

WINDING # 36WG0190

Typical performance - not guaranteed values.

5 HP 1 PH 60 HZ 3450 RPM 230 V 3634L

TORQUES (LB-FT): PO=18.7 PU=16 LR=18 LRA=125





