



Customer information packet

XEFRPM36754

75HP, 1800, 460V, HL365T, TEFC, F1

Specifications

Enclosure	TEFC
Frame	HL365T
Frame Material	Exposed Laminations
Frequency	60.00 Hz
Output @ Frequency	75.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	CCSA US NEMA PREMIUM
Auxiliary Box	NO AUXILLARY BOX
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Constant Torque Speed Range	1-60
Current @ Voltage	74.000 A @ 460.0 V
Duty Rating	CONT
Feedback Device	NO FEEDBACK
Frame Prefix	HL
Heater Indicator	No Heater
High Voltage Full Load Amps	74.0 a
Insulation Class	H
KVA Code	G
Motor Standards	NEMA
Mounting Arrangement	F1
Product Family	Fan - Centrifugal
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Service Factor	1.15
Shaft Diameter	2.374 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Speed	1800 rpm

Part detail

Revision	G
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	LS7023A
Layout	619706-001
Eff. date	04-23-2019
CD Diagram	422927-001
Poles	04
Leads	
Proprietary	False
Created date	06-03-2016

Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat

Nameplate

000613007QF

	DUTY	HP	RPM	AMPS	VOLTS	HZ										
	CONT	75	1800	74	460	60										
CAT.NO.	XEFRPM36754		SPEC. NO.		H36-A000-0002											
SER.NO			FRAME SIZE		HL365T		TYPE PSM									
AMB.	40	S.F.	1.15	ENCL.	TEFC	PH	3	DESIGN	B	CODE	G					
NEMA NOM. EFF	97.3	GUARANTEED EFFICIENCY			96.7	POWER FACTOR		99.2	INSUL. CLASS		H					
D.E. BRG.	75BC02J30X		O.D.E. BRG.		55BC02J30X											
VPWM INVERTER DUTY @1.0SF	CHP HZ	60-90		CT HZ	1-60		VT HZ	0-60								
	XT															

000692000VY


MEAS OPEN CIRCUIT VOLTAGE

IS VOLTS AT RPM.

S. O.	FRAME	HP	TYPE	PHASE	HERTZ	RPM
--	HL365T	75	PSM	3	60	1800
VOLTS	AMPS	DUTY	AMB°C	INSUL	S.F.	NEMA DESIGN
460	72.7	CONT	40	H	1.15	B
CODE LETTER	ENCL	ROTOR INERTIA (lb-ft ²)		STATOR RES. @ 25°C OHMS (BETWEEN LINES)		
G	TEFC	9.37		.08626		TYPICAL DATA
PERFORMANCE						
LOAD	HP	AMPERES	RPM	% POWER FACTOR	% EFFICIENCY	
NO LOAD	0	26.3	1800	3.70	N/A	
1/4	18.7	22.3	1800	83.1	94.7	
2/4	37.5	37.0	1800	98.2	96.5	
3/4	56.2	54.5	1800	99.4	97.1	
4/4	74.9	72.7	1800	99.2	97.3	
5/4	93.6	91.4	1800	98.7	97.2	
SPEED TORQUE						
		RPM	TORQUE (% FULL LOAD)	TORQUE (lb-ft)	AMPERES	
LOCKED ROTOR		0	168	366.6	544.0	
PULL OUT		1800	239	523.1	224.7	
FULL LOAD		1800	100	218.6	72.7	
THIS IS A PERMANENT MAGNET MOTOR GENERATED OPEN CIRCUIT LINE-LINE VOLTAGE at 25°C = 21.8 VOLTS PER 100 RPM REMARKS:						
		DR. BY CAD CK. BY REM APP. BY REM DATE 05/25/2016		LSPM MOTOR PERFORMANCE DATA LS7023A ISSUE DATE 05/25/2016		

S.O.	--	HERTZ	60	AMB°C	40	CODE LETTER	G
FRAME	HL365T	RPM	1800	INSUL.	H	WK ² (lb-ft ²)	9.37
HP	75	VOLTS	460	S.F.	1.15	NEMA DESIGN	B
TYPE	PSM	AMPS	72.7	ENCL.	TEFC	STATOR RES. @ 25°C	.08626
PHASE	3	DUTY	CONT			OHMS (BETWEEN LINES)	

Amps & Torque vs. RPM
During Acceleration



TYPICAL DATA




DR. BY _____ CAD
CK. BY _____ RIM
APP. BY _____ RIM
DATE 05/25/2016

ISPM MOTOR
PERFORMANCE
CURVES
ISSUE DATE 05/25/2016
L57023A

S.O.	--	HERTZ	60	AMB°C	40	CODE LETTER	G
FRAME	HL365T	RPM	1800	INSUL.	H	WK ² (lb-ft ²)	9.37
HP	75	VOLTS	460	S.F.	1.15	NEMA DESIGN	B
TYPE	PSM	AMPS	72.7	ENCL.	TEFC	STATOR RES. @ 25°C	.08626
PHASE	3	DUTY	CONT			OHMS (BETWEEN LINES)	

Performance Data vs. HP
At Synchronous Speed




TYPICAL DATA




DR. BY CAD
CK. BY RIM
APP. BY RIM
DATE 05/25/2016

ISPM MOTOR
PERFORMANCE
CURVES
ISSUE DATE
L57/023A
05/25/2016



422927-001



NOTE:
DATA TO BE SIZED
SO THAT IT FITS INTO
MATERIAL DECAL
DIMENSIONS. MAKE
LETTERS & NUMBERS
AS LARGE AS POSSIBLE.

MATERIAL: CERAMATIC DGF-P4
PERMA GRIP ADHESIVE

ALL LETTERS, NUMBERS
AND LINES TO BE BLACK
ON WHITE BACKGROUND.

422927-001

REV. DESC: CHANGE BACKGROUND COLOR FROM GOLD TO WHITE		
REV. LTR: B	VERSION: 02	TDR: 000000788708
FILE: \RGG\00000\203	REVISED: 08:09:29 03/04/2013	
MTL: -	BY: RGGWT	

BALDOR
EXTERNAL CONNECTION LABEL
SH 1 of 1