



Customer information packet

XM181562T

32M 6P XPFC HOR 182T T'STATS INVERTER

Class - CLI GP D; CLII GP F,G

Division - Division I

Specifications

Enclosure	XPFC
Frame	182T
Frame Material	Steel
Frequency	50.00 Hz 60.00 Hz
Haz Area Class and Group	CLI GP D; CLII GP F,G
Haz Area Division	Division I
Motor Letter Type	Three Phase
Output @ Frequency	1.000 HP @ 50 HZ 1.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 380.0 V @ 50 HZ 230.0 V @ 60 HZ 190.0 V @ 50 HZ
Agency Approvals	CSA EEV UL
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	1.8
Current @ Voltage	4.800 A @ 230.0 V 4.200 A @ 190.0 V 2.400 A @ 460.0 V 2.100 A @ 380.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT

Part detail

Revision	E
Type	AC
Mech. spec.	36R726
Base	
Status	PRD/A
Elec. spec.	36WGS916
Layout	36LYR726
Eff. date	04-22-2025
CD Diagram	CD0005
Poles	06
Leads	9#16
Proprietary	False
Created date	12-19-2018

Efficiency @ 100% Load	87.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	2.1 a
Insulation Class	F
Inverter Code	Inverter Duty
IP Rating	NONE
KVA Code	K
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Max Speed	1800 rpm
Motor Lead Quantity/Wire Size	9 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	X3632M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	18.93 IN
Power Factor	67
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS NON-COMPLIANT
Service Factor	1.00
Shaft Diameter	1.125 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1165 rpm

	970 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP0887XPSLEV												
NO.						CC	010A					
S/N						TEMP CODE			T3C			
SPEC.	36R726S916G1					INV.TYPE		PWM				
CAT.NO.	XM181562T					C HP FR	60		C HP TO	90		
HP	1.5//1					CT HZ FROM		1.8		CT HZ TO		60
VOLTS	230/460//190/380					VT HZ FROM		1.8		VT HZ TO		60
AMPS	4.8/2.4//4.2/2.1				MAG CUR	3/1.5						
RPM	1165//970				MX RPM	1800						
HZ	60//50		PH	3	CL	F	NOM.EFF.		87.5			
SER.F.	1.00		DES	B	SL HZ	1.8	WK2	0.301				
FRAME	182T		RATING		40C AMB-CONT							
	55C AMB AT 1.00 SF SINEWAVE											
	NEMA MG-1 PART 5, IP54					1.15 SF SINEWAVE						

AC Induction Motor Performance Data

Record # 73918

Typical performance - not guaranteed values

Winding: 36WGS916-R035		Type: 3632M	Enclosure: XPFC		
Nameplate Data		460 V, 60 Hz: High Voltage Connection			
Rated Output (HP)	1.5//1	Full Load Torque	6.86 LB-FT		
Volts	230/460//190/380	Start Configuration	direct on line		
Full Load Amps	4.8/2.4//4.2/2.1	Breakdown Torque	23.8 LB-FT		
R.P.M.	1165//970	Pull-up Torque	12.5 LB-FT		
Hz	60//50	Phase	3	Locked-rotor Torque	15.3 LB-FT
NEMA Design Code	B	KVA Code	K	Starting Current	15.8 A
Service Factor (S.F.)			1	No-load Current	1.47 A
NEMA Nom. Eff.	87.5	Power Factor	67	Line-line Res. @ 25°C	7.12 Ω
Rating - Duty	40C	AMB-CONT		Temp. Rise @ Rated Load	34°C
				Locked-rotor Power Factor	30.1
				Rotor inertia	0.301 LB-FT2

Load Characteristics 460 V, 60 Hz, 1.5 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	30	48	60	67	71	74
Efficiency	78.8	85.7	87.6	87.4	86.4	85.4
Speed	1192	1185	1177	1168	1158	1148
Line amperes	1.57	1.77	2.07	2.43	2.88	3.36

ABB Motors and Mechanical Inc.

WINDING # 36WGS916

Typical performance - not guaranteed values.

1.5 HP 3 PH 60 HZ 1168 RPM 460 V 3632M

TORQUES (LB-FT): PO=23.8 PU=12.5 LR=15.3 LRA=15.8





