



Customer information packet

XM18322T

22M 2P XPFC HOR 182T T'STATS INVERTER

Class - CLI GP D; CLII GP F,G

Division - Division I

Specifications

Enclosure	XPFC
Frame	182T
Frame Material	Steel
Frequency	50.00 Hz 60.00 Hz
Haz Area Class and Group	CLI GP D; CLII GP F,G
Haz Area Division	Division I
Motor Letter Type	Three Phase
Output @ Frequency	3.000 HP @ 60 HZ 2.000 HP @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	190.0 V @ 50 HZ 230.0 V @ 60 HZ 380.0 V @ 50 HZ 460.0 V @ 60 HZ
Agency Approvals	CSA EEV UL
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	2.5
Current @ Voltage	3.000 A @ 380.0 V 3.700 A @ 460.0 V 6.000 A @ 190.0 V 7.400 A @ 230.0 V 8.000 A @ 208.0 V
Design Code	A
Drip Cover	No Drip Cover

Part detail

Revision	F
Type	AC
Mech. spec.	36R726
Base	
Status	PRD/A
Elec. spec.	36WGS041
Layout	36LYR726
Eff. date	09-30-2025
CD Diagram	CD0005
Poles	02
Leads	9#16
Proprietary	False
Created date	12-19-2018

Duty Rating	CONT
Efficiency @ 100% Load	86.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	3.0 a
Insulation Class	F
Inverter Code	Inverter Duty
IP Rating	NONE
KVA Code	K
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Max Speed	5400 rpm
Motor Lead Quantity/Wire Size	9 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	X3622M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	17.42 IN
Power Factor	91
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS NON-COMPLIANT
Service Factor	1.00
Shaft Diameter	1.125 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger

Speed	2890 rpm
	3450 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP0887XPSLEV												
NO.						CC	010A					
S/N						TEMP CODE		T3C				
SPEC.	36R726S041G1					INV.TYPE		PWM				
CAT.NO.	XM18322T					C HP FR		60	C HP TO		90	
HP	3//2					CT HZ FROM		2.5	CT HZ TO		60	
VOLTS	230/460//190/380					VT HZ FROM		2.5	VT HZ TO		60	
AMPS	7.4/3.7//6/3				MAG CUR	2.4/1.2						
RPM	3450//2890				MX RPM	5400						
HZ	60//50	PH	3	CL	F	NOM.EFF.	86.5					
SER.F.	1.00	DES	A	SL HZ	2.5	WK2	0.1					
FRAME	182T	RATING		40C AMB-CONT								
	55C AMB AT 1.00 SF SINEWAVE											
	NEMA MG-1 PART 5, IP54				1.15 SF SINEWAVE							

AC Induction Motor Performance Data

Record # 73670

Typical performance - not guaranteed values

Winding: 36WGS041-R041		Type: 3622M	Enclosure: XPFC			
Nameplate Data		460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)	3//2	Full Load Torque	4.7 LB-FT			
Volts	230/460//190/380	Start Configuration	direct on line			
Full Load Amps	7.4/3.7//6/3	Breakdown Torque	19.7 LB-FT			
R.P.M.	3450//2890	Pull-up Torque	12 LB-FT			
Hz	60//50	Phase	3	Locked-rotor Torque	14.1 LB-FT	
NEMA Design Code	A	KVA Code	K	Starting Current	33.3 A	
Service Factor (S.F.)	1	No-load Current	1.17 A			
NEMA Nom. Eff.	86.5	Power Factor	91	Line-line Res. @ 25°C	4.71 Ω	
Rating - Duty	40C	AMB-CONT	Temp. Rise @ Rated Load			52°C
			Locked-rotor Power Factor			48.4
			Rotor inertia			0.0984 LB-FT ²

Load Characteristics 460 V, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	66	82	88	91	92	93
Efficiency	80.3	86	87.3	86.9	86	84.5
Speed	3565	3535	3504	3472	3434	3394
Line amperes	1.56	2.17	2.93	3.67	4.57	5.5

ABB Motors and Mechanical Inc.

WINDING # 36WGS041

Typical performance - not guaranteed values.

3 HP 3 PH 60 HZ 3472 RPM 460 V 3622M

TORQUES (LB-FT): PO=19.7 PU=12 LR=14.1 LRA=33.3





