



Customer information packet

XM25222T

50M 2P XPFC HOR 256T T'STATS INV DUTY

Class - CLI GP D; CLII GP F,G

Division - Division I

Specifications

Enclosure	XPFC
Frame	256T
Frame Material	Iron
Frequency	50.00 Hz 60.00 Hz
Haz Area Class and Group	CLI GP D; CLII GP F,G
Haz Area Division	Division I
Motor Letter Type	Three Phase
Output @ Frequency	20.000 HP @ 60 HZ 15.000 HP @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	190.0 V @ 50 HZ 230.0 V @ 60 HZ 380.0 V @ 50 HZ 460.0 V @ 60 HZ
Agency Approvals	CSA EEV UL
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	30
Current @ Voltage	20.000 A @ 380.0 V 22.000 A @ 460.0 V 40.000 A @ 190.0 V 44.000 A @ 230.0 V 48.000 A @ 208.0 V
Design Code	A
Drip Cover	No Drip Cover

Part detail

Revision	L
Type	AC
Mech. spec.	09E270
Base	
Status	PRD/A
Elec. spec.	09WGZ651
Layout	09LYE270
Eff. date	11-14-2023
CD Diagram	CD0180
Poles	02
Leads	9#10
Proprietary	False
Created date	03-27-2019

Duty Rating	CONT
Efficiency @ 100% Load	91.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	20.0 a
Insulation Class	F
Inverter Code	Inverter Duty
IP Rating	NONE
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	5400 rpm
Motor Lead Quantity/Wire Size	9 @ 10 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	X0950M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	25.50 IN
Power Factor	91
Product Family	Hazardous Location Motor
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	None
Rodent Screen	None
RoHS Status	ROHS NON-COMPLIANT
Service Factor	1.15
Shaft Diameter	1.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger

Speed	2930 rpm
	3530 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP0887XPSLEV												
NO.						CC	010A					
S/N						TEMP CODE		T3C				
SPEC.	09E270Z651G1					INV.TYPE		PWM				
CAT.NO.	XM25222T					C HP FR		60		C HP TO		90
HP	20//15					CT HZ FROM		30		CT HZ TO		60
VOLTS	230/460//190/380					VT HZ FROM		6		VT HZ TO		60
AMPS	44/22//40/20				MAG CUR	11.6/5.8						
RPM	3530//2930				MX RPM	5400						
HZ	60//50		PH	3	CL	F	NOM.EFF.		91			
SER.F.	1.15		DES	A	SL HZ	1.2		WK2	1.28			
FRAME	256T		RATING		40C AMB-CONT							
	55C AMB @1.0SF ON VFD,60C RISE											
	NEMA MG-1 PT.5,IP54											

AC Induction Motor Performance Data

Record # 54030

Typical performance - not guaranteed values

Winding: 09WGZ651-R015			Type: 0950M		Enclosure: XPFC			
Nameplate Data				460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		20//15		Full Load Torque		30 LB-FT		
Volts		230/460//190/380		Start Configuration		direct on line		
Full Load Amps		44/22//40/20		Breakdown Torque		167 LB-FT		
R.P.M.		3530//2930		Pull-up Torque		33.7 LB-FT		
Hz		60//50	Phase	3	Locked-rotor Torque		51 LB-FT	
NEMA Design Code		A	KVA Code		H	Starting Current		160 A
Service Factor (S.F.)		1.15		No-load Current		5.75 A		
NEMA Nom. Eff.		91	Power Factor		91	Line-line Res. @ 25°C		0.43337 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		58°C		
S.F. Amps				Temp. Rise @ S.F. Load		72°C		

Load Characteristics 460 V, 60 Hz, 20 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	65	83	89	91	91	91	91
Efficiency	89.4	92.7	92.9	92.4	91.4	90.1	91.8
Speed	3580.7	3566.7	3547.3	3526.6	3504.5	3479.4	3513
Line amperes	8.04	12.2	17.1	22.4	28.2	34.2	25.9


ABB Motors and Mechanical Inc.

WINDING # 09WGZ651

Typical performance - not guaranteed values.

20 HP 3 PH 60 HZ 3526.6 RPM 460 V 0950M

TORQUES (LB-FT): PO=167 PU=33.7 LR=51 LRA=160



AC Induction Motor Performance Data

Record # 54031

Typical performance - not guaranteed values

Winding: 09WGZ651-R015		Type: 0950M	Enclosure: XPFC		
Nameplate Data		380 V, 50 Hz: High Voltage Connection			
Rated Output (HP)	20//15	Full Load Torque	27 LB-FT		
Volts	230/460//190/380	Start Configuration	direct on line		
Full Load Amps	44/22//40/20	Breakdown Torque	160 LB-FT		
R.P.M.	3530//2930	Pull-up Torque	35.6 LB-FT		
Hz	60//50	Phase	3	Locked-rotor Torque	53.9 LB-FT
NEMA Design Code	A	KVA Code	H	Starting Current	156 A
Service Factor (S.F.)	1.15			No-load Current	5.7 A
NEMA Nom. Eff.	91	Power Factor	91	Line-line Res. @ 25°C	0.41 Ω
Rating - Duty	40C	AMB-CONT	Temp. Rise @ Rated Load		51°C
S.F. Amps			Temp. Rise @ S.F. Load		64°C
				Locked-rotor Power Factor	31.3
				Rotor inertia	1.28 LB-FT2

Load Characteristics 380 V, 50 Hz, 15 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	63	82	88	91	91	92	91
Efficiency	86.8	91.6	91.6	91.2	90.3	89.1	90.6
Speed	2982	2969	2952	2933	2914	2891	2922
Line amperes	7.7	11.5	15.8	20.6	25.9	31.3	23.8

ABB Motors and Mechanical Inc.

WINDING # 09WGZ651

Typical performance - not guaranteed values.

15 HP 3 PH 50 HZ 2933 RPM 380 V 0950M

TORQUES (LB-FT): PO=160 PU=35.6 LR=53.9 LRA=156

